



FW3D10/75/TP40/75/STXX

MODEL: TP

PREPARED BY: _____

TYPE: _____

JOB NAME: _____

DATE: _____

CERTIFICATION: UL Listed NSF Approved

FINISH – Five stage pretreatment process, coated with a lead free TGI C polyester powder coat finish. Some finish options are not available for certain shades. Custom colors and Marine options are available upon request.

MOUNTING – Customizable: choose finish, length, stem length, and distance between shades (minimum 8” with 275watt, 10” with 375watt).

REFLECTOR – Choose shade style, shade finish and number of shades.
Spun from heavy gauge 1100-0 aluminum, ranging in thickness from .050 to .125. Copper is spun from .040 gauge and 110 soft alloy. Brass is spun from .40 gauge.

MODEL #	FINISH	LIGHT SOURCE				MOUNTING OPTIONS	ACCESSORIES
TP	18, 21P, 22P, 41, 41.5, 42, 43, 44, 45, 46, 48, 49, 50, 51, 52, 53, 54, 55, 59, 60, 61, 62, 63, 74, 75, 76, 77, 78, 79, 80, 81, 82, 85, 86, 87, 89, 90, 91, 92, 93, 95, 96, 97, 98	250WRC					TSF ² TSR
		250WCC					
		250WRU ¹					
		250WCU ¹					
		375WRC					
		375WCC					
		375WRU ¹					
		375WCU ¹					

1. not NSF approved. 2. not available with 375 watt bulb.

.SUBJECT TO MODIFICATION WITHOUT NOTICE.



BASELITE CORPORATION
12260 EAST END AVE.
CHINO, CA 91710

PH: 877-999-1990
WEB: WWW.BASELITE.COM
EMAIL: SALES@BASELITE.COM

