



# BASELITE – SCHOOLHOUSE - SPECIFICATION SHEET



PROJECT NAME: \_\_\_\_\_ PROJECT TYPE: \_\_\_\_\_

MODEL #	/	/	/	/	/	/	/	/	/
EXAMPLE:	SCP	PSTL	41.5	ST18	STC	41.5	12LED	3K	LDM120

NOTES:

---



---



---



## A - SHADES

### SCHOOL HOUSE

- SKT
- SCF
- SCFS
- FNF
- FNP
- SCP
- SCPC
- SCPL
- DLP
- DNF
- S2R8

## B – GLASS OPTIONS

### 6" FITTER

- SCH12, SCH14, SCH16, SCH18, SCO12, SHO14, SHO16, SHO18, SOB12, SOB14, SOB16, SOB18, PSGN, PSRD, PSTL, PSYG

### 4" FITTER

- PSBL, AC
- 4" THREADED FITTER**
- BAF.PSGN, BAF.PSRD, BAF.PSTL, BAF.PSBL

## C - FINISH OPTIONS

(SEE WEBSITE FOR SWATCH COLORS)  
(\*SEE NOTES FOR LIMITATIONS\*)

- 14, 15, 16, 17, 18, 19, 19P, 20, 20P, 20PB, 20SB, 21, 21P, 22, 22P, 23, 23P, 38, 39, 40, 41, 41.5, 43, 44, 48, 49, 50, 51, 52, 53, 55, 57, 58, 59, 61, 62, 63, 78, 80, 81, 82, 85, 86, 87, 89, 91, 92, 94, 95, 97, 98, 99, 100

## D – MOUNTING OPTIONS

- BLC – 8' BLACK CORD
- WHC – 8' WHITE CORD
- LBLC – 8' LED BLACK CORD
- LWHC – 8' LED WHITE CORD
- STXX – STEM (XX=STEM LENGTH)

## E – MOUNTING ADD-ONS

- SLC ½" – SLOPE CEILING CANOPY ½"
- STC ½" – STEM CANOPY ½"
- LSLC ½" – LED SLOPE CEILING CANOPY ½"
- LSTC ½" – LED STEM CANOPY ½"

## F – MOUNTING COLOR

\*SEE SECTION "C" FOR MOUNTING COLOR OPTIONS.

## G – LIGHT SOURCE

- INCANDESCENT (INC)**
- 100W
- COMPACT FLOURESCENT (CF)**
- 26W
- 32W
- 42W
- LIGHT EMITTED DIODE (LED)**
- 25W

## H – LED COLOR

(ONLY APPLICABLE FOR LED LIGHT SOURCE. SKIP THIS SECTION IF OPTION DOES NOT APPLY.)

- 27K – 2700 K
- 3K – 3000 K
- 35K – 3500 K
- 4K – 4000 K
- 5K – 5000 K

## I – ELECTRICAL OPTIONS

- LDM120
- LDM277
- LDM0-10

## NOTES



\*ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.)

\*FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY


\*FINISH OPTIONS 19, 21, 22, 23 ARE AN ACID FINISH AND IS APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.

\*FINISH OPTIONS 61 & 62 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.


\*FIXTURE DIMENSIONS MAY VARY ± 0.25"




\*FLUSH MOUNT, MOUNTING OPTIONS DO NOT APPLY




\*FLUSH MOUNT, MOUNTING OPTIONS DO NOT APPLY




**FNP** H-8" W-13"




**SCP** H-6" W-5.5"




**DPL** H-10" W-6"




\*FLUSH MOUNT, MOUNTING OPTIONS DO NOT APPLY



**SCPL** H-29.25" W-20.5"



**S2R8** H-2.5" W-4.5"



**SCPC** H-3" W-6"



**B – GLASS OPTIONS**

\*NOTE – THE LIST OF "SHADES" ARE ALL APPLICABLE WITH THE GLASS OPTIONS SHOWN IN THIS SECTION.

**6" FITTER  
SHADES**

- SCF
- SCFS
- SCP
- SCPC
- SCPL
- DLP
- DNF



**SHC12** – 12" CLEAR GLASS  
**SHC14** – 14" CLEAR GLASS  
**SHC16** – 16" CLEAR GLASS  
**SHC18** – 18" CLEAR GLASS



**SHO12** – 12" OPAL GLASS  
**SHO14** – 14" OPAL GLASS  
**SHO16** – 16" OPAL GLASS  
**SHO18** – 18" OPAL GLASS



**SOB12** – 12" SLANT OPAL  
**SOB14** – 14" SLANT OPAL  
**SOB16** – 16" SLANT OPAL  
**SOB18** – 18" SLANT OPAL



**PSGN**  
 12" OPAL GLASS  
 WITH LIME GREEN AND BLACK  
 PINSTRIPE HAND-PAINTED LINES



**PSRD**  
 12" OPAL GLASS  
 WITH RED-ORANGE AND BLACK  
 PINSTRIPE HAND-PAINTED LINES



**PSTL**  
 12" OPAL GLASS  
 WITH TEAL AND BLACK  
 PINSTRIPE HAND-PAINTED LINES



**PSGY**  
 12" OPAL GLASS  
 WITH GREY PINSTRIPE  
 HAND-PAINTED LINES

\*NOTE – THE LIST OF "SHADES" ARE ALL APPLICABLE WITH THE GLASS OPTIONS SHOWN IN THIS SECTION.

**4" FITTER  
SHADES**

- FNF
- FNP
- S2R8



**PSBL**  
 8" OPAL GLASS  
 WITH NAVY BLUE AND BLACK  
 PINSTRIPE HAND-PAINTED LINES



**AC**  
 7" CLEAR TEXTURED  
 ACORN GLASS

\*NOTE – THE LIST OF "SHADES" ARE ALL APPLICABLE WITH THE GLASS OPTIONS SHOWN IN THIS SECTION.

**4" THREADED  
FITTER  
SHADES**

- SKT



**BAF.PSGN**  
 8" OPAL GLASS  
 WITH LIME GREEN PINSTRIPE  
 HAND-PAINTED LINES



**BAF.PSRD**  
 8" OPAL GLASS  
 WITH RED-ORANGE PINSTRIPE  
 HAND-PAINTED LINES



**BAF.PSTL**  
 8" OPAL GLASS  
 WITH TEAL PINSTRIPE  
 HAND-PAINTED LINES



**BAF.PSBL**  
 8" OPAL GLASS  
 WITH NAVY BLUE PINSTRIPE  
 HAND-PAINTED LINES




**D - MOUNTING OPTIONS**

**STEM MOUNTS**

\*STEMS RATED FOR DAMP LOCATION    \*AVAILABLE MODELS FOR LED    \*CANOPY NOT INCLUDED, ADD IN SECTION D

**\*AVAILABLE MODELS FOR THE 1/4" STEM OPTION**

**SKT**  
**S2R8**




**ST(XX)**    STEM- 1/4" NPT

XX = LENGTH OF STEM  
(EXAMPLE – "ST18" = STEM MOUNT 18" LENGTH)  
\*CANOPY NOT INCLUDED, ADD IN SECTION E

**\*AVAILABLE MODELS FOR THE 1/2" STEM OPTION**

**SCP**  
**DPL**  
**FNP**



**ST(XX)**    STEM- 1/2" NPT

XX = LENGTH OF STEM  
(EXAMPLE – "ST18" = STEM MOUNT 18" LENGTH)  
\*CANOPY NOT INCLUDED, ADD IN SECTION E

**INCANDESCENT CORD MOUNTS**

\*CORDS RATED FOR DRY LOCATION    \*CANOPY DIMENSIONS: .625" (H) 5.25" (W)

**\*AVAILABLE MODELS FOR INC CORD OPTION**

**SCP**  
**SKT**  
**S2R8**




**BLC**    8' BLACK CORD (INCLUDES INC CANOPY)  
**WHC**    8' WHITE CORD (INCLUDES INC CANOPY)

**L.E.D. AND CF CORD MOUNTS**

FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY. \*CORDS RATED FOR DRY LOCATION \*CANOPY DIMENSIONS: 3" (H) 6" (W)

**\*AVAILABLE MODELS FOR LED CORD OPTION**


**SCP**  
**SKT**  
**S2R8**




**LBLC**    8' BLACK CORD (INCLUDES LED CANOPY)  
**LWHC**    8' WHITE CORD (INCLUDES LED CANOPY)

**E - MOUNTING ADD-ONS**

**INCANDESCENT 1/2" STEM ADD-ONS**




**SLC 1/2" - SLOPE CEILING CANOPY 1/2"**  
\*(Slopes To 20 Degrees)




**STC 1/2" - STEM MOUNT CANOPY 1/2"**

**L.E.D. AND CF 1/2" STEM ADD-ONS**

\* FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY.



**LSLC 1/2" LED SLOPE CEILING CANOPY 1/2"**  
\*(Slopes To 20 Degrees)



**LSTC 1/2" LED STEM MOUNT CANOPY 1/2"**





**G – LIGHT SOURCE**

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

OPTION	WATTAGE	LUMEN	CRI	VOLTAGE	DIMMING
<b>LIGHT EMITTING DIODE (LED)</b>					
LED12W	12W	1000	1200	>90	120-277 VAC
LED25W	25W	1900	2000	>90	120-277 VAC
		@3000K	@5000K		SEE SECTION "F"
<p><b>*IMPORTANT – FOR LIGHT EMITTED DIODE (LED) LIGHT SOURCE OPTION, FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE RIGHT.</b></p> <p>EXAMPLE: / LED25W /</p>		<p><b>LED 12W - SKT, SCF12, SCFS12, FNF12, DLP12, S2R8</b> <b>LED 25W (MAX) - SKT, SCF12, SCFS12, FNF12, DLP12, S2R8</b></p>			

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
<b>INCANDESCENT (INC) <small>MED E26</small></b>					
100WINC	100W	PER BULB SPECS	>90	120-277 VAC	N/A
<p><b>*IMPORTANT – FOR INCANDESCENT (INC) LIGHT SOURCE OPTION, FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE RIGHT.</b></p> <p>EXAMPLE: / INC100W /</p>		<p><b>INC 100W(MAX) - SKT, SCF12, SCFS12, FNF12, DLP12, S2R8</b></p>			

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
<b>COMPACT FLOURESCENT (CF)</b>					
CF26W	26W	PER BULB SPECS	>90	120-277 VAC	N/A
CF32W	32W	PER BULB SPECS	>90	120-277 VAC	N/A
CF42W	42W	PER BULB SPECS	>90	120-277 VAC	N/A
<p><b>*IMPORTANT – FOR COMPACT FLOURESCENT (CF) LIGHT SOURCE, FIXTURES ARE LIMITED DUE TO THE SIZE OF THE SHADE. PLEASE SEE THE CHART TO THE RIGHT TO SEE WHAT WATTAGE IS COMPARABLE FOR EACH FIXTURE WHEN ORDERING.</b></p> <p>EXAMPLE: / CF42W /</p>		<p><b>CF 26W, 32W, OR 42(MAX) - SKT, SCF12, SCFS12, FNF12, DLP12, S2R8</b></p>			

**I – ELECTRICAL OPTIONS**

MOST BASELITE'S ELECTRICAL OPTIONS ARE ONLY COMPATIBLE FOR CERTAIN FIXTURES. PLEASE SEE NOTES BELOW AND FOR FURTHER DEATIALS CONTACT THE FACTORY. FOR DIMMING BALLAST OPTION PLEASE CHOOSE MARK X OR MARK VII, SO RESTRICTIONS APPLY DUE TO THE SIZE OF THE BALLAST AND FIXTURE.

**LED DIMMING OPTIONS**

FOR TRIAC OR 0-10V OPTOIN CHOOSE FROM THE FOLLOWING. CONTACT DRIVER MANUFACTURER FOR SPECIFICATIONS.

- LDM120** - TRIAC DIMMING AT 120 VOLT
- LDM277** - TRIAC DIMMING AT 277 VOLT
- LDM0-10V** - 0 – 10v