



# BASELITE - BOLLARDS – INC – SPECIFICATION SHEET



PROJECT NAME: \_\_\_\_\_ PROJECT TYPE: \_\_\_\_\_

MODEL #	/ / X / X / X / X / X / X / X / / X / X
	A B C D E F G H I J K
EXAMPLE:	BOL1 41 150INC CL

\*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES:

---



---



---



## A - SHADES

- BOLLARDS**  
**BOL1** - 150WINC (MAX)  
**SBOL1** - 150WINC (MAX)  
**BOL4** - 150WINC (MAX)  
**BOL5** - 150WINC (MAX)  
**BOL6** - 150WINC (MAX)  
**BOL7** - 150WINC (MAX)  
**BOL8** - 150WINC (MAX)  
**BOL12** - 150WINC (MAX)  
**BOL14** - 150WINC (MAX)  
**BOL15** - 150WINC (MAX)

## B - FINISH OPTIONS

(SEE WEBSITE FOR SWATCH COLORS)  
 (\*SEE NOTES FOR LIMITATIONS\*)  
 14, 15, 16, 17, 18, 19, 19P, 20, 20P, 20PB,  
 20SB, 21, 21P, 22, 22P, 23, 23P, 38, 39, 40,  
 41, 41.5, 42, 43, 44, 45, 46, 48, 49, 50, 51,  
 52, 53, 54, 55, 57, 58, 59, 60, 61, 62, 63, 64,  
 65, 66, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79,  
 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91,  
 92, 93, 94, 95, 96, 97, 98, 99, 100, MG.

## C – MOUNTING OPTIONS

N/A

## D – MOUNTING ADD-ONS

N/A

## E – MOUNTING COLOR

N/A

## F – LIGHT SOURCE

(SEE PAGE 2 FOR WATTAGE LIMITATIONS)  
**INCANDESCENT (INC)**  
 150INC

## G – LED COLOR TEMP

NOT AVAILABLE

## H – ELECTRICAL OPTION

NOT AVAILABLE

## I – GLASS OPTIONS

(SEE CHART ON PAGE 2 FOR GLASS OPTION LIMITATIONS\*)  
 CL – CLEAR GLASS  
 FR – FROSTED GLASS  
 TYPE 3 – 2.75 WIDTH TO HEIGHT RATIO  
 TYPE 5 – CIRCULAR LIGHT DISTRIBUTION

## J – ACCESSORIES

N/A

## K – ACCESSORY COLOR

N/A

## NOTES

- (1). FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY.
  - (2). FINISH OPTIONS 19, 21, 22, 23, 75, 76, 77, 83, 84, 88, 93 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.
  - (3). FINISH OPTIONS 19, 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.
  - (4). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.
- \*ALL FIXTURES MOUNT TO A 4-O JUNCTION BOX.  
 \*FIXTURE DIMENSIONS MAY VARY ± 0.25.



	HEIGHT(A)	WIDTH(B)
<b>BOL1</b>	43"	6"
<b>BOL4</b>	43"	7"
<b>BOL5</b>	43"	7"
<b>BOL6</b>	43"	7"




	HEIGHT(A)	WIDTH(B)
<b>BOL12</b>	43"	6"
<b>BOL14</b>	43"	6"
<b>BOL15</b>	43"	6"



	HEIGHT(A)	WIDTH(B)
<b>BOL7</b>	43"	13.5"
<b>BOL8</b>	43"	15"



	HEIGHT(A)	WIDTH(B)
<b>BOL7</b>	43"	13.5"
<b>BOL8</b>	43"	15"



	HEIGHT(A)	WIDTH(B)
<b>SBOL1</b>	40"	6"



# BASELITE – BOLLARDS – INC – SPECIFICATION SHEET

## F – LIGHT SOURCE

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

### INCANDESCENT (INC) E26 BASE

**INC 150W (MAX)** - BOL1, SBOL1, BOL4, BOL5, BOL6, BOL7, BOL8, BOL12, BOL14, BOL15

**\*IMPORTANT** – FOR LIGHT EMITTED DIODE (LED) LIGHT SOURCE OPTION FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE LEFT.

EXAMPLE: / 150INC /

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
150WINC	150W	PER BULB SPECS	>90	120-277 VAC	N/A

## I – GLASS OPTIONS

\*NOTE: SEE GLASS OPTION CHART BELOW FOR AVAILABLE GLASS OPTIONS PER FIXTURE SELECTION.

	CLEAR GLASS	FROSTED GLASS	TYPE 3	TYPE 5
BOL1	YES	YES	NO	NO
SBOL1	NO	NO	NO	NO
BOL4	NO	NO	YES	YES
BOL5	NO	NO	NO	NO
BOL6	NO	NO	NO	NO
BOL7	NO	NO	NO	NO
BOL8	NO	NO	NO	NO
BOL12	NO	NO	NO	NO
BOL14	YES	YES	NO	NO
BOL15	YES	YES	NO	NO