



BASELITE – WOOD HANDLE – LED– SPEC SHEET



PROJECT NAME: _____ PROJECT TYPE: _____

MODEL #	/	/	/	x	/	/	/	/	/	/	/
	A	B	C	D	E	F	G	H	I	J	K
EXAMPLE:	W513	41	BLC	BB	43	12W	27K	-	-	44	LDM120

NOTES:



TRD.WH3.54.BLC.BB.100INC

A - SHADES

WOOD HANDLE

- TRD.WH3 - 25WLED(MAX)
- TR.WH3 - CALL MANUFACTURER
- TR2.WH3 - CALL MANUFACTURER
- CNW18.WH4 - 25WLED(MAX)
- W513.WH - 12WLED(MAX)
- CGBW10.WH2 - CALL MANUFACTURER
- SCPW10.WH2 - CALL MANUFACTURER
- S5.CA57.WH1 - CALL MANUFACTURER
- S3.GS08.WH1 - CALL MANUFACTURER
- S3.WG6.WH1 - CALL MANUFACTURER

B - FINISH OPTIONS

- (SEE WEBSITE FOR SWATCH COLORS)
(*SEE NOTES FOR LIMITATIONS*)
- 14, 15, 16, 17, 18, 19, 19P, 20, 20P, 20PB, 20SB, 21, 21P, 22, 22P, 23, 23P, 38, 39, 40, 41, 41.5, 42, 43, 44, 45, 46, 48, 49, 50, 51, 52, 53, 54, 55, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, MG.

C – MOUNTING OPTIONS

LED CORD MOUNT

LBLC, LWHC

D – MOUNTING ADD-ONS

BB

E – MOUNTING COLOR

SEE SECTION “B” FOR COLOR OPTIONS.

F – LIGHT SOURCE

LIGHT EMITTED DIODE (LED)
12W, 25W

G – LED COLOR

- (ONLY APPLICABLE FOR LED LIGHT SOURCE. SKIP THIS SECTION IF OPTION DOES NOT APPLY.)
- 27K – 2700 K ⁽⁶⁾
- 3K – 3000 K
- 35K – 3500 K
- 4K – 4000 K
- 5K – 5000 K ⁽⁶⁾

H – GLASS OPTION

CERTAIN FIXTURES AVAILABLE UPON REQUEST, CALL FACTORY FOR DETAILS.

I - ACCESSORIES

CERTAIN FIXTURES AVAILABLE UPON REQUEST, CALL FACTORY FOR DETAILS.

J – ACCESSORY COLOR

SEE SECTION “B” FOR COLOR OPTIONS.

K – ELECTRICAL OPTION

- LDM120
- LDM277
- LDM0-10

NOTES

- (1). FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY.
 - (2). FINISH OPTIONS 19, 21, 22, 23, 75,76, 77, 83, 84, 88, 93 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.
 - (3). FINISH OPTIONS 19, 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE.
 - (4). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.
 - (5). COLOR CORDS ARE NOT APPLICABLE FOR LED OPTIONS.
- *ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.).
- *ALL FIXTURES MOUNT TO A 4-O JUNCTION BOX.
- *FIXTURE DIMENSIONS MAY VARY ± 0.25.
- *CORD AND CANOPY COME IN THE SAME COLOR.




A – SHADES

WOOD HANDLE SHADE SERIES

*FIXTURE COMES AS SHOWN WITH WOOD HANDLE


* CUSTOM FIXTURES AVAILABLE UPON REQUEST, CALL FACTORY FOR DETAILS.




TRD.WH3 H-13" W-9"

TR.WH3 H-13" W-9"


*TRD- ALUMINUM SHADE
*TR- GLASS SHADE




TR2.WH3 H-15.5" W-12"




CNW18.WH4 H-20" W-18"




CGBW10.WH2 H-13.5" W-9.5"




W513.WH3 H-11" W-13"




SCPW10.WH2 H-10.5" W-10"



S5.CA57.WH1 H-14.5" W-6"



S3.GS08.WH1 H-14" W-8"




S3.WG6.WH1 H-14" W-5"



C - MOUNTING OPTIONS

LED CORD MOUNTS

*FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY.
*CORDS RATED FOR DRY LOCATION *CANOPY DIMENSIONS: 3" (H) 6" (W) *CORD AND CANOPY COME IN THE SAME COLOR.




LBLC 8' BLACK CORD (INCLUDES LED CANOPY)
LWHC 8' WHITE CORD (INCLUDES LED CANOPY)

NOTES:
*DISTANCE TO LAMP (CF) 10'
*All compact fluorescent and LED housings may vary in size according to light source chosen.

D - MOUNTING ADD-ONS

CORD ADD-ONS

* CORDS COMES STANDARD WITH A PLASTIC BUSHING IF BRASS BUSHING IS NOT DESIRED



BB BRASS BUSHING

F – LIGHT SOURCE

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

LIGHT EMITTING DIODE (LED)

LED 12W (MAX)- W513.WH3
LED 25W (MAX)- TRD.WH3, CNW18.WH4
CALL MANUFACTURER- TR.WH3, TR2.WH3, CGBW10.WH2, SCPW10.WH2, S5.CA57.WH1, S3.GS08.WH1, S3.WG6.WH1

***IMPORTANT –** FOR LIGHT EMITTED DIODE (LED) LIGHT SOURCE OPTION FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE LEFT.

EXAMPLE: / LED25W /

OPTION	WATTAGE	LUMENS		CRI	VOLTAGE	DIMMING
LED12W	12W	1000	1200	>90	120-277 VAC	0-10V
LED25W	25W	1900	2000	>90	120-277 VAC	0-10V
		@3000K	@5000K			

K – ELECTRICAL OPTION

MOST BASELITE'S ELECTRICAL OPTIONS ARE ONLY COMPATIBLE FOR CERTAIN FIXTURES. PLEASE SEE NOTES BELOW AND FOR FURTHER DEATIALS CONTACT THE FACTORY.FOR DIMMING BALLAST OPTION PLEASE CHOOSE MARK X OR MARK VII, SO RESTRICTIONS APPLY DUE TO THE SIZE OF THE BALLAST AND FIXTURE.

LED DIMMING OPTIONS

FOR TRIAC OR 0-10V OPTOIN CHOOSE FROM THE FOLLOWING. CONTACT DRIVER MANUFACTURER FOR SPECIFICATIONS.

- LDM120** - TRIAC DIMMING AT 120 VOLT
- LDM277** - TRIAC DIMMING AT 277 VOLT
- LDM0-10V** – 0 – 10v