



BASELITE – SCHOOLHOUSE - SPECIFICATION SHEET



PROJECT NAME: _____ PROJECT TYPE: _____

MODEL #	/	/	/	/	/	/	/	/	/
EXAMPLE:	SCP	PSTL	41.5	ST18	STC	41.5	12LED	3K	LDM120

NOTES:



SCFS/PSTL/41.5/12LED/3K/LDM120

A - SHADES

SCHOOL HOUSE

- SKT
- SCF
- SCFS
- FNF
- FNP
- SCP
- SCPC
- SCPL
- DLP
- DNF
- S2R8

B – GLASS OPTIONS

6" FITTER

- SCH12, SCH14, SCH16, SCH18, SCO12, SHO14, SHO16, SHO18, SQO12, SOB12, SOB14, SOB16, SOB18, PSGN, PSRD, PSTL, PSGY

4" FITTER

- PSBL, SQO8, AC, SHC10

4" THREADED FITTER

- BAF.PSGN, BAF.PSRD, BAF.PSTL

C - FINISH OPTIONS

(SEE WEBSITE FOR SWATCH COLORS) (*SEE NOTES FOR LIMITATIONS*)

- 14, 15, 16, 17, 18, 19, 19P, 20, 20P, 20PB, 20SB, 21, 21P, 22, 22P, 23, 23P, 38, 39, 40, 41, 41.5, 43, 44, 48, 49, 50, 51, 52, 53, 55, 57, 58, 59, 61, 62, 63, 78, 80, 81, 82, 85, 86, 87, 89, 91, 92, 94, 95, 97, 98, 99, 100

D – MOUNTING OPTIONS

- BLC – 8' BLACK CORD
- WHC – 8' WHITE CORD
- LBLC – 8' LED BLACK CORD
- LWHC – 8' LED WHITE CORD
- STXX – STEM (XX=STEM LENGTH)

E – MOUNTING ADD-ONS

- SLC ½" – SLOPE CEILING CANOPY ½"
- STC ½" – STEM CANOPY ½"
- LSLC ½" – LED SLOPE CEILING CANOPY ½"
- LSTC ½" – LED STEM CANOPY ½"

F – MOUNTING COLOR

*SEE SECTION "C" FOR MOUNTING COLOR OPTIONS.

G – LIGHT SOURCE

(SEE SECTION "G" FOR LIGHT SOURCE AND WATTAGE OPTIONS)

INCANDESCENT (INC)

- 100W, 150W, 200W

COMPACT FLOURESCENT (CF)

- 26W
- 32W
- 42W

LIGHT EMITTED DIODE (LED)

- 12W, 25W

H – LED COLOR

(ONLY APPLICABLE FOR LED LIGHT SOURCE. SKIP THIS SECTION IF OPTION DOES NOT APPLY.)

- 27K – 2700 K
- 3K – 3000 K
- 35K – 3500 K
- 4K – 4000 K
- 5K – 5000 K

I – ELECTRICAL OPTIONS

- LDM120
- LDM277
- LDM0-10

NOTES


*ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.)

*FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY


*FINISH OPTIONS 19, 21, 22, 23 ARE AN ACID FINISH AND IS APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.

*FINISH OPTIONS 61 & 62 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.

*FIXTURE DIMENSIONS MAY VARY ± 0.25"




SKT H-3" W-4"




SCF H-8.75" W-6"

*FLUSH MOUNT, MOUNTING OPTIONS DO NOT APPLY




SCFS H-6" W-6"


*FLUSH MOUNT, MOUNTING OPTIONS DO NOT APPLY




FNP H-10.5" W-6"



SCP H-6" W-6"




DPL H-10" W-6"




FNF H-7" W-6"


*FLUSH MOUNT, MOUNTING OPTIONS DO NOT APPLY



SCPL H-29.25" W-20.5"



S2R8 H-2.5" W-4.5"



SCPC H-3" W-6"



B – GLASS OPTIONS

*NOTE – THE LIST OF "SHADES" ARE ALL APPLICABLE WITH THE GLASS OPTIONS SHOWN IN THIS SECTION.

**6" FITTER
SHADES**

- SCF
- SCFS
- SCP
- SCPC
- SCPL
- DLP
- DNF



SHC12 – 12" CLEAR GLASS

SHC14 – 14" CLEAR GLASS

SHC16 – 16" CLEAR GLASS

SHC18 – 18" CLEAR GLASS



SHO12 – 12" OPAL GLASS

SHO14 – 14" OPAL GLASS

SHO16 – 16" OPAL GLASS

SHO18 – 18" OPAL GLASS



SQO12 – 12" SQUARE OPAL GLASS



SOB12 – 12" SLANT OPAL GLASS

SOB14 – 14" SLANT OPAL GLASS

SOB16 – 16" SLANT OPAL GLASS

SOB18 – 18" SLANT OPAL GLASS



PSGN
12" OPAL GLASS
WITH LIME GREEN AND BLACK
PINSTRIPE HAND-PAINTED LINES



PSRD
12" OPAL GLASS
WITH RED-ORANGE AND BLACK
PINSTRIPE HAND-PAINTED LINES



PSTL
12" OPAL GLASS
WITH TEAL AND BLACK
PINSTRIPE HAND-PAINTED LINES



PSGY
12" OPAL GLASS
WITH GREY PINSTRIPE
HAND-PAINTED LINES

*NOTE – THE LIST OF "SHADES" ARE ALL APPLICABLE WITH THE GLASS OPTIONS SHOWN IN THIS SECTION. FOR LED OPTION 12W MAX.

**4" FITTER
SHADES**

- FNF
- FNP
- S2R8



PSBL
8" OPAL GLASS
WITH NAVY BLUE AND BLACK
PINSTRIPE HAND-PAINTED LINES



SQO8
8" SQUARE
OPAL GLASS



AC
7" CLEAR TEXTURED
ACORN GLASS



SHC10
10" CLEAR GLASS

*NOTE – THE LIST OF "SHADES" ARE ALL APPLICABLE WITH THE GLASS OPTIONS SHOWN IN THIS SECTION. FOR LED OPTION 12W MAX.

**4" THREADED
FITTER
SHADES**

- SKT



BAF.PSGN
8" OPAL GLASS
WITH LIME GREEN PINSTRIPE
HAND-PAINTED LINES



BAF.PSRD
8" OPAL GLASS
WITH RED-ORANGE PINSTRIPE
HAND-PAINTED LINES



BAF.PSTL
8" OPAL GLASS
WITH TEAL PINSTRIPE
HAND-PAINTED LINES



BAF.PSBL
8" OPAL GLASS
WITH NAVY BLUE PINSTRIPE
HAND-PAINTED LINES



D - MOUNTING OPTIONS

STEM MOUNTS

*STEMS RATED FOR DAMP LOCATION

*AVAILABLE MODELS FOR LED

*CANOPY NOT INCLUDED, ADD IN SECTION D

*AVAILABLE MODELS FOR THE 1/4" STEM OPTION

SKT
S2R8



ST(XX) STEM- 1/4" NPT

XX = LENGTH OF STEM
(EXAMPLE – "ST18" = STEM MOUNT 18" LENGTH)
*CANOPY NOT INCLUDED, ADD IN SECTION E

*AVAILABLE MODELS FOR THE 1/2" STEM OPTION

SCP
DPL
FNP



ST(XX) STEM- 1/2" NPT

XX = LENGTH OF STEM
(EXAMPLE – "ST18" = STEM MOUNT 18" LENGTH)
*CANOPY NOT INCLUDED, ADD IN SECTION E


INCANDESCENT CORD MOUNTS

*CORDS RATED FOR DRY LOCATION

*CANOPY DIMENSIONS: .625" (H) 5.25" (W)

*AVAILABLE MODELS FOR INC CORD OPTION

SCP
SKT
S2R8



BLC 8' BLACK CORD (INCLUDES INC CANOPY)


WHC 8' WHITE CORD (INCLUDES INC CANOPY)

L.E.D. AND CF CORD MOUNTS

FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY. *CORDS RATED FOR DRY LOCATION *CANOPY DIMENSIONS: 3" (H) 6" (W)

*AVAILABLE MODELS FOR LED CORD OPTION

SCP
SKT
S2R8




LBLC 8' BLACK CORD (INCLUDES LED CANOPY)

LWHC 8' WHITE CORD (INCLUDES LED CANOPY)

E - MOUNTING ADD-ONS

INCANDESCENT 1/2" STEM ADD-ONS



SLC 1/2" - SLOPE CEILING CANOPY 1/2"


*(Slopes To 20 Degrees)



STC 1/2" - STEM MOUNT CANOPY 1/2"


L.E.D. AND CF 1/2" STEM ADD-ONS

* FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY.



LSLC 1/2" LED SLOPE CEILING CANOPY 1/2"

*(Slopes To 20 Degrees)



LSTC 1/2" LED STEM MOUNT CANOPY 1/2"



G – LIGHT SOURCE

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

OPTION	WATTAGE	LUMEN		CRI	VOLTAGE	DIMMING
LIGHT EMITTING DIODE (LED)						
LED12W	12W	1000	1200	>90	120-277 VAC	SEE SECTION "F"
LED25W	25W	1900	2000	>90	120-277 VAC	SEE SECTION "F"
		@3000K	@5000K			
<p>*IMPORTANT – FOR LIGHT EMITTED DIODE (LED) LIGHT SOURCE OPTION, FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGERESTRICIONS. PLEASE SEE AVAILABILITY CHART TO THE RIGHT.</p> <p>EXAMPLE: / LED25W /</p>		<p>LED 12W (MAX)- SKT, S2R8 LED 25W (MAX) - SCF, SCFS, FNF, FNP, DLP, DNF, SCPL, SCPC, SCP</p>				

OPTION	WATTAGE	LUMEN	CRI	VOLTAGE	DIMMING
INCANDESCENT (INC) <small>MED E26</small>					
100WINC	100W	PER BULB SPECS	>90	120-277 VAC	N/A
<p>*IMPORTANT – FOR INCANDESCENT (INC) LIGHT SOURCE OPTION, FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE RIGHT.</p> <p>EXAMPLE: / INC100W /</p>		<p>INC 100W(MAX) - SKT, SCF, SCFS, FNF, DLP, S2R8 (WITH 12" GLASS OPTION) INC 150W(MAX) - SKT, SCF, SCFS, FNF, DLP, S2R8 (WITH 14" & 16" GLASSS OPTION) INC 200W(MAX) - SCF, SCFS, DLP, DNF, SCPL, SCPC, SCP (WITH 18" GLASS OPTION)</p>			

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
COMPACT FLOURESCENT (CF)					
CF26W	26W	PER BULB SPECS	>90	120-277 VAC	N/A
CF32W	32W	PER BULB SPECS	>90	120-277 VAC	N/A
CF42W	42W	PER BULB SPECS	>90	120-277 VAC	N/A
<p>*IMPORTANT – FOR COMPACT FLOURESCENT (CF) LIGHT SOURCE, FIXTURES ARE LIMITED DUE TO THE SIZE OF THE SHADE. PLEASE SEE THE CHART TO THE RIGHT TO SEE WHAT WATTAGE IS COMPARABLE FOR EACH FIXTURE WHEN ORDERING.</p> <p>EXAMPLE: / CF42W /</p>		<p>CF 26W, 32W, OR 42(MAX) - SCF, SCFS, FNF, FNP, DLP, DNF, SCPL, SCPC, SCP, SKT, S2R8</p>			

I – ELECTRICAL OPTIONS

MOST BASELITE'S ELECTRICAL OPTIONS ARE ONLY COMPATIBLE FOR CERTAIN FIXTURES. PLEASE SEE NOTES BELOW AND FOR FURTHER DEATIALS CONTACT THE FACTORY. FOR DIMMING BALLAST OPTION PLEASE CHOOSE MARK X OR MARK VII, SO RESTRICTIONS APPLY DUE TO THE SIZE OF THE BALLAST AND FIXTURE.

LED DIMMING OPTIONS

FOR TRIAC OR 0-10V OPTOIN CHOOSE FROM THE FOLLOWING. CONTACT DRIVER MANUFACTURER FOR SPECIFICATIONS.

- LDM120** - TRIAC DIMMING AT 120 VOLT
- LDM277** - TRIAC DIMMING AT 277 VOLT
- LDM0-10V** - 0 – 10v