



# BASELITE – ALLOY COLLECTION – INC – SPEC SHEET



PROJECT NAME: \_\_\_\_\_ PROJECT TYPE: \_\_\_\_\_

MODEL #	/	/	/	/	/	/	/	/	/	/	/
	A	B	C	D	E	F	G	H	I	J	K
EXAMPLE:	HDC12	41	E16	SQ 1/2"	43	45W	3K	PR3	GR12	44	LDM120

\*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES:



HDC12/50-78/ST18/78/60INC

## A - SHADES

**ALLOY COLLECTION**  
**AC810** - 150WINC (MAX)  
**CNC10** - 150WINC (MAX)  
**HDC12** - 150WINC (MAX)  
**HRC14** - 150WINC (MAX)  
**TAC14** - 150WINC (MAX)  
**WC514** - 150WINC (MAX)

## B - FINISH OPTIONS

(SEE WEBSITE FOR SWATCH COLORS)  
 (\*SEE NOTES FOR LIMITATIONS\*)  
 14, 15, 16, 17, 18, 19, 19P, 20, 20P, 20PB,  
 20SB, 21, 21P, 22, 22P, 23, 23P, 38, 39, 40,  
 41, 41.5, 42, 43, 44, 45, 46, 48, 49, 50, 51,  
 52, 53, 54, 55, 57, 58, 59, 60, 61, 62, 63, 64,  
 65, 66, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79,  
 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91,  
 92, 93, 94, 95, 96, 97, 98, 99, 100, MG.

## C - MOUNTING OPTIONS

**1/2" ARM EXTENSIONS**  
 E1, E2, E3, E4, B1, E16, E17, E27

**3/4" ARM EXTENSIONS**  
 E3A, E4A, E5, E6, E7, E8, E9,  
 E10, E11, E12, E13, B15, B15S,  
 E19, E20, E21, E25

**E14 - CREATE YOUR OWN**  
 (BASELITE WILL TAKE YOUR SKETCH AND  
 FABRICATE A CUSTOM ARM EXTENSION TO  
 MEET YOUR NEEDS).

**1/2" WALL MOUNT**  
 WM20, WM21, WM23, WM24,  
 WM25, WM26, WM29, WM29V

**3/4" WALL MOUNT**  
 B13, WM13, WM13R, WM13X

**1" WALL MOUNT**  
 B9, B9C, B10, B11, B12, B101, WM10,  
 WM11, WM14, WM14X, WM15, WM18,  
 WM30, WM35, WM35X, WM55, WM55X,  
 WM60, WM61, WM70, WM71, WM71X

**CORD MOUNT (INC)**  
 BLC, WHC, TCB, TCW, TCHB, TCHW, TLB, TLW,  
 TLW, RCB, RCW, RCHB, RCHW, FHB, FHW,  
 CBLC, CWHC

**STEM MOUNT**  
 ST6, ST12, ST18, ST24, ST36, ST48, STXX

## D - MOUNTING ADD-ONS

**INC ADD-ONS**  
 CB1/2", CB3/4", CBC1/2", CBC3/4",  
 SLC1/2", SLC3/4", STC1/2"

**UNIVERSAL ADD-ONS**  
 SQ 1/2", SQ 3/4", FH 1/2", FH 3/4", TRB 1/2",  
 TRB 3/4", SWL, LGSWL, CNK

## E - MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

## F - LIGHT SOURCE

(SEE PAGE 4 FOR WATTAGE LIMITATIONS)  
**INCANDESCENT (INC)**  
 100W 150W

## G - LED COLOR TEMP

NOT AVAILABLE

## H - ELECTRICAL OPTION

NOT AVAILABLE

## I - GLASS OPTIONS

CL3, CL4, CLT3, CLT4, BL3, BL4, RE3, RE4,  
 GR3, GR4, AH3, AH4, FR3, FR4, FRT3, FRT4,  
 PR3, PR4, BA, BAX, BAF, PR8, PR8F, FN, OC

## J - ACCESSORIES


GR10, GR12, GR14, UGR, CGR, LGR10, LGR12,  
 LGR14, CRL10, CRL12, CRL14, FLE10, FLE12,  
 FLE14, FGR10, FGR12, FGR14, GU-1, GU-2

## K - ACCESSORY COLOR


SEE SECTION "B" FOR COLOR OPTIONS.

## NOTES


- (1). FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY.
- (2). FINISH OPTIONS 19, 21, 22, 23, 75, 76, 77, 83, 84, 88, 93 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.
- (3). FINISH OPTIONS 19, 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.
- (4). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.
- (5). COLOR CORDS ARE NOT APPLICABLE FOR LED OPTIONS.  
 \*ALL ARMS COME WITH A CAST BACKPLATE (CB1/2", CB3/4", LWTM, CFWTM, ECT.).  
 \*ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.).  
 \*ALL FIXTURES MOUNT TO A 4-0 JUNCTION BOX.  
 \*FIXTURE DIMENSIONS MAY VARY ±0.25.  
 \*CORD AND CANOPY COME IN THE SAME COLOR.




AC810 H-9.5" W-10"




CNC10 H-7" W-10"




TAC14 H-6.25" W-14"



HRC14 H-5" W-14"



HDC12 H-9" W-12.5"










WC514 H-8" W-14"

## C - MOUNTING OPTIONS
















### 1/2" ARM EXTENSIONS

\*ARMS RATED FOR WET LOCATION \* MAXIMUM SECTIONS OF ARMS ARE DIMENSIONED



### 3/4" ARM EXTENSIONS

\*ARMS RATED FOR WET LOCATION \* MAXIMUM SECTIONS OF ARMS ARE DIMENSIONED



**E14**






\* Baselite will take your sketch and fabricate a custom arm extension to meet your needs  
\* Dimensions to be determined by customer

**NOTES:**

\* All arms sold with Cast Backplate (CB)  
\* Backplate may vary in size depending on light source.

### 1/4" WALL MOUNTS

\*MOUNTS RATED FOR WET LOCATION \* MAXIMUM SECTIONS OF MOUNTS ARE DIMENSIONED





C - MOUNTING OPTIONS (CONTINUED)

1/2" WALL MOUNTS

\*MOUNTS RATED FOR WET LOCATION \* MAXIMUM SECTIONS OF MOUNTS ARE DIMENSIONED



**B10** 4.75"(H) 11"(W)



**B101** 4.75"(H) 12"(W)




**B11** 4.75"(H) 13"(W)




**B13** 4.75"(H) 15"(W)



**WM13** 12"(H) 9.5"(W)



**WM13R** 12"(H) 9.5"(W)



**WM13X** 12"(H) 10.5"(W)

3/4" WALL MOUNTS


\*MOUNTS RATED FOR WET LOCATION \* MAXIMUM SECTIONS OF MOUNTS ARE DIMENSIONED



**B12** 4.75"(H) 14"(W)




**B9** 5"(H) 18"(W)




**B9C** 5"(H) 18"(W)

\*CHAIN HEIGHT TBD BY CUSTOMER



**WM14** 18"(H) 12"(W)



**WM14X** 18"(H) 14"(W)




**WM15** 23"(H) 19.5"(W)



**WM18** 30"(H) 20"(W)



**WM35** 26"(H) 18.25"(W)



**WM35X** 26"(H) 22"(W)




**WM55** 19"(H) 25.5"(W)




**WM55X** 19"(H) 27"(W)




**WM60** 18"(H) 20"(W)




**WM60X** 18"(H) 22"(W)




**WM61** 18"(H) 20"(W)




**WM61X** 18"(H) 22"(W)




**WM70** 18"(H) 20"(W)



**WM70X** 18"(H) 22"(W)



**WM71** 18"(H) 20"(W)




**WM71X** 18"(H) 22"(W)

STEM MOUNTS

\*STEMS RATED FOR DAMP LOCATION

\*DP24 COMES STANDARD WITH STC AND ST18

\* 1/4" NPT AND 3/4" NPT AVAILABLE UPON REQUEST



**DP24** DOUBLE PENDANT



**ST(XX)** STEM- 1/2" NPT

XX = LENGTH OF STEM  
(EXAMPLE - "ST18" = STEM MOUNT 18" LENGTH)  
\*CANOPY NOT INCLUDED, ADD IN SECTION D



**C - MOUNTING OPTIONS (CONTINUED)**


**INCANDESCENT CORD MOUNTS**

\*INCANDESCENT MAX WATTAGE 150 WATT. CALL FACTORY FOR HIGHER WATTAGES.  
\*CORDS RATED FOR DRY LOCATION \*CANOPY DIMENSIONS: .625" (H) 5.25" (W)

\*LOOPS, CABLES, AND CHAINS AVAILABLE ONLY FOR INCANDESCENT  
\*CORD AND CANOPY COME IN THE SAME COLOR.



**BLC** 8' BLACK CORD  
**WHC** 8' WHITE CORD




**TCB** 8' BLACK CORD, CABLE, and LOOP  
**TCW** 8' WHITE CORD, CABLE, and LOOP



**TCHB** 8' BLACK CORD, 3" CHAIN, and LOOP  
**TCHW** 8' WHITE CORD, 3" CHAIN, and LOOP



**TLB** 8' BLACK TELEPHONE CORD AND CABLE  
**TLW** 8' WHITE TELEPHONE CORD AND CABLE  
\* Not available H.I.D.



**RCB** 8' BLACK CORD, CABLE, and LOOP  
**RCW** 8' WHITE CORD, CABLE, and LOOP



**RCHB** 8' BLACK CORD, 3" CHAIN, and LOOP  
**RCHW** 8' WHITE CORD, 3" CHAIN, and LOOP



**FHB** 8' BLACK CORD WITH FLAT HUB  
**FHW** 8' WHITE CORD WITH FLAT HUB




**CBLC** 8' BLACK CORD and CABLE  
**CWLC** 8' WHITE CORD and CABLE

**D - MOUNTING ADD-ONS**

**INCANDESCENT ARM ADD-ONS**


\* FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY.




**CB 1/2"** CAST ALUMINUM BACKPLATE 1/2 NPT  
**CB 3/4"** CAST ALUMINUM BACKPLATE 3/4 NPT



**CBC 1/2"** 1/2" BACKPLATE COVER  
**CBC 3/4"** 3/4" BACKPLATE COVER  
\* Includes slip ring to hold 1/2" or 3/4" arm extension in place



**SLC 1/2"** SLOPE CEILING CANOPY 1/2"  
**SLC 3/4"** SLOPE CEILING CANOPY 3/4"  
\*(Slopes To 20 Degrees)




**STC 1/2"** 1/2" STEM MOUNT CANOPY

**UNIVERSAL STEM AND ARM ADD-ONS**

\* EXAMPLE FOR MULTIPLE MOUNTING ADD-ONS:


MODEL #: -/-/LWTM, TRB X", LGSWL/-/-/-/-/-/




**CNK** CANOPY For MULTIPLE FIXTURES  
\*CNK dimensions vary on number of fixtures applied



**FH 1/2"** FLAT HUB 1/2"  
**FH 3/4"** FLAT HUB 3/4"



**LGSWL** 1/2" NPT SWIVEL  
For all shades greater than 7" wide in diameter



**TRB 1/2"-4' Cable** SUPPORT  
**TRB 3/4"-4' Cable** SUPPORT

**F - LIGHT SOURCE**

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

**INCANDESCENT (INC) MED E26**

**INC 150W - AC810, CNC10, HDC14, HRC14, TAC14, WC514**

\*IMPORTANT - FOR INCANDESCENT (INC) LIGHT SOURCE OPTION, FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE RIGHT.

EXAMPLE: /INC150W /

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
100WINC	100W	PER BULB SPECS	>90	120-277 VAC	N/A
150WINC	150W	PER BULB SPECS	>90	120-277 VAC	N/A



**I – GLASS OPTIONS**

\*NOTE: MUST USE TEMPERED GLASS FOR LIGHT FIXTURES USING HIGH INTENSITY DISCHARGE (HID) LIGHT SOURCE OPTION.



**CL3** 3" CLEAR GLASS



**PR3** 3" PRISMATIC GLASS



**RE3** 3" RED GLASS



**BL3** 3" BLUE GLASS



**BA** 6" OPAL BALL  
(100W INC MAX/LED12W)



**BAX** 9" CLEAR GLOBE



**FN** 8" CLEAR TEXTURED GLOBE  
(150W INC MAX/LED25W)

**CL4** 4" CLEAR GLASS

**PR4** 4" PRISMATIC GLASS

**RE4** 4" RED GLASS

**BL4** 4" BLUE GLASS

**BAF** 9" FROSTED GLOBE  
(200W INC MAX/LED25W)

**CLT3** 3" CLEAR TEMPERED

**CLT4** 4" CLEAR TEMPERED




**FR3** 3" FROSTED GLASS



**AH3** 3" AMBER HYDE GLASS



**GR3** 3" GREEN GLASS



**FR4** 4" FROSTED GLASS

**AH4** 4" AMBER HYDE GLASS

**GR4** 4" GREEN GLASS



**BA7** 7" CLEAR GLOBE



**PR8** 8" PRISMATIC



**OC** 8" OPAL TAPERED GLOBE  
(60W INC MAX/LED25W)

**FRT3** 3" FROSTED TEMPERED

**FRT4** 4" FROSTED TEMPERED


**BA7F** 7" FROSTED GLOBE  
(100W INC MAX/LED25W)

**PR8F** 8" PRISMATIC FROSTED  
(200W INC MAX/LED45W)


GLASS – MAX WATTAGE  
3" GLASS – 100W INC / LED12W  
4" GLASS – 200W INC / LED25W

GLASS – DIMENSIONS  
3" GLASS  
Diameter 3.34"  
Height 6.93"  
Fitter 3.29"  
4" GLASS  
Diameter 4.34"  
Height 8.37"  
Fitter 4.29"


**J – ACCESSORIES**



**GR10** 10" WIRE GRILL




**LGR10** 10" LOUVERED GRILL



**FGR10** 10" FLAT GRILL



**CRL10** 10" CURVED POLYCARB LENS



**FLE10** 10" FLAT CLEAR LENS

**GR12** 12" WIRE GRILL

**LGR12** 12" LOUVERED GRILL

**FGR12** 12" FLAT GRILL

**CRL12** 12" CURVED POLYCARB LENS

**FLE12** 12" FLAT CLEAR LENS

**GR14** 14" WIRE GRILL

**LGR14** 14" LOUVERED GRILL


**FGR14** 14" FLAT GRILL

**CRL14** 14" CURVED POLYCARB LENS


**FLE14** 14" FLAT CLEAR LENS




**UGR** U- WIRE GUARD




**WG-1** WIRE GUARD



**WG-2** WIRE GUARD



**GU-1** CAST ALUMINUM GUARD



**GU-2** CAST GUARD