

WATER PIPE LIGHTS

SPECIFICATION SHEET



MODEL: WP48.UD

PREPARED BY:		
TYPE:		
JOB NAME:		
DATE:		
CERTIFICATION:		

WP48/UD/49/5-40INC

FINISH – Five stage pretreatment process, coated with a lead free TGI C polyester powder coat finish. White is standard inside reflectors, *some finish options excluded. See color chart below for color options (unless specified). Some finish options are not available for certain fixtures. Custom colors and Marine options are available upon request.

LAMP HOLDERS – Accommodates **Incandescent** – medium base porcelain socket, copper shell with nickel plate, rated 250v, 660W.

MOUNTING – Available with wall mounting. Projection from wall is 10" and custom lengths and configurations are available upon request. Fixtures are pre-wired with 48" or 96" leads .

REFLECTOR – This fixture is made from a high grade 356 cast aluminum and steel pipe fittings.

MODEL# FINISH	FINICH	LIGHT SOURCE			MOUNTING OPTIONS	ACCESCODIES	
	FINISH	INC	CF*	MH*	LED	MOUNTING OPTIONS	ACCESSORIES
WP48.UD	14, 15, 16, 17, 18, 19*, 19P, 20, 20P, 21, 21P*, 22P*, 22, 23, 23P*,38, 39, 40*, 41, 42, 43, 44, 45, 46, 48*, 49*, 50, 51, 52, 53, 54*, 55, 57*, 58*, 59, 60, 61*, 62*, 63*, 64, 65, 66, 70*, 71*, 72*, 73*, 74, 75, 76, 77, 78*, 79, 80, 81, 82, 83,* 84*, 85, 86, 87, 88*, 89, 90, 91, 92*, 93*, 94*, 95, 96, 97, 98*, 99, 100	5-40W	N/A	N/A	N/A	WALL MOUNT	N/A

^{*} same finish color inside and out.

SUBJECT TO MODIFICATION WITHOUT NOTICE.



PH: 877-999-1990 WEB: WWW.BASELITE.COM EMAIL: SALES@BASELITE.COM





^{*} remote ballast / driver.