

BASELITE - CYLINDER - CF- SPECIFICATION SHEET





PROJECT TYPE: . PROJECT NAME: -MODEL# С Κ В D F F G Н EXAMPLE: CY510

NOTES:



A - SHADES

CYLINDERS

CY48 - 32WCF (MAX)

CY510 - 42WCF (MAX)

CY816 - 57WCF (MAX)

CY618 - 42WCF (MAX)

CY620 - 42WCF (MAX)

CYB510 - 42WCF (MAX)

CYB816 - 57WCF (MAX)

CYBU510 - 2-26WCF (MAX)

CYBU816 - 42WCF (MAX)

CG512 - 42WCF (MAX)

PD2012 - 42WCF (MAX)

SD2012 - 42WCF (MAX)

B-FINISH OPTIONS

(SEE WEBSITE FOR SWATCH COLORS) (*SEE NOTES FOR LIMITATIONS*) 14, 15, 16, 17, 18, 19, 19P, 20, 20P, 20PB, 20SB, 21, 21P, 22, 22P, 23, 23P, 38, 39, 40, 41, 41.5, 42, 43, 44, 45, 46, 48, 49, 50, 51, 52, 53, 54, 55, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, MG.

C – MOUNTING OPTIONS

COMPACT FLUORESCENT CORD MOUNT CFBLC, CFWHC, CFTCB, CFTCW, CFTCHB, CFTCHW, CFTLB, CFTLW, CFRCB, CFRCW

CFRCHB, CFRCHW, CFFHB, CFFHW, CFHBLC, CFHWHC, CFCBLC, CFCWHC

STEM MOUNT

ST6, ST12, ST18, ST24, ST36, ST48, STXX

D - MOUNTING ADD-ONS

CF ADD-ONS

CFSLC, CFSTC

UNIVERSAL ADD-ONS

FH ½", FH ¾", SWL, LGSWL, CNK

E - MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

F - LIGHT SOURCE

(SEE PAGE 3 FOR WATTAGE LIMITATIONS) COMPACT FLUORESCENT (CF) 26W. 32W. 42W

G – LED COLOR TEMP

NOT AVAILABLE

H – ELECTRICAL OPTION

(SEE PAGE 3 FOR DIMMING OPTION SPECIFICATIONS)

CDM120 CDM277

CDM120/277

I - GLASS OPTIONS

NOT AVAILABLE

J - ACCESSORIES

NOT AVAILABLE

K – ACCESSORY COLOR

NOT AVAILABLE

NOTES

(1). FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY. (2). FINISH OPTIONS 19, 21, 22, 23, 75,76, 77, 83, 84, 88, 93 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.

(3). FINISH OPTIONS 19, 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.

(4). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.

(5). COLOR CORDS ARE NOT APPLICABLE FOR LED OPTIONS.

*ALL ARMS COME WITH A CAST BACKPLATE (CB1/2", CB3/4", LWTM, CFWTM, ECT.).

*ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.).

*ALL FIXTURES MOUNT TO A 4-O JUNCTION BOX.


*FIXTURE DIMENSIONS MAY VARY ±0.25. *CORD AND CANOPY COME IN THE SAME COLOR.



CY48 H - 8" W - 4" CY510 H - 10" W - 5" CY816 H - 16" W - 8"




CY618 H-6" W-18" CY620 H - 6" W - 20"




CYB510 H-10" W-5" **CYB816** H-16" W-8" CYBU510 H-10" W-5" CYBU816 H-16" W-8"


*FIXTURES COME AS SHOWN
*ALL MOUNTING OPTIONS DO NOT APPLY



PD2012 H-12" W-20"



CG512 H-12" W-5"



SD2012 H-12" W-20"


BASELITE MODERN LIGHTING CATALOG

PROJECT NAME: PROJECT TYPE:

C - MOUNTING OPTIONS

STEM MOUNTS

*STEMS RATED FOR DAMP LOCATION



DP24 DOUBLE PENDANT 20"(H) 24"(W)

*DP24 COMES STANDARD WITH CFSTC AND ST18



ST(XX)

STEM- 1/2" NPT

XX = LENGTH OF STEM (EXAMPLE - "ST18" = STEM MOUNT 18" LENGTH)
*CANOPY NOT INCLUDED, ADD IN SECTION D * 1/4" NPT AND 3/4" NPT AVAILABLE UPON REQUEST



SC24 SCROLL STEM 33"(H) 26(W)

*SC24 COMES STANDARD WITH CFSTC

COMPACT FLUORESCENT CORD MOUNTS

*FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY.

*CORDS RATED FOR DRY LOCATION

*CANOPY DIMENSIONS: 4" (H) 5.5" (W)

*CORD AND CANOPY COME IN THE SAME COLOR.



CFBLC 8' BLACK CORD CFWHC 8' WHITE CORD



CFTCB 8' BLACK CORD, CABLE, and LOOP

CFTCW 8' WHITE CORD, CABLE, and LOOP



CFTCHB 8' BLACK CORD, 3' CHAIN, and LOOP

8' WHITE CORD, 3' CHAIN, and LOOP



CFRCB 8' BLACK CORD, CABLE, and LOOP

CFRCW 8' WHITE CORD, CABLE, and LOOP



CFRCHB 8' BLACK CORD, 3' CHAIN, and LOOP CFRCHW 8' WHITE CORD, 3' CHAIN, and LOOP



CFFHB 8' BLACK CORD WITH FLAT HUB

CFFHW 8' WHITE CORD WITH FLAT HUB



CFCBLC 8' BLACK CORD and CABLE

CFCWHC 8' WHITE CORD and CABLE




*DISTANCE TO LAMP (CF)

*All compact fluorescent and LED housings may vary in size according to light source chosen.


D-MOUNTING ADD-ONS

COMPACT FLUORESCENT STEM AND ARM ADD-ONS

* FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY.



CFSLC CF SLOPE CEILING CANOPY



CFSTC CF STEM MOUNT CANOPY



BASELITE MODERN LIGHTING CATALOG

PROJECT NAME: ______PROJECT TYPE: _____

D - MOUNTING ADD-ONS (CONTINUED)

UNIVERSAL STEM AND ARM

* EXAMPLE FOR MULTIPLE MOUNTING ADD-ONS:

MODEL #:

-/-/-LWTM, TRB ½", LGSWL/-/-/-/-/
A B C D E F G H I J K




CNK CANOPY FOR MULTIPLE FIXTURES

*CNK dimensions vary on number of fixtures applied



FH 1/2" FLAT HUB 1/2"
FH 3/4" FLAT HUB 3/4"



LGSWL 1/2" NPT SWIVEL

For all shades greater than
7" wide in diameter

F - LIGHT SOURCE

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

COMPACT FLOURESCENT (CF)

CF 2-26W(MAX) - CYBU510

CF 26W, OR 32W(MAX) - CY48

CF 26W, 32W, OR 42(MAX) - CY510, CYB510, CG512,

PD2012, SD2012

CF 26W, 32W 42, OR 57(MAX) - CY816, CYB816

CF 2-26W, 32W, OR 42(MAX) - CY618, CY620, CYBU816

*IMPORTANT – FOR COMPACT FLOURESCENT (CF) LIGHT SOURCE, FIXTURES ARE LIMITED DUE TO THE SIZE OF THE SHADE. PLEASE SEE THE CHART TO THE LEFT TO SEE WHAT WATTAGE IS COMPARABLE FOR EACH FIXTURE WHEN ORDERING.

EXAMPLE: / CF42W

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
CF26W	26W	PER BULB SPECS	>90	120-277 VAC	0-10V
CF32W	32W	PER BULB SPECS	>90	120-277 VAC	0-10V
CF42W	42W	PER BULB SPECS	>90	120-277 VAC	0-10V
CF57W	57W	PER BULB SPECS	>90	120-277 VAC	0-10V

H - ELECTRICAL OPTION

MOST BASELITE'S ELECTRICAL OPTIONS ARE ONLY COMPATIBLE FOR CERTAIN FIXTURES. PLEASE SEE NOTES BELOW AND FOR FURTHER DEATIALS CONTACT THE FACTORY. FOR DIMMING BALLAST OPTION PLEASE CHOOSE MARK X OR MARK VII, SO RESTRICTIONS APPLY DUE TO THE SIZE OF THE BALLAST AND FIXTURE.

COMPACT FLUORESCENT DIMMING OPTIONS

PROVIDED WITH ADVANCE TRANSFORMER, PLEASE CHOOSE MARK 10 OR MARK 7 WITH SPECIFIED VOLTAGE FROM THE LIST BELOW. CONTACT BALLAST MANUFACTURER FOR SPECIFICATIONS.

CDM7-120/277 - ADVANCE MARK 7 0-10v ELECTRICAL BALLST - 120/277 VOLT

CDM10-120 - ADVANCE MARK 10 TRI-ELV ELECTRICAL BALLST - 120 VOLT

CDM10-277 - ADVANCE MARK 10 TRI-ELV ELECTRICAL BALLST - 277 VOLT