



BASELITE – HZ - VA - VE – CF – SPECIFICATION SHEET



PROJECT NAME: _____ PROJECT TYPE: _____

MODEL #	/	/	/	X	/	/	/	/	/	/	/
	A	B	C	D	E	F	G	H	I	J	K
EXAMPLE:	VE1	41	E19	-	41	12WLED	3K	LDM120	FR3	CG1	41

*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES:

A - SHADES

HZ SERIES

HZ1 - 42WCF (MAX), (3" GLASS), (3" GUARD)

HZ2 - 42WCF (MAX), (4" GLASS), (4" GUARD)

VA SERIES

VA1 - 42WCF (MAX), (3" GLASS), (3" GUARD)

VA2 - 42WCF (MAX), (4" GLASS), (4" GUARD)

VE SERIES

VE1 - 42WCF (MAX), (3" GLASS), (3" GUARD)

VE2 - 42WCF (MAX), (4" GLASS), (4" GUARD)

B - FINISH OPTIONS

(*SEE NOTES FOR LIMITATIONS*)

(SEE WEBSITE FOR SWATCH COLORS)

20, 21, 22, 23, 40, 41, 41.5, 42, 43, 44, 45,
46, 48, 49, 50, 51, 52, 53, 54, 55, 59, 60,
61, 62, 63, 70, 71, 72, 73

C - MOUNTING OPTIONS

* ALL FIXTURES COMES AS IS. NO OTHER
MOUNTING APPLIES

E19 - COMES STANDARD WITH VA1, VA2,
VE1, VE2

D - MOUNTING ADD-ONS

NOT AVAILABLE

E - MOUNTING COLOR

SEE SECTION "B" FOR COLOR
OPTIONS.

F – LIGHT SOURCE

(SEE PAGE 2 FOR WATTAGE LIMITATIONS)

COMPACT FLUORESCENT (CF)

26W, 32W, 42W

G – LED COLOR TEMP

NOT AVAILABLE

H – ELECTRICAL OPTION

(SEE PAGE 2 FOR DIMMING OPTION SPECIFICATIONS)

CDM120

CDM277

CDM120/277

I – GLASS OPTIONS

3" GLASS (AVAILABLE FOR HZ1, VA1, VE1)

CL3, CLT3, BL3, RE3, GR3,
AH3, FR3, FRT3, PR3

4" GLASS (AVAILABLE FOR HZ2, VA2, VE2)

CL4, CLT4, BL4, RE4, GR4,
AH4, FR4, FRT4, PR4

J – ACCESSORIES

3" GUARDS (AVAILABLE FOR HZ1, VA1, VE1)

CG1, WG1

4" GUARDS (AVAILABLE FOR HZ2, VA2, VE2)

CG2, WG2

K – ACCESSORY COLOR

SEE SECTION "B" FOR COLOR
OPTIONS.

NOTES

(1). FINISH OPTIONS 40, 49, 54, 61, 62,
63, 70, 71, 72, 73 ONLY AVAILABLE
INSIDE AND OUT OF FIXTURE. OTHER
FINISHES ARE WHITE INSIDE.

(2). FINISH OPTIONS FOR SHADES ≤ 10"
IN DIAMETER ARE THE SAME INSIDE AND
OUT OF FIXTURE. SHADES > 10" IN
DIAMETER ARE WHITE ON THE INSIDE.

(3). FINISH OPTIONS 61, 62, 70, 71, 72,
73 ARE FINISHED WITH A SUPERCHROME
ON THE INSIDE FOR ALL LED LIGHT
SOURCE OPTIONS.

*ALL ARMS COME WITH A CAST
BACKPLATE (CB1/2", CB3/4", LWTM,
CFWTM, ECT.).

*ACCORDING TO THE LIGHT SOURCE THE
BACKPLATE MAY VARY IN SIZE.

(EXAMPLE: LED LIGHT SOURCE WILL
HAVE A DEEPER BACKPLATE TO HOUSE
THE DRIVER.).

*ALL FIXTURES MOUNT TO A 4-O
JUNCTION BOX.

*FIXTURE DIMENSIONS MAY VARY
± 0.25.

*RATED FOR WET LOCATION.




VA1/53/E19/100WINC/AH3/CG1/53




HZ1 H - 4.5" W - 21" PROJ. - 5"

HZ2 H - 6.125" W - 29" PROJ. - 6.5"
3" GLASS & 3" GUARD AVAILABLE FOR HZ1
4" GLASS & 4" GUARD AVAILABLE FOR HZ2



VA1 H - 10.625" W - 16.25" PROJ. - 6"

VA2 H - 12.625" W - 20" PROJ. - 7"
3" GLASS & 3" GUARD AVAILABLE FOR VA1
4" GLASS & 4" GUARD AVAILABLE FOR VA2



VE1 H - 4" W - 24" PROJ. - 9"

VE2 H - 5.5" W - 28.75" PROJ. - 10"
3" GLASS & 3" GUARD AVAILABLE FOR VE1
4" GLASS & 4" GUARD AVAILABLE FOR VE2



F – LIGHT SOURCE

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

COMPACT FLUORESCENT (CF)

CF 26W, 32W, OR 42(MAX) - HZ1, VA1, VE1, HZ2, VA2, VE2

***IMPORTANT – FOR COMPACT FLUORESCENT (CF) LIGHT SOURCE, FIXTURES ARE LIMITED DUE TO THE SIZE OF THE SHADE. PLEASE SEE THE CHART TO THE LEFT TO SEE WHAT WATTAGE IS COMPARABLE FOR EACH FIXTURE WHEN ORDERING.**

EXAMPLE: / CF42W /

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
CF26W	26W	PER BULB SPECS	>90	120-277 VAC	See section "H"
CF32W	32W	PER BULB SPECS	>90	120-277 VAC	See section "H"
CF42W	42W	PER BULB SPECS	>90	120-277 VAC	See section "H"

H – ELECTRICAL OPTION

MOST BASELITE'S ELECTRICAL OPTIONS ARE ONLY COMPATIBLE FOR CERTAIN FIXTURES. PLEASE SEE NOTES BELOW AND FOR FURTHER DEATIALS CONTACT THE FACTORY.
FOR DIMMING BALLAST OPTION PLEASE CHOOSE MARK X OR MARK VII, SO RESTRICTIONS APPLY DUE TO THE SIZE OF THE BALLAST AND FIXTURE.

COMPACT FLUORESCENT DIMMING OPTIONS

PROVIDED WITH ADVANCE TRANSFORMER, PLEASE CHOOSE MARK 10 OR MARK 7 WITH SPECIFIED VOLTAGE FROM THE LIST BELOW. CONTACT BALLAST MANUFACTURER FOR SPECIFICATIONS.

CDM7-120/277 - ADVANCE MARK 7 0-10v ELECTRICAL BALLST – 120/277 VOLT

CDM10-120 - ADVANCE MARK 10 ELECTRICAL BALLST – 120 VOLT

CDM10-277 - ADVANCE MARK 10 ELECTRICAL BALLST – 277 VOLT

I – GLASS OPTIONS

*NOTE: MUST USE TEMPERED GLASS FOR LIGHT FIXTURES USING HIGH INTENSITY DISCHARGE (HID) LIGHT SOURCE OPTION.

*3" GLASS AVAILABLE HZ1, VA1, VE1

*4" GLASS AVAILABLE FOR HZ2, VA2, VE2



CL3 3" CLEAR GLASS
CL4 4" CLEAR GLASS
CLT3 3" CLEAR TEMPERED
CLT4 4" CLEAR TEMPERED



PR3 3" PRISMATIC GLASS
PR4 4" PRISMATIC GLASS



RE3 3" RED GLASS
RE4 4" RED GLASS



BL3 3" BLUE GLASS
BL4 4" BLUE GLASS



FR3 3" FROSTED GLASS
FR4 4" FROSTED GLASS
FRT3 3" FROSTED TEMPERED
FRT4 4" FROSTED TEMPERED




AH3 3" AMBER HYDE GLASS
AH4 4" AMBER HYDE GLASS



GR3 3" GREEN GLASS
GR4 4" GREEN GLASS

GLASS – DIMENSIONS	
3" GLASS	
Diameter	3.34"
Height	6.93"
Fitter	3.29"
4" GLASS	
Diameter	4.34"
Height	8.37"
Fitter	4.29"




GLASS – MAX WATTAGE	
3" GLASS – 100W INC / LED12W	
4" GLASS – 200W INC / LED25W	


J – ACCESSORIES

* 3" GUARDS AVAILABLE FOR HZ1, VA1, VE1


* 4" GUARDS AVAILABLE FOR HZ2, VA2, VE2




WG1 WIRE GUARD



WG2 WIRE GUARD



CG1 CAST GUARD



CG2 CAST GUARD