



# BASELITE – P - HP – INC – SPECIFICATION SHEET



PROJECT NAME: \_\_\_\_\_ PROJECT TYPE: \_\_\_\_\_

MODEL #	/	/	/	X	/	X	/	/	/	/	/	/
	A	B	C	D	E	F	G	H	I	J	K	
EXAMPLE:	HP2	41	BLC	-	-	25WLED	3K	LDM120	FR4	CG2	41	

\*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES:

## A - SHADES

### P-HP SERIES

**P1** - 100WINC (MAX), (3" GLASS), (3" GUARD)  
**P2** - 200WINC (MAX), (4" GLASS), (4" GUARD)  
**HP1** - 100WINC (MAX), (3" GLASS), (3" GUARD)  
**HP2** - 200WINC (MAX), (4" GLASS), (4" GUARD)

## B - FINISH OPTIONS

(\*SEE NOTES FOR LIMITATIONS\*)  
 (SEE WEBSITE FOR SWATCH COLORS)  
 20, 21, 22, 23, 40, 41, 41.5, 42, 43, 44, 45,  
 46, 48, 49, 50, 51, 52, 53, 54, 55, 59, 60,  
 61, 62, 63, 70, 71, 72, 73

## C - MOUNTING OPTIONS

\* ALL FIXTURES COMES AS IS.  
 NO OTHER MOUNTING APPLIES

### CORD MOUNT

BLC, WHC, TCB, TCW, TCHB, TCHW, TLB,  
 TLW, TLB, TLW, RCB, RCW, RCHB, RCHW,  
 FHB, FHW, CBLC, CWHC, CHB, CHW

### STEM MOUNT

ST6, ST12, ST18, ST24, ST36, ST48, STXX

## D - MOUNTING ADD-ONS

### LED ADD-ONS

LWTM, LSLC, LSTC

### UNIVERSAL ADD-ONS

FH ½", FH ¾", LGSWL

## E - MOUNTING COLOR

SEE SECTION "B" FOR COLOR  
 OPTIONS.

## F - LIGHT SOURCE

(SEE PAGE 3 FOR WATTAGE LIMITATIONS)

### INCANDESCENT (INC)

100W, 150W, 200W

## G - LED COLOR TEMP

NOT AVAILABLE

## H - ELECTRICAL OPTION

NOT AVAILABLE

## I - GLASS OPTIONS

**3" GLASS** (AVAILABLE FOR P1 & HP1)

CL3, CLT3, BL3, RE3, GR3,  
 AH3, FR3, FRT3, PR3

**4" GLASS** (AVAILABLE FOR P2 & HP2)

CL4, CLT4, BL4, RE4, GR4,  
 AH4, FR4, FRT4, PR4

## J - ACCESSORIES

**3" GUARDS** (AVAILABLE FOR P1 & HP1)

CG1, WG1

**4" GUARDS** (AVAILABLE FOR P2 & HP2)

CG2, WG2

## K - ACCESSORY COLOR

SEE SECTION "B" FOR COLOR  
 OPTIONS.

## NOTES

(1). FINISH OPTIONS 40, 49, 54, 61, 62,  
 63, 70, 71, 72, 73 ONLY AVAILABLE  
 INSIDE AND OUT OF FIXTURE. OTHER  
 FINISHES ARE WHITE INSIDE.

(2). FINISH OPTIONS FOR SHADES ≤ 10"  
 IN DIAMETER ARE THE SAME INSIDE AND  
 OUT OF FIXTURE. SHADES > 10" IN  
 DIAMETER ARE WHITE ON THE INSIDE.

(3). FINISH OPTIONS 61, 62, 70, 71, 72,  
 73 ARE FINISHED WITH A SUPERCHROME  
 ON THE INSIDE FOR ALL LED LIGHT  
 SOURCE OPTIONS.

\*ALL ARMS COME WITH A CAST  
 BACKPLATE (CB1/2", CB3/4", LWTM,  
 CFWTM, ECT.).

\*ACCORDING TO THE LIGHT SOURCE THE  
 BACKPLATE MAY VARY IN SIZE.

(EXAMPLE: LED LIGHT SOURCE WILL  
 HAVE A DEEPER BACKPLATE TO HOUSE  
 THE DRIVER.).

\*ALL FIXTURES MOUNT TO A 4-O  
 JUNCTION BOX.


\*FIXTURE DIMENSIONS MAY VARY  
 ± 0.25.

\*CORD AND CANOPY COME IN THE SAME  
 COLOR.

\*RATED FOR WET LOCATION.




HP2/62/BLC/100WINC/FR4/CG2/62



**P1** H - 9.625" W - 4"

**P2** H - 12" W - 5.5"

3" GLASS & 3" GUARD AVAILABLE FOR P1  
 4" GLASS & 4" GUARD AVAILABLE FOR P2



**HP1** H - 9.625" W - 8"

**HP2** H - 12" W - 10"

3" GLASS & 3" GUARD AVAILABLE FOR HP1  
 4" GLASS & 4" GUARD AVAILABLE FOR HP2



## C - MOUNTING OPTIONS

### STEM MOUNTS

\*STEMS RATED FOR DAMP LOCATION



#### ST(XX) STEM- 1/2" NPT

XX = LENGTH OF STEM

(EXAMPLE - "ST18" = STEM MOUNT 18" LENGTH)

\*CANOPY NOT INCLUDED, ADD IN SECTION D

\* 1/4" NPT AND 3/4" NPT AVAILABLE UPON REQUEST

### INCANDESCENT CORD MOUNTS

\*INCANDESCENT MAX WATTAGE 150 WATT. CALL FACTORY FOR HIGHER WATTAGES. LOOPS, CABLES, AND CHAINS AVAILABLE ONLY FOR INCANDESCENT

\*CORDS RATED FOR DRY LOCATION

\*CANOPY DIMENSIONS: .625" (H) 5.25" (W)

\*CORD AND CANOPY COME IN THE SAME COLOR.



**BLC** 8' BLACK CORD

**WHC** 8' WHITE CORD



**TCB** 8' BLACK CORD, CABLE, and LOOP

**TCW** 8' WHITE CORD, CABLE, and LOOP



**TCHB** 8' BLACK CORD, 3' CHAIN, and LOOP

**TCHW** 8' WHITE CORD, 3' CHAIN, and LOOP



**TLB** 8' BLACK TELEPHONE CORD AND CABLE

**TLW** 8' WHITE TELEPHONE CORD AND CABLE

\* Not available H.I.D.



**RCB** 8' BLACK CORD, CABLE, and LOOP

**RCW** 8' WHITE CORD, CABLE, and LOOP



**RCHB** 8' BLACK CORD, 3' CHAIN, and LOOP

**RCHW** 8' WHITE CORD, 3' CHAIN, and LOOP



**FHB** 8' BLACK CORD WITH FLAT HUB

**FHW** 8' WHITE CORD WITH FLAT HUB



**CBLC** 8' BLACK CORD and CABLE

**CWLC** 8' WHITE CORD and CABLE



**CHB** 8' BLACK CORD, 3' CHAIN, and LOOP


**CHW** 8' WHITE CORD, 3' CHAIN, and LOOP

\* Loop may vary due to shade style


## D - MOUNTING ADD-ONS

### LED - STEM AND ARM ADD-ONS


\* FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY.



**LWTM** WEATHERTIGHT LED WALL MOUNT



**LSLC** LED SLOPE CEILING CANOPY



**LSTC** LED STEM MOUNT CANOPY






## D – MOUNTING ADD-ONS ( CONTINUED)


### UNIVERSAL STEM AND ARM ADD-ONS

\* EXAMPLE FOR MULTIPLE MOUNTING ADD-ONS:

MODEL #: -/-/-/-(LWTM, TRB 1/2", LGSWL)-/-/-/-/-/-/-/-/  
A B C D E F G H I J K



**LGSWL 1/2" NPT SWIVEL**  
For all shades greater than  
7" wide in diameter



**FH 1/2"** FLAT HUB 1/2"  
**FH 3/4"** FLAT HUB 3/4"

## F – LIGHT SOURCE

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

### INCANDESCENT (INC) MED E26

**INC 100W- P1, HP1**  
**INC 200W- P2, HP2**

**\*IMPORTANT – FOR INCANDESCENT (INC) LIGHT SOURCE OPTION, FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE LEFT.**

EXAMPLE: / INC150W /

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
100WINC	100W	PER BULB SPECS	>90	120-277 VAC	N/A
150WINC	150W	PER BULB SPECS	>90	120-277 VAC	N/A
200WINC	200W	PER BULB SPECS	>90	120-277 VAC	N/A

## I – GLASS OPTIONS

\*NOTE: MUST USE TEMPERED GLASS FOR LIGHT FIXTURES USING HIGH INTENSITY DISCHARGE (HID) LIGHT SOURCE OPTION.

\*3" GLASS AVAILABLE FOR E1 & HE1

\*4" GLASS AVAILABLE FOR E2 & HE2



**CL3** 3" CLEAR GLASS  
**CL4** 4" CLEAR GLASS  
**CLT3** 3" CLEAR TEMPERED  
**CLT4** 4" CLEAR TEMPERED



**PR3** 3" PRISMATIC GLASS  
**PR4** 4" PRISMATIC GLASS



**RE3** 3" RED GLASS  
**RE4** 4" RED GLASS



**BL3** 3" BLUE GLASS  
**BL4** 4" BLUE GLASS



**FR3** 3" FROSTED GLASS  
**FR4** 4" FROSTED GLASS  
**FRT3** 3" FROSTED TEMPERED  
**FRT4** 4" FROSTED TEMPERED




**AH3** 3" AMBER HYDE GLASS  
**AH4** 4" AMBER HYDE GLASS



**GR3** 3" GREEN GLASS  
**GR4** 4" GREEN GLASS

GLASS – DIMENSIONS	
3" GLASS	
Diameter	3.34"
Height	6.93"
Fitter	3.29"
4" GLASS	
Diameter	4.34"
Height	8.37"
Fitter	4.29"




GLASS – MAX WATTAGE	
3" GLASS – 100W INC / LED12W	
4" GLASS – 200W INC / LED25W	




J – ACCESSORIES

\* 3" GUARDS AVAILABLE FOR E1 & HE1


\*4" GUARDS AVAILABLE FOR E2 & HE2




**WG1** 3" WIRE GUARD



**WG2** 4" WIRE GUARD



**CG1** 3" CAST GUARD



**CG2** 4" CAST GUARD