



BASELITE – SFM – INC – SPECIFICATION SHEET



PROJECT NAME: _____ PROJECT TYPE: _____

MODEL #	/	/	X	/	/	X	/	/	X	/	/	/
	A	B	C	D	E	F	G	H	I	J	K	
EXAMPLE:	HW1	41	-	-	-	100WINC	3K	-	FR3	CG1	41	

*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES:

A - SHADES

SFM SERIES

SFM1 - 100WINC (MAX), (3" GLASS), (3" GUARD)

SFM2 - 200WINC (MAX), (4" GLASS), (4" GUARD)

B - FINISH OPTIONS

(*SEE NOTES FOR LIMITATIONS*)

(SEE WEBSITE FOR SWATCH COLORS)

20, 21, 22, 23, 40, 41, 41.5, 42, 43, 44, 45,
46, 48, 49, 50, 51, 52, 53, 54, 55, 59, 60,
61, 62, 63, 70, 71, 72, 73

C - MOUNTING OPTIONS

NOT AVAILABLE

D - MOUNTING ADD-ONS

WJB41/2, WJB43/4

E - MOUNTING COLOR

NOT AVAILABLE

F - LIGHT SOURCE

(SEE PAGE 2 FOR WATTAGE LIMITATIONS)

INCANDESCENT (INC)

100W, 150W, 200W

G - LED COLOR TEMP

NOT AVAILABLE

H - ELECTRICAL OPTION

NOT AVAILABLE

I - GLASS OPTIONS

3" GLASS (AVAILABLE FOR SFM1)

CL3, CLT3, BL3, RE3, GR3,
AH3, FR3, FRT3, PR3

4" GLASS (AVAILABLE FOR SFM2)

CL4, CLT4, BL4, RE4, GR4,
AH4, FR4, FRT4, PR4

J - ACCESSORIES

3" GUARDS (AVAILABLE FOR SFM1)

CG1, WG1

4" GUARDS (AVAILABLE FOR SFM2)

CG2, WG2

K - ACCESSORY COLOR

SEE SECTION "B" FOR COLOR
OPTIONS.

NOTES

- (1). FINISH OPTIONS 40, 49, 54, 61, 62, 63, 70, 71, 72, 73 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.
- (2). FINISH OPTIONS FOR SHADES ≤ 10" IN DIAMETER ARE THE SAME INSIDE AND OUT OF FIXTURE. SHADES > 10" IN DIAMETER ARE WHITE ON THE INSIDE.
- (3). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.

*ALL ARMS COME WITH A CAST BACKPLATE (CB1/2", CB3/4", LWTM, CFWTM, ECT.).

*ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE.

(EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.).


*ALL FIXTURES MOUNT TO A 4-O JUNCTION BOX.

*FIXTURE DIMENSIONS MAY VARY ± 0.25.

*RATED FOR DAMP LOCATION.



SFM1/53/200WINC/AH3/CG1/53



SFM1	H - 9"	W - 4.5"
SFM2	H - 12"	W - 5.5"



D – MOUNTING ADD-ONS



WJB4 1/2 JUNCTION BOX w/ 1/2" KNOCK OUTS
WJB4 3/4 JUNCTION BOX w/ 3/4" KNOCK OUTS

F – LIGHT SOURCE

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

INCANDESCENT (INC) MED E26

INC 100W - SFM1
INC 200W - SFM2

***IMPORTANT** – FOR INCANDESCENT (INC) LIGHT SOURCE OPTION, FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE LEFT.

EXAMPLE: / INC150W /

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
100WINC	100W	PER BULB SPECS	>90	120-277 VAC	N/A
150WINC	150W	PER BULB SPECS	>90	120-277 VAC	N/A
200WINC	200W	PER BULB SPECS	>90	120-277 VAC	N/A



I – GLASS OPTIONS

*NOTE: MUST USE TEMPERED GLASS FOR LIGHT FIXTURES USING HIGH INTENSITY DISCHARGE (HID) LIGHT SOURCE OPTION.

*3" GLASS AVAILABLE FOR SFM1

*4" GLASS AVAILABLE FOR SFM2



CL3 3" CLEAR GLASS

CL4 4" CLEAR GLASS

CLT3 3" CLEAR TEMPERED

CLT4 4" CLEAR TEMPERED



PR3 3" PRISMATIC GLASS

PR4 4" PRISMATIC GLASS



RE3 3" RED GLASS

RE4 4" RED GLASS



BL3 3" BLUE GLASS

BL4 4" BLUE GLASS



FR3 3" FROSTED GLASS

FR4 4" FROSTED GLASS

FRT3 3" FROSTED TEMPERED

FRT4 4" FROSTED TEMPERED



AH3 3" AMBER HYDE GLASS

AH4 4" AMBER HYDE GLASS



GR3 3" GREEN GLASS

GR4 4" GREEN GLASS

GLASS – DIMENSIONS

3" GLASS

Diameter 3.34"

Height 6.93"


Fitter 3.29"

4" GLASS

Diameter 4.34"

Height 8.37"

Fitter 4.29"




GLASS – MAX WATTAGE
3" GLASS – 100W INC / LED12W
4" GLASS – 200W INC / LED25W


J – ACCESSORIES

* 3" GUARDS AVAILABLE FOR SFM1


* 4" GUARDS AVAILABLE FOR SFM2




WG1 WIRE GUARD



WG2 WIRE GUARD



CG1 CAST GUARD



CG2 CAST GUARD