



# BASELITE – MID CENTURY MODERN – INC – SPEC SHEET



PROJECT NAME: \_\_\_\_\_ PROJECT TYPE: \_\_\_\_\_

| MODEL #  | /   | /        | /   | /   | /  | /      | / | X | / | X | / | X | / | X | / | X |
|----------|-----|----------|-----|-----|----|--------|---|---|---|---|---|---|---|---|---|---|
| EXAMPLE: | A   | B        | C   | D   | E  | F      | G | H | I | J | K |   |   |   |   |   |
|          | 3TD | 80-59-81 | BLC | CNK | 41 | 150INC |   |   |   |   |   |   |   |   |   |   |

\*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES:

---



---



---



## A - SHADES

### ***MID CENTURY MODERN PENDANTS***

- PEL** - 150WINC (MAX)
- PELB** - 100WINC (MAX)
- PEM** - 150WINC (MAX)
- PEMB** - 100WINC (MAX)
- PEN** - 150WINC (MAX)
- PENB** - 100WINC (MAX)

## B - FINISH OPTIONS

(SEE WEBSITE FOR SWATCH COLORS)  
 (\*SEE NOTES FOR LIMITATIONS\*)  
 14, 15, 16, 17, 18, 19, 19P, 20, 20P,  
 20PB, 20SB, 21, 21P, 22, 22P, 23, 23P,  
 38, 39, 40, 41, 41.5, 42, 43, 44, 45, 46,  
 48, 49, 50, 51, 52, 53, 54, 55, 57, 58, 59,  
 60, 61, 62, 63, 64, 65, 66, 70, 71, 72, 73,  
 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84,  
 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95,  
 96, 97, 98, 99, 100, MG.

## C – MOUNTING OPTIONS

**CORD MOUNT (INC)**  
 BLC, WHC, TCB, TCW, TCHB, TCHW, TLB, TLW,  
 LTLB, TLW, RCB, RCW, RCHB, RCHW, FHB,  
 FHW, HBLC, HWHC, CBLC, CWHC, CHB, CHW

**STEM MOUNT (INC)**  
 ST6, ST12, ST18, ST24, ST36, ST48, STXX

## D – MOUNTING ADD-ONS

**INC ADD-ONS**  
 CNK – MULTIPLE FIXTURE CANOPY  
 STC – STEM MOUNT CANOPY  
 SLC1/2" – SLOPE CEILING CANOPY ½"

## E – MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

## F – LIGHT SOURCE

(SEE PAGE 3 FOR WATTAGE LIMITATIONS)  
**INCANDESCENT (INC)**  
 100w, 150W, 200W

## G – LED COLOR TEMP

NOT AVAILABLE

## H – ELECTRICAL OPTION

NOT AVAILABLE

## I – GLASS OPTIONS

CALL FACTORY FOR REQUEST.

## J – ACCESSORIES


CALL FACTORY FOR REQUEST.

## K – ACCESSORY COLOR


SEE SECTION "B" FOR COLOR OPTIONS.

## NOTES


- (1). FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY.
  - (2). FINISH OPTIONS 19, 21, 22, 23, 75, 76, 77, 83, 84, 88, 93 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.
  - (3). FINISH OPTIONS FOR SHADES ≤ 10" IN DIAMETER ARE THE SAME INSIDE AND OUT OF FIXTURE. SHADES > 10" IN DIAMETER ARE WHITE ON THE INSIDE.
  - (4). FINISH OPTIONS 19, 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.
  - (5). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.
  - (5). COLOR CORDS ARE NOT APPLICABLE FOR LED OPTIONS.
- \*ALL FIXTURES MOUNT TO A 4-0 JUNCTION BOX.  
 \*FIXTURE DIMENSIONS MAY VARY ±0.25.



**PEL** H-21" W-16"  
**PELB** H-11" W-9.5"



**PEM** H-12" W-22"  
**PEMB** H-9" W-14"



**PEN** H-24" W-10"  
**PENB** H-14" W-7.5"



**C - MOUNTING OPTIONS**

**D - MOUNTING ADD-ONS**

**STEM MOUNT**

\*STEMS RATED FOR DAMP LOCATION \* 1/4" NPT AND 3/4" NPT AVAILABLE UPON REQUEST




**ST(XX)** STEM- 1/2" NPT

XX = LENGTH OF STEM  
(EXAMPLE - "ST18" = STEM MOUNT 18" LENGTH)  
\*CANOPY NOT INCLUDED, ADD IN SECTION D


**MOUNTING ADD-ON**



**CNK** CANOPY For MULTIPLE FIXTURES  
\*CNK dimensions vary on number of fixtures applied



**SLC 1/2"** SLOPE CEILING CANOPY 1/2"  
\*(Slopes To 20 Degrees)



**STC 1/2"** 1/2" STEM MOUNT CANOPY

**INCANDESCENT CORD MOUNTS**

\*INCANDESCENT MAX WATTAGE 150 WATT. CALL FACTORY FOR HIGHER WATTAGES. LOOPS, CABLES, AND CHAINS AVAILABLE ONLY FOR INCANDESCENT \*CORDS RATED FOR DRY LOCATION \*CANOPY DIMENSIONS: .625" (H) 5.25" (W)



**BLC** 8' BLACK CORD  
**WHC** 8' WHITE CORD



**TCB** 8' BLACK CORD, CABLE, and LOOP  
**TCW** 8' WHITE CORD, CABLE, and LOOP



**TCHB** 8' BLACK CORD, 3' CHAIN, and LOOP  
**TCHW** 8' WHITE CORD, 3' CHAIN, and LOOP




**TLB** 8' BLACK TELEPHONE CORD AND CABLE  
**TLW** 8' WHITE TELEPHONE CORD AND CABLE  
\* Not available H.I.D.




**RCB** 8' BLACK CORD, CABLE, and LOOP  
**RCW** 8' WHITE CORD, CABLE, and LOOP



**RCHB** 8' BLACK CORD, 3' CHAIN, and LOOP  
**RCHW** 8' WHITE CORD, 3' CHAIN, and LOOP



**FHB** 8' BLACK CORD WITH FLAT HUB  
**FHW** 8' WHITE CORD WITH FLAT HUB



**CBLC** 8' BLACK CORD and CABLE  
**CWLC** 8' WHITE CORD and CABLE



**CHB** 8' BLACK CORD, 3' CHAIN, and LOOP  
**CHW** 8' WHITE CORD, 3' CHAIN, and LOOP  
\* Loop may vary due to shade style

**F – LIGHT SOURCE**

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

**INCANDESCENT (INC) MED E26**

**INC 100W (MAX)** – PELB, PEMB, PENB  
**INC 150W (MAX)** - PEL, PEM, PEN

\*IMPORTANT – FOR LIGHT EMITTED DIODE (LED) LIGHT SOURCE OPTION, FIXTURES ARE LIMITED DUE TO SIZE OF THE SIZE OF THE DRIVER.

EXAMPLE: / 150INC /

| OPTION | WATTAGE | LUMENS         | CRI | VOLTAGE     | DIMMING |
|--------|---------|----------------|-----|-------------|---------|
| 100INC | 100W    | PER BULB SPECS | >90 | 120-277 VAC | N/A     |
| 150INC | 150W    | PER BULB SPECS | >90 | 120-277 VAC | N/A     |