



# BASELITE – SCHOOLHOUSE – INC – SPEC SHEET



PROJECT NAME: \_\_\_\_\_ PROJECT TYPE: \_\_\_\_\_

MODEL #	/	/	/	/	/	/	/	/	/
EXAMPLE:	A	B	C	D	E	F	G	H	I
	SCP	PSTL	41.5	ST18	STC	41.5	12LED	3K	LDM120

NOTES:



## A - SHADES

### SCHOOL HOUSE

- SKT** -100W (MAX) 8" GLASS
- S2R8** -100W (MAX) 8" GLASS
- SCF** -100W (MAX) 12" GLASS 150W (MAX) 14" & 16" GLASS 200W (MAX) 18" GLASS
- SCFS** -100W(MAX) 12" GLASS 150W (MAX) 14" & 16" GLASS 200W (MAX) 18" GLASS
- FNF** -100W (MAX) 12" GLASS 150W (MAX) 14" & 16" GLASS
- FNP** -100W (MAX) 12" GLASS 150W (MAX) 14" & 16" GLASS
- SCP** -200W (MAX) 18" GLASS
- SCPC** -200W (MAX) 18" GLASS
- SCPL** -200W (MAX) 18" GLASS
- DLP** -100W (MAX) 12" GLASS 150W (MAX) 14" & 16" GLASS 200W (MAX) 18" GLASS

## B – GLASS OPTIONS

- 6" FITTER**  
SCH14, SCO12, SHO14, SHO16, SHO18, SQO12, SOB12, SOB14, SOB16, SOB18, PSGN, PSRD, PSTL, PSGY
- 4" FITTER**  
PSBL, SQO8, AC, SHC10
- 4" THREADED FITTER**  
BAF.PSGN, BAF.PSRD, BAF.PSTL, BAF.PSBL

## C - FINISH OPTIONS

- (SEE WEBSITE FOR SWATCH COLORS)  
(\*SEE NOTES FOR LIMITATIONS\*)
- 14, 15, 16, 17, 18, 19, 19P, 20, 20P, 20PB, 20SB, 21, 21P, 22, 22P, 23, 23P, 38, 39, 40, 41, 41.5, 43, 44, 48, 49, 50, 51, 52, 53, 55, 57, 58, 59, 61, 62, 63, 78, 80, 81, 82, 85, 86, 87, 89, 91, 92, 94, 95, 97, 98, 99, 100

## D – MOUNTING OPTIONS

- BLC - 8' BLACK CORD
- WHC - 8' WHITE CORD
- TCHB - 8' CORD, 3' CHAIN, & LOOP
- TCHW - 8' CORD, 3' CHAIN, & LOOP
- CBLC - 8' CORD & CABLE
- CWLC - 8' CORD & CABLE
- STXX - STEM (XX=STEM LENGTH)

## E – MOUNTING ADD-ONS

- SLC ½" – SLOPE CEILING CANOPY ½"
- STC ½" – STEM CANOPY ½"

## F – MOUNTING COLOR

\*SEE SECTION "C" FOR MOUNTING COLOR OPTIONS.

## G – LIGHT SOURCE

(SEE SECTION "G" FOR LIGHT SOURCE AND WATTAGE OPTIONS)

**INCANDESCENT (INC)**  
100W, 150W, 200W

## H – LED COLOR

(ONLY APPLICABLE FOR LED LIGHT SOURCE. SKIP THIS SECTION IF OPTION DOES NOT APPLY.)

- 27K – 2700 K
- 3K – 3000 K
- 35K – 3500 K
- 4K – 4000 K
- 5K – 5000 K


## I – ELECTRICAL OPTIONS

(ONLY APPLICABLE FOR LED LIGHT SOURCE. SKIP THIS SECTION IF OPTION DOES NOT APPLY.)


- LED DIMMING OPTIONS**  
LDM120  
LDM277  
LDM0-10

## NOTES

- \*ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.)
- \*FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY
- \*FINISH OPTIONS 19, 21, 22, 23 ARE AN ACID FINISH AND IS APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.
- \*FINISH OPTIONS 61 & 62 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.
- \*FIXTURE DIMENSIONS MAY VARY ± 0.25"



**SKT** H-3" W-4"




**SCF** H-8.75" W-6"

\*FLUSH MOUNT, MOUNTING OPTIONS DO NOT APPLY




**SCFS** H-6" W-6"


\*FLUSH MOUNT, MOUNTING OPTIONS DO NOT APPLY




**FNP** H-10.5" W-6"



**SCP** H-6" W-6"




**DPL** H-10" W-6"



**FNF** H-7" W-6"


\*FLUSH MOUNT, MOUNTING OPTIONS DO NOT APPLY



**SCPL** H-29.25" W-20.5"



**S2R8** H-2.5" W-4.5"



**SCPC** H-3" W-6"



**B – GLASS OPTIONS**

\*NOTE – THE LIST OF "SHADES" ARE ALL APPLICABLE WITH THE GLASS OPTIONS SHOWN IN THIS SECTION.

**6" FITTER  
SHADES**

- SCF
- SCFS
- SCP
- SCPC
- SCPL
- DLP



**SHC14** – 14" CLEAR GLASS



**SHO12** – 12" OPAL GLASS

**SHO14** – 14" OPAL GLASS

**SHO16** – 16" OPAL GLASS

**SHO18** – 18" OPAL GLASS



**SQO12** – 12" SQUARE OPAL GLASS



**SOB12** – 12" SLANT OPAL GLASS

**SOB14** – 14" SLANT OPAL GLASS

**SOB16** – 16" SLANT OPAL GLASS

**SOB18** – 18" SLANT OPAL GLASS



**PSGN**  
12" OPAL GLASS  
WITH LIME GREEN AND BLACK  
PINSTRIPE HAND-PAINTED LINES



**PSRD**  
12" OPAL GLASS  
WITH RED-ORANGE AND BLACK  
PINSTRIPE HAND-PAINTED LINES



**PSTL**  
12" OPAL GLASS  
WITH TEAL AND BLACK  
PINSTRIPE HAND-PAINTED LINES



**PSGY**  
12" OPAL GLASS  
WITH GREY PINSTRIPE  
HAND-PAINTED LINES

\*NOTE – THE LIST OF "SHADES" ARE ALL APPLICABLE WITH THE GLASS OPTIONS SHOWN IN THIS SECTION. FOR LED OPTION 12W MAX.

**4" FITTER  
SHADES**

- FNF
- FNP
- S2R8



**PSBL**  
8" OPAL GLASS  
WITH NAVY BLUE AND BLACK  
PINSTRIPE HAND-PAINTED LINES



**SQO8**  
8" SQUARE  
OPAL GLASS



**AC**  
7" CLEAR TEXTURED  
ACORN GLASS



**SHC10**  
10" CLEAR GLASS

\*NOTE – THE LIST OF "SHADES" ARE ALL APPLICABLE WITH THE GLASS OPTIONS SHOWN IN THIS SECTION. FOR LED OPTION 12W MAX.

**4" THREADED  
FITTER  
SHADES**

- SKT



**BAF.PSGN**  
8" OPAL GLASS  
WITH LIME GREEN PINSTRIPE  
HAND-PAINTED LINES



**BAF.PSRD**  
8" OPAL GLASS  
WITH RED-ORANGE PINSTRIPE  
HAND-PAINTED LINES



**BAF.PSTL**  
8" OPAL GLASS  
WITH TEAL PINSTRIPE  
HAND-PAINTED LINES



**BAF.PSBL**  
8" OPAL GLASS  
WITH NAVY BLUE PINSTRIPE  
HAND-PAINTED LINES



**D - MOUNTING OPTIONS**

**STEM MOUNTS**

\*STEMS RATED FOR DAMP LOCATION

\*CANOPY NOT INCLUDED, ADD IN SECTION D

\*AVAILABLE MODELS FOR THE 1/4" STEM OPTION

**SKT**  
**S2R8**



**ST(XX)** STEM- 1/4" NPT

XX = LENGTH OF STEM  
(EXAMPLE – "ST18" = STEM MOUNT 18" LENGTH)  
\*CANOPY NOT INCLUDED, ADD IN SECTION E

\*AVAILABLE MODELS FOR THE 1/2" STEM OPTION

**SCP**  
**DPL**  
**FNP**



**ST(XX)** STEM- 1/2" NPT

XX = LENGTH OF STEM  
(EXAMPLE – "ST18" = STEM MOUNT 18" LENGTH)  
\*CANOPY NOT INCLUDED, ADD IN SECTION E

**INCANDESCENT CORD MOUNTS**

\*CORDS RATED FOR DRY LOCATION

\*CANOPY DIMENSIONS: .625" (H) 5.25" (W)


\*AVAILABLE MODELS FOR INC CORD OPTION

**SCP**  
**SKT**  
**S2R8**



**BLC** 8' BLACK CORD (INCLUDES INC CANOPY)

**WHC** 8' WHITE CORD (INCLUDES INC CANOPY)



**TCHB** 8' BLACK CORD, 3' CHAIN, and LOOP

**TCHW** 8' WHITE CORD, 3' CHAIN, and LOOP  
\*MUST USE FOR 18" GLASS OPTION




**CBLC** 8' BLACK CORD and CABLE

**CWLC** 8' WHITE CORD and CABLE  
\*MUST USE FOR 18" GLASS OPTION


**E - MOUNTING ADD-ONS**

**INCANDESCENT 1/2" STEM ADD-ONS**



**SLC 1/2"** - SLOPE CEILING CANOPY 1/2"

\*(Slopes To 20 Degrees)



**STC 1/2"** - STEM MOUNT CANOPY 1/2"

**G – LIGHT SOURCE**

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

INCANDESCENT (INC) MED E26						
OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING	
100WINC	100W	PER BULB SPECS	>90	120-277 VAC	N/A	
150WINC	150W	PER BULB SPECS	>90	120-277 VAC	N/A	
200WINC	200W	PER BULB SPECS	>90	120-277 VAC	N/A	
<p>*IMPORTANT – FOR INCANDESCENT (INC) LIGHT SOURCE OPTION, FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE RIGHT. <b>EXAMPLE: /INC100W /</b></p>		<p><b>INC 100W(MAX)</b> - SKT, S2R8 (WITH 8" GLASS OPTION) SCF, SCFS, FNF, DLP, S2R8 (WITH 12" GLASS OPTION)  <b>INC 150W(MAX)</b> - SKT, SCF, SCFS, FNF, DLP, S2R8 (WITH 14" &amp; 16" GLASS OPTION)  <b>INC 200W(MAX)</b> - SCF, SCFS, DLP, SCPL, SCPC, SCP (WITH 18" GLASS OPTION)</p>				