



# BASELITE – POLE LIGHTS – CF – SPEC SHEET



PROJECT NAME: \_\_\_\_\_ PROJECT TYPE: \_\_\_\_\_

<b>MODEL #</b>	/	/	/	X	/	/	X	/	X	/	X	/	X	/	X	/	X
EXAMPLE:	AS24	74	3STP8	-	41	57CF	-	-	-	-	-	-	-	-	-	-	-

\*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES:

---



---



---



## A - SHADES

- ASTRO**  
**AS116** – 57WCF (MAX)  
**AS120** – 57WCF (MAX)  
**AS24** – 57WCF (MAX)  
**AST24** – 57WCF (MAX)

- EURO**  
**EUP30** – 70WCF (MAX)  
**EUP130** – 70WCF (MAX)

- ISLAND LITES**  
**IL202** – 57WCF (MAX)  
**IL203** – 57WCF (MAX)  
**IL262** – 57WCF (MAX)  
**IL263** – 57WCF (MAX)  
**IM18** – 57WCF (MAX)  
**IM20** – 57WCF (MAX)  
**IMC20** – 57WCF (MAX)  
**IW20** – 57WCF (MAX)  
**INT20** – 57WCF (MAX)

- METRO**  
**ME18** – 70WCF (MAX)  
**ME24** – 70WCF (MAX)  
**MER18** – 70WCF C (MAX)  
**MER24** – 70WCF (MAX)  
**MES18** – 70WCF (MAX)  
**MES24** – 70WCF (MAX)

## B - FINISH OPTIONS

(SEE WEBSITE FOR SWATCH COLORS)  
 (\*SEE NOTES FOR LIMITATIONS\*)  
 14, 15, 16, 17, 18, 19, 19P, 20, 20P, 20PB,  
 20SB, 21, 21P, 22, 22P, 23, 23P, 38, 39, 40,  
 41, 41.5, 42, 43, 44, 45, 46, 48, 49, 50, 51,  
 52, 53, 54, 55, 57, 58, 59, 60, 61, 62, 63, 64,  
 65, 66, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79,  
 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91,  
 92, 93, 94, 95, 96, 97, 98, 99, 100, MG.

## C – MOUNTING OPTIONS

- POST MOUNTS**  
 PM10, PM15, PM18, PM20, PM21,  
 PM25, PM30, PM35, PM40, PM45,  
 PM50, PM55, PM56, PM60, PM61,  
 PM62, PM63, PM70, PM71, PM72,  
 PM73

**POLE MOUNTS**

TYPE A	TYPE B	TYPE C
3AAP8	3ABP8	3ACP8
3AAP10	3ABP10	3ACP10
3AAP12	3ABP12	3ACP12
4AAP8	4ABP8	4ACP8
4AAP10	4ABP10	4ACP10
4AAP12	4ABP12	4ACP12
3FAP8	3FBP8	3FCP8
3FAP10	3FBP10	3FCP10
3FAP12	3FBP12	3FCP12
4FAP8	4FBP8	4FCP8
4FAP10	4FBP10	4FCP10
4FAP12	4FBP12	4FCP12

TYPE D	TYPE E	TYPE G
3ADP8	3AEP8	3AGP8
3ADP10	3AEP10	3AGP10
3ADP12	3AEP12	3AGP12
4ADP8	4AEP8	4AGP8
4ADP10	4AEP10	4AGP10
4ADP12	4AEP12	4AGP12
3FDP8	3FEP8	3FGP8
3FDP10	3FEP10	3FGP10
3FDP12	3FEP12	3FGP12
4FDP8	4FEP8	4FGP8
4FDP10	4FEP10	4FGP10
4FDP12	4FEP12	4FGP12

**POLE MOUNTS**

ALUMINUM FLUTED	DIRECT BURIAL
3FFP8	3DBP8
3FFP10	3DBP10
3FFP12	3DBP12
4FFP8	4DBP8
4FFP10	4DBP10
4FFP12	4DBP12

STEEL POLES (ROUND)	STEEL POLES (SQUARE)
3STP8	3SQP8
3STP10	3SQP10
3STP12	3SQP12
4STP8	4SQP8
4STP10	4SQP10
4STP12	4SQP12

## D – MOUNTING ADD-ONS

NOT AVAILABLE

## E – MOUNTING COLOR

SEE SECTION “B” FOR COLOR OPTIONS.

## F – LIGHT SOURCE

(SEE PAGE 2 FOR WATTAGE LIMITATIONS)  
**COMPACT FLUORESCENT (CF)**  
 42W, 57W, 70W

## G – LED COLOR TEMP

NOT AVAILABLE

## H – ELECTRICAL OPTION

(SEE PAGE 2 FOR DIMMING OPTIKON SPECIFICATIONS)  
**CDM-120**  
**CDM-277**  
**CDM-120/277**

## I – GLASS OPTIONS

NOT AVAILABLE

## J – ACCESSORIES

NOT AVAILABLE

## K – ACCESSORY COLOR

SEE SECTION “B” FOR COLOR OPTIONS.


## NOTES

- (1). FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY.
- (2). FINISH OPTIONS 19, 21, 22, 23, 75, 76, 77, 83, 84, 87, 88 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.
- (3). FINISH OPTIONS 19, 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.
- (4). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.


**A – SHADES**

**POLE LIGHTS**


**ASTRO**




**AS24** H-29" W-24"



**AS116** H-16" W-16"




**AS120** H-18" W-20"




**AST24** H-29" W-24"

**EURO**




**EUP30** H-30" W-30"



**EUP130** H-30" W-30"

**ISLAND LITES**




**IL202** H-17" W-20" F-2 3/8"

**IL203** H-17" W-20" F-3"


**IL262** H-17" W-26" F-2 3/8"

**IL263** H-17" W-26" F-3"




**IM18** H-14.5" W-18" F-3"


**IM20** H-14.5" W-20" F-3"



**IMC20** H-24" W-20" F-3"




**IW20** H-17" W-20" F-3"




**INT20** H-28" W-20" F-3"

**METRO**




**ME18** H-27" W-18"

**ME24** H-27" W-24"



**MER18** H-27" W-18"

**MER24** H-27" W-24"



**MES18** H-27" W-18"

**MES24** H-27" W-24"





**F – LIGHT SOURCE**

BASELITE’S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

**COMPACT FLUORESCENT (CF)**

**CF 26W, 32W, 39, 42 OR 57(MAX)-** AS116, AS120, AS24, AST24, IL202, IL203, IL262, IL263, IM18, IM20, IMC20, IW20, INT20  
**CF 26W, 32W, 42, 57, OR 70(MAX)-** EUP30, EUP130, ME18, ME24, MER18, MER24, MES18, MES24

**\*IMPORTANT – FOR COMPACT FLUORESCENT (CF) LIGHT SOURCE, FIXTURES ARE LIMITED DUE TO THE SIZE OF THE SHADE. PLEASE SEE THE CHART TO THE LEFT TO SEE WHAT WATTAGE IS COMPARABLE FOR EACH FIXTURE WHEN ORDERING.**

**EXAMPLE: /CF42W /**

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
CF42W	42W	PER BULB SPECS	>90	120-277 VAC	0-10V
CF57W	57W	PER BULB SPECS	>90	120-277 VAC	0-10V
CF70W	70W	PER BULB SPECS	>90	120-277 VAC	0-10V

**H – ELECTRICAL OPTION**

MOST BASELITE’S ELECTRICAL OPTIONS ARE ONLY COMPATIBLE FOR CERTAIN FIXTURES. PLEASE SEE NOTES BELOW AND FOR FURTHER DETAILS CONTACT THE FACTORY. FOR DIMMING BALLAST OPTION, PLEASE CHOOSE MARK X OR MARK VII, SO RESTRICTIONS APPLY DUE TO THE SIZE OF THE BALLAST AND FIXTURE.

**COMPACT FLUORESCENT DIMMING OPTIONS**

PROVIDED WITH ADVANCE TRANSFORMER, PLEASE CHOOSE MARK 10 OR MARK 7 WITH SPECIFIED VOLTAGE FROM THE LIST BELOW. CONTACT BALLAST MANUFACTURER FOR SPECIFICATIONS.

**CDM7-120/277 -** ADVANCE MARK 7 0-10v ELECTRICAL BALLST – 120/277 VOLT

**CDM10-120 -** ADVANCE MARK 10 ELECTRICAL BALLST – 120 VOLT

**CDM10-277 -** ADVANCE MARK 10 ELECTRICAL BALLST – 277 VOLT

**NOTES:**

FOR COMPACT FLUORESCENT DIMMING OPTION:

**MARK 7 –** 120 THROUGH 277V. BALLASTS MAY BE REMOTE MOUNTED UP TO 6 IN. AWAY FROM LAMPS. 100% - 3% FULL RANGE CONTINUOUS DIMMING. SOME LIGHT MANUFACTURERS RECOMMEND BURNING IN NEW LAMPS 100 HOURS AT FULL LIGHT OUTPUT BEFORE DIMMING. CONSULT LIGHT MANUFACTURER.

**MARK 10 –** 120V ONLY. ONE AND TWO-LAMP BALLASTS MAY BE REMOTE MOUNTED UP TO 6 FT. AWAY FROM LAMPS. THREE LAMP BALLASTS MAY NOT BE REMOTE MOUNTED. 100% - 5% FULL RANGE CONTINUOUS DIMMING. SOME LIGHT MANUFACTURERS RECOMMEND BURNING IN NEW LAMPS 100 HOURS AT FULL LIGHT OUTPUT BEFORE DIMMING. CONSULT LIGHT MANUFACTURER.