







**C – MOUNTING OPTIONS**

**CORD MOUNTS**


BASELITE USES A DURABLE SJT CORD FOR ALL CORD MOUNT OPTIONS. ALL CORD MOUNTS COME WITH AN 6" ROUND CANOPY.




**CBLC** 8' BLACK CORD, CABLE & CANOPY  
**CWHC** 8' WHITE CORD, CABLE & CANOPY




**TLB** 2.5' BLACK TELEPHONE CABLE  
**TLW** 2.5' WHITE TELEPHONE CABLE



**TCB** 8' CABLE, BLACK CORD, CANOPY & LOOP  
**TCW** 8' CABLE, WHITE CORD, CANOPY & LOOP



**BLC** 8' BLACK CORD AND CANOPY  
**WHC** 8' WHITE CORD AND CANOPY



**3CBLC** 3 CABLE AND BLACK CORD & CANOPY  
**3CWHC** 3 CABLE AND WHITE CORD & CANOPY



**HKBC** 3/4" HOOK WITH 8' BLACK CORD  
**HKWC** 3/4" HOOK WITH 8' WHITE CORD

**STEM MOUNTS**




**ST(XX)** STEM- 3/4" NPT  
XX = LENGTH OF STEM  
(EXAMPLE – "ST18" = STEM MOUNT 18" LENGTH)  
\*CANOPY NOT INCLUDED, ADD IN SECTION D


**D - MOUNTING ADD-ONS**

**INCANDESCENT MOUNTING ADD-ONS**

\* FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY.



**SLC 1/2"** SLOPE CEILING CANOPY 1/2"  
**SLC 3/4"** SLOPE CEILING CANOPY 3/4"  
\*(Slopes To 20 Degrees)



**STC 1/2"** 1/2" STEM MOUNT CANOPY



**HB3 - 3/8" HUB**




**F – LIGHT SOURCE**

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.


INCANDESCENT (INC) <small>MED E26</small>					
<b>INC 150W (MAX)- PC12</b> <b>INC 300W (MAX)- PC16, PC22</b>			<b>*IMPORTANT – FOR LIGHT EMITTED DIODE (LED) LIGHT SOURCE OPTION FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE LEFT.</b>  EXAMPLE: / 300WINC /		
OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
150WINC	150W	PER BULB SPECS	>90	120-277 VAC	N/A
300WINC	300W	PER BULB SPECS	>90	120-277 VAC	N/A

**J – ACCESSORIES**


\*NOTE: MUST USE TEMPERED GLASS FOR LIGHT FIXTURES USING HIGH INTENSITY DISCHARGE (HID) LIGHT SOURCE OPTION.




**CRL12** - 12" CLEAR CURVED LENS  
**CRL16** - 16" CLEAR CURVED LENS  
**CRL22** - 22" CLEAR CURVED LENS



**ARFL12** - 12" FLAT CLEAR LENS WITH CLIPS  
**ARFL16** - 16" FLAT CLEAR LENS WITH CLIPS  
**ARFL22** - 22" FLAT CLEAR LENS WITH CLIPS




**ARFR12** - 12" FLAT METAL RING  
**ARFR16** - 16" FLAT METAL RING  
**ARFR22** - 22" FLAT METAL RING




**FLE12** - 12" FLAT CLEAR LENS WITH CLIPS  
**FLE16** - 16" FLAT CLEAR LENS WITH CLIPS  
**FLE22** - 22" FLAT CLEAR LENS WITH CLIPS



**BLE12** - 12" FLAT CLEAR LENS WITH BAND  
**BLE16** - 16" FLAT CLEAR LENS WITH BAND  
**BLE22** - 22" FLAT CLEAR LENS WITH BAND



**LL12** - 12" CLEAR CONICAL LENS  
**LL16** - 16" CLEAR CONICAL LENS  
**LL22** - 22" CLEAR CONICAL LENS



**LGR12** - 12" LOUVERED GRILL  
**LGR16** - 16" LOUVERED GRILL  
**LGR22** - 22" LOUVERED GRILL



**FWG16** - 16" FULL WIRE GRILL  
**FWG22** - 22" FULL WIRE GRILL



**DRL16** - 16" PRISMATIC DROP LENS  
**DRL22** - 22" PRISMATIC DROP LENS



**TRS16** - 16" TOP RING ALUMINUM SHIELD  
**TRS22** - 22" TOP RING ALUMINUM SHIELD



**BRS16** - 16" BOTTOM RING ALUMINUM SHIELD  
**BRS22** - 22" BOTTOM RING ALUMINUM SHIELD