



BASELITE – POLE LIGHTS – LED – SPEC SHEET



PROJECT NAME: _____ PROJECT TYPE: _____

MODEL #	/	/	/	X	/	/	/	/	X	X	/
EXAMPLE:	A	B	C	D	E	F	G	H	I	J	K
	AS24	74	3STP8	-	41	50W	3K	LDM120	-	-	-

*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES:



A - SHADES

- ASTRO**
AS116 - 25WLED (MAX)
AS120 - 25WLED (MAX)
AS24 - 35WLED (MAX)
AST24 - 35WLED (MAX)

- EURO**
EUP30 - 35WLED (MAX)
EUP130 - 35WLED (MAX)

- ISLAND LITES**
IL202 - 25WLED (MAX)
IL203 - 25WLED (MAX)
IL262 - 25WLED (MAX)
IL263 - 25WLED (MAX)
IM18 - 25WLED (MAX)
IM20 - 25WLED (MAX)
IMC20 - 25WLED (MAX)
IW20 - 25WLED (MAX)
INT20 - 50WLED (MAX)

- METRO**
ME18 - 35WLED (MAX)
ME24 - 35WLED (MAX)
MER18 - 35WLED (MAX)
MER24 - 35WLED (MAX)
MES18 - 35WLED (MAX)
MES24 - 35WLED (MAX)

B - FINISH OPTIONS

(SEE WEBSITE FOR SWATCH COLORS)
 (*SEE NOTES FOR LIMITATIONS*)
 14, 15, 16, 17, 18, 19, 19P, 20, 20P, 20PB,
 20SB, 21, 21P, 22, 22P, 23, 23P, 38, 39, 40,
 41, 41.5, 42, 43, 44, 45, 46, 48, 49, 50, 51,
 52, 53, 54, 55, 57, 58, 59, 60, 61, 62, 63, 64,
 65, 66, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79,
 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91,
 92, 93, 94, 95, 96, 97, 98, 99, 100, MG.

C – MOUNTING OPTIONS

POST MOUNTS
 PM10, PM15, PM18, PM20, PM21,
 PM25, PM30, PM35, PM40, PM45,
 PM50, PM55, PM56, PM60, PM61,
 PM62, PM63, PM70, PM71, PM72,
 PM73

POLE MOUNTS

TYPE A	TYPE B	TYPE C
3AAP8	3ABP8	3ACP8
3AAP10	3ABP10	3ACP10
3AAP12	3ABP12	3ACP12
4AAP8	4ABP8	4ACP8
4AAP10	4ABP10	4ACP10
4AAP12	4ABP12	4ACP12
3FAP8	3FBP8	3FCP8
3FAP10	3FBP10	3FCP10
3FAP12	3FBP12	3FCP12
4FAP8	4FBP8	4FCP8
4FAP10	4FBP10	4FCP10
4FAP12	4FBP12	4FCP12

TYPE D	TYPE E	TYPE G
3ADP8	3AEP8	3AGP8
3ADP10	3AEP10	3AGP10
3ADP12	3AEP12	3AGP12
4ADP8	4AEP8	4AGP8
4ADP10	4AEP10	4AGP10
4ADP12	4AEP12	4AGP12
3FDP8	3FEP8	3FGP8
3FDP10	3FEP10	3FGP10
3FDP12	3FEP12	3FGP12
4FDP8	4FEP8	4FGP8
4FDP10	4FEP10	4FGP10
4FDP12	4FEP12	4FGP12

POLE MOUNTS

ALUMINUM FLUTED	DIRECT BURIAL
3FFP8	3DBP8
3FFP10	3DBP10
3FFP12	3DBP12
4FFP8	4DBP8
4FFP10	4DBP10
4FFP12	4DBP12

STEEL POLES (ROUND)	STEEL POLES (SQUARE)
3STP8	3SQP8
3STP10	3SQP10
3STP12	3SQP12
4STP8	4SQP8
4STP10	4SQP10
4STP12	4SQP12

D – MOUNTING ADD-ONS

NOT AVAILABLE

E – MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

F – LIGHT SOURCE

(SEE PAGE 2 FOR WATTAGE LIMITATIONS)
LIGHT EMITTED DIODE (LED)
 10W, 12W, 25W, 35W

*NOTE – MAX WATTAGE IS LISTED NEXT TO THE SHADE MODEL NUMBER IN SECTION "A". ALL WATTAGES BELOW THAT ARE ALSO AVAILABLE FOR THE SAME MODEL NUMBER.

G – LED COLOR TEMP

- 27K – 2700 K
- 3K – 3000 K
- 35K – 3500 K
- 4K – 4000 K
- 5K – 5000 K

H – ELECTRICAL OPTION

(SEE PAGE 2 FOR DIMMING OPTION SPECIFICATIONS)
LDM120
LDM0-10

I – GLASS OPTIONS

NOT AVAILABLE

J – ACCESSORIES

NOT AVAILABLE

K – ACCESSORY COLOR

SEE SECTION "B" FOR COLOR OPTIONS.


NOTES

- (1). FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY.
- (2). FINISH OPTIONS 19, 21, 22, 23, 75, 76, 77, 83, 84, 87, 88 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.
- (3). FINISH OPTIONS 19, 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.
- (4). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.


A – SHADES

POLE LIGHTS


ASTRO




AS24 H-29" W-24"



AS116 H-16" W-16"




AS120 H-18" W-20"




AST24 H-29" W-24"

EURO




EUP30 H-30" W-30"



EUP130 H-30" W-30"

ISLAND LITES




IL202 H-16.5" W-20" F-2 3/8"

IL203 H-18.5" W-20" F-3"


IL262 H-16.5" W-26" F-2 3/8"

IL263 H-18.5" W-26" F-3"




IM18 H-16.5" W-18" F-3"


IM20 H-16.5" W-20" F-3"



IMC20 H-22" W-20" F-3"




IW20 H-17" W-20" F-3"




INT20 H-28" W-20" F-3"

METRO




ME18 H-27" W-18"

ME24 H-27" W-24"



MER18 H-27" W-18"

MER24 H-27" W-24"



MES18 H-27" W-18"

MES24 H-27" W-24"



F – LIGHT SOURCE

BASELITE’S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

LIGHT EMITTING DIODE (LED)

LED 25W (MAX) – AS116, AS120, IL203, IL203, IL262, IL263, IM18, IM20, IMC20, IW20
LED 35W (MAX) – AS24, AST24, EUP30, EUP130, ME18, ME24, MER18, MER24, MES18, MES24
LED 50W (MAX) – INT20

***IMPORTANT** – FOR LIGHT EMITTED DIODE (LED) LIGHT SOURCE OPTION, FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE MAX WATTAGE AVAILABILITY. **EXAMPLE: /LED50W /**

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
LED10W	10W	1570	>90	120-277 VAC	See section "H"
LED12W	12W	1596	>90	120-277 VAC	See section "H"
LED25W	25W	3125	>90	120-277 VAC	See section "H"
LED35W	35W	4200	>90	120-277 VAC	See section "H"
LED50W	50W	5750	>90	120-277 VAC	See section "H"

@3500K

H – ELECTRICAL OPTION

MOST BASELITE’S ELECTRICAL OPTIONS ARE ONLY COMPATIBLE FOR CERTAIN FIXTURES. PLEASE SEE NOTES BELOW AND FOR FURTHER DETAILS CONTACT THE FACTORY. FOR DIMMING BALLAST OPTION, PLEASE CHOOSE MARK X OR MARK VII, SO RESTRICTIONS APPLY DUE TO THE SIZE OF THE BALLAST AND FIXTURE.

LED DIMMING OPTIONS

FOR TRIAC OR 0-10V OPTOIN CHOOSE FROM THE FOLLOWING. CONTACT DRIVER MANUFACTURER FOR SPECIFICATIONS.

LDM120 - TRIAC DIMMING AT 120 VOLT

LDM0-10V – 0 – 10v