



# BASELITE - BISTRO – INC – SPECIFICATION SHEET



PROJECT NAME: \_\_\_\_\_ PROJECT TYPE: \_\_\_\_\_

MODEL #	/	/	/	X	/	X	/	X	/	X	/	X	/	X	/	X
EXAMPLE:	W513	41	BLC			60W										

\*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES:



S2H2/41-20/BLC/100INC

## A - SHADES

### BISTRO COLLECTION

- S2H1 - (100W MAX)
- S2H2 - (100W MAX)
- S2H3 - (100W MAX)
- S2H4 - (100W MAX)
- S2H5 - (100W MAX)
- S2H6 - (100W MAX)
- S2H7 - (100W MAX)
- S2H8 - (100W MAX)
- S2H9 - (100W MAX)
- S2H10 - (100W MAX)
- CA57 - (100W MAX)
- GBL6 - (100W MAX)
- WMCS - (100W MAX)
- S2KT6 - (100W MAX)
- FMS14 - (100W MAX)

## B - FINISH OPTIONS

(SEE WEBSITE FOR SWATCH COLORS)  
 (\*SEE NOTES FOR LIMITATIONS\*)  
 14, 15, 16, 17, 18, 19, 19P, 20, 20P, 20PB,  
 20SB, 21, 21P, 22, 22P, 23, 23P, 38, 39, 40,  
 41, 41.5, 42, 43, 44, 45, 46, 48, 49, 50, 51,  
 52, 53, 54, 55, 57, 58, 59, 60, 61, 62, 63, 64,  
 65, 66, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79,  
 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91,  
 92, 93, 94, 95, 96, 97, 98, 99, 100, MG.

## C – MOUNTING OPTIONS

- 1/2" WALL MOUNT  
WM20, WM21, WM23, WM24, WM25, WM26, WM29, WM29V
- CORD MOUNT  
BLC, WHC
- STEM MOUNT  
ST6, ST12, ST18, ST24, ST36, ST48, STXX

## D – MOUNTING ADD-ONS

NOT AVAILABLE

## E – MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

## F – LIGHT SOURCE

(SEE PAGE 3 FOR WATTAGE LIMITATIONS)  
INCANDESCENT (INC)  
 60W, 100W (MAX)

## G – LED COLOR TEMP

NOT AVAILABLE

## H – ELECTRICAL OPTION

NOT AVAILABLE

## I – GLASS OPTIONS

NOT AVAILABLE

## J – ACCESSORIES


NOT AVAILABLE

## K – ACCESSORY COLOR


SEE SECTION "B" FOR COLOR OPTIONS.

## NOTES


- (1). FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY.
- (2). FINISH OPTIONS 19, 21, 22, 23, 75, 76, 77, 83, 84, 88, 93 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.
- (3). FINISH OPTIONS 19, 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.
- (4). FINISH OPTIONS FOR SHADES ≤ 10" IN DIAMETER ARE THE SAME INSIDE AND OUT OF FIXTURE. SHADES > 10" IN DIAMETER ARE WHITE ON THE INSIDE.
- (5). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.
- (6). COLOR CORDS ARE NOT APPLICABLE FOR LED OPTIONS.  
 \*ALL ARMS COME WITH A CAST BACKPLATE (CB1/2", CB3/4", LWTM, CFWTM, ECT.).  
 \*ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER).  
 \*ALL FIXTURES MOUNT TO A 4-O JUNCTION BOX.  
 \*FIXTURE DIMENSIONS MAY VARY ± 0.25.  
 \*CORD AND CANOPY COME IN THE SAME COLOR.




**FMS14** H- 4" W- 14"




**S2H1** H- 4.5" W- 8.5"




**S2H3** H- 5" W- 9"




**S2H5** H- 6" W- 10"




**S2H7** H- 4.5" W- 10"




**S2H9** H- 5" W- 9"




**CA57** H- 7.625" W- 5.25"




**WMCS** H- 6.5" W- 5"




**S2H2** H- 4.5" W- 12"




**S2H4** H- 3.5" W- 10"




**S2H6** H- 7" W- 12"




**S2H8** H- 3.125" W- 9"




**S2H10** H- 4.5" W- 7.5"



**S2KT6** H- 8" W- 6"



**H2FH** H- 2.5" W- 12"




**GBL6** H- 5" W- 6"



C - MOUNTING OPTIONS


1/4" WALL MOUNTS




**WM20** 6"(H) 8.25"(W)




**WM21** 4.75"(H) 8"(W)




**WM23** 12.5"(H) 8"(W)



**WM24** 11"(H) 6.375"(W)




**WM26** 12"(H) 9"(W)



**WM25** 9"(H) 5.5"(W)



**WM29** 9.5"(H) 14"(W)



**WM29V** 21.75"(H) 15.25"(W)

CORD MOUNT

\*CORDS RATED FOR DRY LOCATION

\*CANOPY DIMENSIONS: .625" (H) 5.25" (W)

\*CORD AND CANOPY COME IN THE SAME COLOR.



**BLC** 8' BLACK CORD (INCLUDES CANOPY) INC

**WHC** 8' WHITE CORD (INCLUDES CANOPY) INC

STEM MOUNTS



**ST(XX)** STEM- 1/4" NPT

XX = LENGTH OF STEM  
(EXAMPLE - "ST18" = STEM MOUNT 18" LENGTH)  
\*CANOPY NOT INCLUDED, ADD IN SECTION D

\*STEM OPTION FOR ALL BISTRO  
EXCLUDING: FMS14 & H2FH



**ST(XX)** STEM- 1/2" NPT

XX = LENGTH OF STEM  
(EXAMPLE - "ST18" = STEM MOUNT 18" LENGTH)  
\*CANOPY NOT INCLUDED, ADD IN SECTION D

\*STEM OPTION ONLY FOR FMS14 & H2FH



**F- LIGHT SOURCE**

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

<b>INCANDESCENT (INC) MED E26</b>					
<b>INC 100W (MAX)</b> - S2H1, S2H2, S2H3, S2H4, S2H5, S2H6, S2H7, S2H8, S2H9, S2H10, S2KT6, CA57, FMS14, GBL6, GRS810, H2, WMC5			*IMPORTANT – FOR LIGHT EMITTED DIODE (LED) LIGHT SOURCE OPTION FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE LEFT.		
OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
60WINC	60W	PER BULB SPEC	PER BULB SPEC	120-277 VAC	PER BULB SPEC
100WINC	100W	PER BULB SPEC	PER BULB SPEC	120-277 VAC	PER BULB SPEC