



BASELITE - CYLINDER – INC – SPECIFICATION SHEET



PROJECT NAME: _____ PROJECT TYPE: _____

MODEL #	/	/	/	/	/	/	/	/	/	X	X	X
EXAMPLE:	A	B	C	D	E	F	G	H	I	J	K	
	CY510	41	ST18	STC	43	100INC	-	-	-	-	-	-

*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES:



A - SHADES

CYLINDERS

- CY48 - 100WINC (MAX)
- CY510 - 150WINC (MAX)
- CY816 - 200WINC (MAX)
- CY618 - 3-75WINC (MAX)
- CY620 - 3-75WINC (MAX)
- CYB510 - 150WINC (MAX)
- CYB816 - 200WINC (MAX)
- CYBU510 - 2-100WINC (MAX)
- CYBU816 - 2-100WINC (MAX)
- CG512 - 100WINC (MAX)
- CYD510 - 60WINC (MAX)
- GCY320 - 60WINC (MAX)
- PD2012 - 150WINC (MAX)
- SD2012 - 150WINC (MAX)

B - FINISH OPTIONS

(SEE WEBSITE FOR SWATCH COLORS)
(*SEE NOTES FOR LIMITATIONS*)
14, 15, 16, 17, 18, 19, 19P, 20, 20P, 20PB, 20SB, 21, 21P, 22, 22P, 23, 23P, 38, 39, 40, 41, 41.5, 42, 43, 44, 45, 46, 48, 49, 50, 51, 52, 53, 54, 55, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, MG.

C - MOUNTING OPTIONS

- CORD MOUNT**
BLC, WHC, TCB, TCW, TCHB, TCHW, TLB, TLW, TLB, TLW, RCB, RCW, RCHB, RCHW, FHB, FHW, HBLC, HWHC, CBLC, CWHC, CHB, CHW
- STEM MOUNT**
ST6, ST12, ST18, ST24, ST36, ST48, STXX

D - MOUNTING ADD-ONS

- INC ADD-ONS**
SLC, STC
- UNIVERSAL ADD-ONS**
FH ½", FH ¾", SWL, LGSWL, CNK

E - MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

F - LIGHT SOURCE

- (SEE PAGE 3 FOR WATTAGE LIMITATIONS)
INCANDESCENT (INC)
60W, 3-75W, 100W, 2-100W, 150W, 200W

G - LED COLOR TEMP

NOT AVAILABLE

H - ELECTRICAL OPTION

NOT AVAILABLE

I - GLASS OPTIONS

NOT AVAILABLE

J - ACCESSORIES

NOT AVAILABLE

K - ACCESSORY COLOR

NOT AVAILABLE

NOTES


- FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY.
- FINISH OPTIONS 19, 21, 22, 23, 75, 76, 77, 83, 84, 88, 93 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.
- FINISH OPTIONS 19, 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.
- FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.
- COLOR CORDS ARE NOT APPLICABLE FOR LED OPTIONS.
*ALL ARMS COME WITH A CAST BACKPLATE (CB1/2", CB3/4", LWTM, CFWTM, ECT.).
*ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.).
*ALL FIXTURES MOUNT TO A 4-0 JUNCTION BOX.
*FIXTURE DIMENSIONS MAY VARY ±0.25.
*CORD AND CANOPY COME IN THE SAME COLOR.



- CY48** H - 8" W - 4"
- CY510** H - 10" W - 5"
- CY816** H - 16" W - 8"




- CY618** H - 6" W - 18"
- CY620** H - 6" W - 20"



- CYB510** H - 10" W - 5"
- CYB816** H - 16" W - 8"
- CYBU510** H - 10" W - 5"
- CYBU816** H - 16" W - 8"

*FIXTURES COME AS SHOWN
*ALL MOUNTING OPTIONS DO NOT APPLY




- PD2012** H - 12" W - 20"




- CG512** H - 12" W - 5"



- GCY320** H - 20" W - 4"



- SD2012** H - 12" W - 20"




- CYD510** H - 8" W - 4"



C - MOUNTING OPTIONS

STEM MOUNTS



DP24 DOUBLE PENDANT 20"(H) 24"(W)
*DP24 COMES STANDARD WITH STC AND ST18



ST(XX) STEM- 1/2" NPT
XX = LENGTH OF STEM
(EXAMPLE - "ST18" = STEM MOUNT 18" LENGTH)
*CANOPY NOT INCLUDED, ADD IN SECTION D
* 1/4" NPT AND 3/4" NPT AVAILABLE UPON REQUEST




SC24 SCROLL STEM 33"(H) 26(W)
*SC24 COMES STANDARD WITH STC

INCANDESCENT CORD MOUNTS

*INCANDESCENT MAX WATTAGE 150 WATT. CALL FACTORY FOR HIGHER WATTAGES. LOOPS, CABLES, AND CHAINS AVAILABLE ONLY FOR INCANDESCENT *CORDS RATED FOR DRY LOCATION *CANOPY DIMENSIONS: .625" (H) 5.25" (W)
*CORD AND CANOPY COME IN THE SAME COLOR.




BLC 8' BLACK CORD
WHC 8' WHITE CORD



TCB 8' BLACK CORD, CABLE, and LOOP
TCW 8' WHITE CORD, CABLE, and LOOP



TCHB 8' BLACK CORD, 3' CHAIN, and LOOP
TCHW 8' WHITE CORD, 3' CHAIN, and LOOP




TLB 8' BLACK TELEPHONE CORD AND CABLE
TLW 8' WHITE TELEPHONE CORD AND CABLE
* Not available H.I.D.




RCB 8' BLACK CORD, CABLE, and LOOP
RCW 8' WHITE CORD, CABLE, and LOOP



RCHB 8' BLACK CORD, 3' CHAIN, and LOOP
RCHW 8' WHITE CORD, 3' CHAIN, and LOOP



FHB 8' BLACK CORD WITH FLAT HUB
FHW 8' WHITE CORD WITH FLAT HUB




CBLC 8' BLACK CORD and CABLE
CWLK 8' WHITE CORD and CABLE



CHB 8' BLACK CORD, 3' CHAIN, and LOOP
CHW 8' WHITE CORD, 3' CHAIN, and LOOP
* Loop may vary due to shade style

D - MOUNTING ADD-ONS

INCANDESCENT AND H.I.D STEM AND ARM ADD-ONS



SLC 1/2" SLOPE CEILING CANOPY 1/2"
SLC 3/4" SLOPE CEILING CANOPY 3/4"
*(Slopes To 20 Degrees)




STC 1/2" 1/2" STEM MOUNT CANOPY

D - MOUNTING ADD-ONS (CONTINUED)

UNIVERSAL STEM AND ARM


* EXAMPLE FOR MULTIPLE MOUNTING ADD-ONS:

MODEL #: -/-/-(L)WTM, TRB 1/2", LGSWL-/-/-/-/-/-/-/
A B C D E F G H I J K




CNK CANOPY For MULTIPLE FIXTURES

*CNK dimensions vary on number of fixtures applied



FH 1/2" FLAT HUB 1/2"

FH 3/4" FLAT HUB 3/4"



LGSWL 1/2" NPT SWIVEL

For all shades greater than 7" wide in diameter

F - LIGHT SOURCE

INCANDESCENT (INC) MED E26				
INC 60W – CYD510, GCY320 INC 3-75W - CY618, CY620 INC 100W - CY48, CG512 INC 2-100W - CYBU510, CYBU816 INC 150W - CY510, CYB510, PD2012, SD2012 INC 200W - CY816, CYB816			<p>*IMPORTANT – FOR INCANDESCENT (INC) LIGHT SOURCE OPTION, FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE LEFT.</p> <p>EXAMPLE: / INC150W /</p>	
OPTION	WATTAGE	LUMENS	VOLTAGE	DIMMING
75WINC	75W	PER BULB SPECS	120-277 VAC	PER BULB SPECS
100WINC	100W	PER BULB SPECS	120-277 VAC	PER BULB SPECS
150WINC	150W	PER BULB SPECS	120-277 VAC	PER BULB SPECS
200WINC	200W	PER BULB SPECS	120-277 VAC	PER BULB SPECS