




MACHINE AGE

SPECIFICATION SHEET



4S1WG3/17/GRTE3/TCC/60INC



MODEL: 4S1WG3

PREPARED BY: _____

TYPE: _____

JOB NAME: _____

DATE: _____

CERTIFICATION: UL LISTED

FINISH – Five stage pretreatment process, coated with a lead free TGI C polyester powder coat finish. White is standard inside reflectors, *some finish options excluded. See color chart below for color options (unless specified). Some finish options are not available for certain fixtures. Custom colors and Marine options are available upon request. **Finishes #14PN, 19, 20, 20PB, 20SB, 21, 22, 23, 39, 40, 57, 58, 88 do not apply to this fixture.**

LAMP HOLDERS – Accommodates **Incandescent/LED** bulb – medium base porcelain socket, copper shell with nickel plate, rated 250v.

MOUNTING – Fixtures are pre-wired with 96” cord. Available with cord or stem sets. Cords can be adjusted to the desired length through the top of the fixture before mounting.

REFLECTOR – Socket covers are spun from heavy gauge 1100-0 aluminum, ranging in thickness from .050 to .125. The gears are cast from a high grade 356 aluminum. Accompanied with decorative wire grills.

MODEL #	FINISH	LIGHT SOURCE				MOUNTING OPTIONS	ACCESSORIES
		INC	CF*	MH*	LED		
4S1WG3	SEE THE FINISH OPTION CHART ON THE WEBSITE AT THE BOTTOM OF THE PAGE UNDER “PRODUCT INFORMATION.”	60W	N/A	N/A	N/A	CORD MOUNT, STEM MOUNT	WG3, WG4, WG5, WG7, WH1

* same finish color inside and out.
* remote ballast / driver.

.SUBJECT TO MODIFICATION WITHOUT NOTICE.



BASELITE CORPORATION
12260 EAST END AVE.
CHINO, CA 91710

PH: 877-999-1990
WEB: WWW.BASELITE.COM
EMAIL: SALES@BASELITE.COM

