



BASELITE – CAFÉ LITES – LED – SPECIFICATION SHEET



PROJECT NAME: _____ PROJECT TYPE: _____

MODEL #	/	/	/	X	/	/	/	/	/	/	/
	A	B	C	D	E	F	G	H	I	J	K
EXAMPLE:	W508	41	WM19		41	12W	3K	LDM120	CL3	GU-1	41

*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES:



WS508/21P/BLC/60INC

A - SHADES

- CAFÉ LITES**
BH08 - (12W MAX)
CS06B - (12W MAX)
CS06 - (12W MAX)
CS07 - (12W MAX)
CS08 - (12W MAX)
CSP08 - (12W MAX)
D608 - (12W MAX)
JIB610 - (12W MAX)
JIB611 - (12W MAX)
SBH08 - (12W MAX)
R908 - (12W MAX)
W507 - (12W MAX)
W507B - (12W MAX)
W508 - (12W MAX)
WS508 - (12W MAX)
WS508B - (12W MAX)

B - FINISH OPTIONS

(*SEE WEBSITE FOR SWATCH COLORS)
 (*SEE NOTES FOR LIMITATIONS)
 14, 15, 16, 17, 18, 19, 19P, 20, 20P, 20PB,
 20SB, 21, 21P, 22, 22P, 23, 23P, 38, 39, 40,
 41, 41.5, 42, 43, 44, 45, 46, 48, 49, 50, 51,
 52, 53, 54, 55, 57, 58, 59, 60, 61, 62, 63, 64,
 65, 66, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79,
 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91,
 92, 93, 94, 95, 96, 97, 98, 99, 100, MG.

C – MOUNTING OPTIONS

¼" WALL MOUNT
 WM19, WM20, WM21, WM23, WM24,
 WM25, WM26, WM27, WM28, WM29,
 WM29V
LED CORD MOUNT
 LBLC, LWHC

D – MOUNTING ADD-ONS

NOT AVAILABLE

E – MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

F – LIGHT SOURCE

(SEE PAGE 2 FOR WATTAGE LIMITATIONS)
LIGHT EMITTED DIODE (LED)
 LED10WF, LED12W

*NOTE – MAX WATTAGE IS LISTED NEXT TO THE SHADE MODEL NUMBER IN SECTION "A". ALL WATTAGES BELOW THAT ARE ALSO AVAILABLE FOR THE SAME MODEL NUMBER.

G – LED COLOR TEMP

- 27K – 2700 KELVIN
 3K – 3000 KELVIN
 35K – 3500 KELVIN
 4K – 4000 KELVIN
 5K – 5000 K ELVIN

H – ELECTRICAL OPTION

(SEE PAGE 3 FOR FURTHER INFORMATION)
LDM120
LDM0-10V

I – GLASS OPTIONS

CL3, BL3, RE3, GR3, AH3, FR3, PR3

J – ACCESSORIES














GR6, GR7, GR8, UGR, GU-1, WG-1

K – ACCESSORY COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

NOTES


- (1). FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY.
 - (2). FINISH OPTIONS 19, 21, 22, 23, 75, 76, 77, 83, 84, 88, 93 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.
 - (3). FINISH OPTIONS 19, 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.
 - (4). FINISH OPTIONS FOR SHADES ≤ 10" IN DIAMETER ARE THE SAME INSIDE AND OUT OF FIXTURE. SHADES > 10" IN DIAMETER ARE WHITE ON THE INSIDE.
 - (5). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.
 - (6). COLOR CORDS ARE NOT APPLICABLE FOR LED OPTIONS.
- *ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.).
 *ALL FIXTURES MOUNT TO A 4-O JUNCTION BOX.
 *FIXTURE DIMENSIONS MAY VARY ± 0.25.
 *CORD AND CANOPY COME IN THE SAME COLOR.





C - MOUNTING OPTIONS


1/4" WALL MOUNTS




WM20 6"(H) 8.25"(W)



WM23 12.5"(H) 8"(W)



WM24 11"(H) 6.375"(W)



WM26 12"(H) 9"(W)

CORD MOUNT

*FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY. *CORDS RATED FOR DRY LOCATION
*CANOPY DIMENSIONS: 4" (H) 5.5" (W) *CORD AND CANOPY COME IN THE SAME COLOR.



- LBLC** 8' BLACK CORD (INCLUDES LED CANOPY)
- LWHC** 8' WHITE CORD (INCLUDES LED CANOPY)

F- LIGHT SOURCE

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

LIGHT EMITTING DIODE (LED)

LED 12W (MAX)- BH08, D608, JIB610, JIB611, R908, W508, WS508, CS06, CS07, CS08, SBH08, W507, W507B, WS508, CSP08

***IMPORTANT** – FOR LIGHT EMITTED DIODE (LED) LIGHT SOURCE OPTION, FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE MAX WATTAGE AVAILABILITY. **EXAMPLE: /LED12W /**

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
LED10WF	10W	1280	>90	120-277 VAC	TRI-ELV *120V ONLY
LED12W	12W	1481	>90	120-277 VAC	See section "H"
		@3500K			



H – ELECTRICAL OPTION

LED DIMMING OPTIONS

LED10WF – ONLY AVAILABLE WITH **LDM120** - TRI-ELV DIMMING OPITON. ALL OTHER WATTAGES CAN CHOOSE FROM THE OPTIONS BELOW. CONTACT DRIVER MANUFACTURER FOR FURTHER SPECIFICATIONS.

LDM120 - TRIAC / ELV – INPUT 120 / 277V - DIMMING AT 120 VOLT ONLY

LDM0-10V – 0 – 10V – DIMMING AT 120 / 277 VOLTS

I – GLASS OPTIONS



CL3 3" CLEAR GLASS



FR3 3" FROSTED GLASS



PR3 3" PRISMATIC GLASS



BL3 3" BLUE GLASS




AH3 3" AMBER HYDE GLASS



GR3 3" GREEN GLASS




RE3 3" RED GLASS



GLASS – DIMENSIONS	
3" GLASS	
Diameter	3.34"
Height	6.93"
Fitter	3.29"

GLASS – MAX WATTAGE	
3" GLASS – 100W INC / LED12W	

J – ACCESSORIES




GR6 6" WIRE GRILL

GR7 7" WIRE GRILL


GR8 8" WIRE GRILL



UGR U- WIRE GUARD



WG-1 WIRE GUARD



GU-1 CAST ALUMINUM GUARD