



BASELITE – QSP-QSD – INC – SPECIFICATION SHEET



PROJECT NAME: _____ PROJECT TYPE: _____

MODEL #	/	/	/	/	/	/	/	/	/	X	/	/
	A	B	C	D	E	F	G	H	I	J	K	
EXAMPLE:	QSP22	41	ST24	SLC1/2"	43	45W	3K	LDM120		GR13	44	

*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES:



QSP22/74/ST18/HB3/LL22/100INC

A - SHADES

QSP SERIES

QSP16 - 300WINC (MAX)

QSP22 - 300WINC (MAX)

QSD SERIES

QSD16 - 300WINC (MAX)

QSDS16 - 300WINC (MAX)

QSD22 - 300WINC (MAX)

B - FINISH OPTIONS

(SEE WEBSITE FOR SWATCH COLORS)

(*SEE NOTES FOR LIMITATIONS*)

21P, 41, 41.5, 43, 44, 48, 51, 52, 53, 58, 59, 61, 62, 74, 79, 97, 99, 100, MG.

C - MOUNTING OPTIONS

CORD MOUNT

BLC - 8' black cord & canopy

WHC - 8' white cord & canopy

TCB - 8' black cord, loop, cable & canopy

TCW - 8' white cord, loop, cable & canopy

TLB - 8' black telephone cable

TLW - 8' white telephone cable

CBLC - 8' black cord, cable and canopy

CWHC - 8' white cord, cable and canopy

3CBLC - 3 cable and 8' black cord & canopy

3CBLW - 3 cable and 8' white cord & canopy

HKBC - hook and 8' black cord & canopy

HKWC - hook and 8' white cord & canopy

STEM MOUNT

ST18 - 18" stem

ST24 - 24" stem

ST36 - 36" stem

ST48 - 48" stem

STXX - XX = stem length

D - MOUNTING ADD-ONS

INC ADD-ONS

SLC1/2" - slope ceiling canopy 1/2"

SLC3/4" - slope ceiling canopy 3/4"

STC1/2" - stem mount canopy 1/2"

HB3 - 3/4" hub

E - MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

F - LIGHT SOURCE

(SEE PAGE 3 FOR WATTAGE LIMITATIONS)

INCANDESCENT (INC)

300W(max)

G - LED COLOR TEMP

NOT AVAILABLE

H - ELECTRICAL OPTION

NOT AVAILABLE

I - GLASS OPTIONS

NOT AVAILABLE

J - ACCESSORIES

LGR12 - 12" louvered grill

LGR16 - 16" louvered grill

LGR22 - 22" louvered grill

ARFL12 - 12" flat clear diffuser

ARFL16 - 16" flat clear diffuser

ARFL22 - 22" flat clear diffuser

ARFR12 - 12" flat metal ring

ARFR16 - 16" flat metal ring

ARFR22 - 22" flat metal ring

FLE12 - 12" flat clear lens w/ clips

FLE16 - 16" flat clear lens w/ clips

FLE22 - 22" flat clear lens w/ clips

BLE12 - 12" flat clear lens w/ band

BLE16 - 16" flat clear lens w/ band

BLE22 - 22" flat clear lens w/ band

LL12 - 12" clear conical lens

LL16 - 16" clear conical lens

LL22 - 22" clear conical lens

CRL12 - 12" clear curved lens

CRL16 - 16" clear curved lens

CRL22 - 22" clear curved lens

DRL16 - 16" clear drop lens

DRL22 - 22" clear drop lens

BRS16 - 16" aluminum bottom ring

BRS22 - 22" aluminum bottom ring

TRS16 - 16" aluminum top ring

TRS22 - 22" aluminum top ring

FWG16 - 16" full wire grill

FWG22 - 22" full wire grill

K - ACCESSORY COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

NOTES

(1). FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY.

(2). FINISH OPTIONS 19, 21, 22, 23, 75, 76, 77, 83, 84, 88, 93 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.

(3). FINISH OPTIONS 19, 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.


(4). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.

*ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE.


(EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.).

*ALL FIXTURES MOUNT TO A 4-0 JUNCTION BOX.


*FIXTURE DIMENSIONS MAY VARY ±0.25.



	HEIGHT	WIDTH
QSD16	H-19"	W-16"
QSD22	H-22"	W-22"







	HEIGHT	WIDTH
QSP16	H-19"	W-16"
QSP22	H-22"	W-22"




	HEIGHT	WIDTH
QSDS16	H-17"	W-16"

**C – MOUNTING OPTIONS****CORD MOUNTS**

BASELITE USES A DURABLE SJT CORD FOR ALL CORD MOUNT OPTIONS. ALL CORD MOUNTS COME WITH AN 6" ROUND CANOPY.

**CBLC** 8' BLACK CORD, CABLE & CANOPY
CWHC 8' WHITE CORD, CABLE & CANOPY**TLB** 2.5' BLACK TELEPHONE CABLE
TLW 2.5' WHITE TELEPHONE CABLE**TCB** 8' CABLE, BLACK CORD, CANOPY & LOOP
TCW 8' CABLE, WHITE CORD, CANOPY & LOOP**BLC** 8' BLACK CORD AND CANOPY
WHC 8' WHITE CORD AND CANOPY**HKBC** 3/4" HOOK WITH 8' BLACK CORD
HKWC 3/4" HOOK WITH 8' WHITE CORD**STEM MOUNTS****ST(XX)** STEM- 3/4" NPTXX = LENGTH OF STEM
(EXAMPLE – "ST18" = STEM MOUNT 18" LENGTH)
*CANOPY NOT INCLUDED, ADD IN SECTION D**D - MOUNTING ADD-ONS****INCANDESCENT MOUNTING ADD-ONS**

* FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY.

**SLC 1/2"** SLOPE CEILING CANOPY 1/2"
SLC 3/4" SLOPE CEILING CANOPY 3/4"
*(Slopes To 20 Degrees)**STC 1/2"** 1/2" STEM MOUNT CANOPY**HB3 -** 3/4" HUB




F – LIGHT SOURCE

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

INCANDESCENT (INC) MED E26					
INC 300W (MAX) - QSD16, QSDS16, QSD22, QSP16, QSP22			*IMPORTANT – FOR LIGHT EMITTED DIODE (LED) LIGHT SOURCE OPTION FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE LEFT. EXAMPLE: / 300WINC /		
OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
300WINC	300W	PER BULB SPECS	>90	120-277 VAC	PER BULB SPECS

J – ACCESSORIES


*NOTE: MUST USE TEMPERED GLASS FOR LIGHT FIXTURES USING HIGH INTENSITY DISCHARGE (HID) LIGHT SOURCE OPTION.




CRL16 - 16" CLEAR CURVED LENS
CRL22 - 22" CLEAR CURVED LENS




BLE16 16" FLAT CLEAR LENS WITH BAND
BLE22 22" FLAT CLEAR LENS WITH BAND




FLE16 - 16" FLAT CLEAR LENS WITH CLIPS
FLE22 - 22" FLAT CLEAR LENS WITH CLIPS



LL16 16" CLEAR CONICAL LENS
LL22 22" CLEAR CONICAL LENS



LGR16 16" LOUVERED GRILL
LGR22 22" LOUVERED GRILL



FWG16 - 16" FULL WIRE GRILL
FWG22 - 22" FULL WIRE GRILL



DRL16 - 16" PRISMATIC DROP LENS
DRL22 - 22" PRISMATIC DROP LENS



TRS16 - 16" TOP RING ALUMINUM SHIELD
TRS22 - 22" TOP RING ALUMINUM SHIELD



BRS16 - 16" BOTTOM RING ALUMINUM SHIELD
BRS22 - 22" BOTTOM RING ALUMINUM SHIELD