





C – MOUNTING OPTIONS

CORD MOUNTS


BASELITE USES A DURABLE SJT CORD FOR ALL CORD MOUNT OPTIONS. ALL CORD MOUNTS COME WITH AN 6" ROUND CANOPY.




CBLC 8' BLACK CORD, CABLE & CANOPY
CWHC 8' WHITE CORD, CABLE & CANOPY




TLB 2.5' BLACK TELEPHONE CABLE
TLW 2.5' WHITE TELEPHONE CABLE



TCB 8' CABLE, BLACK CORD, CANOPY & LOOP
TCW 8' CABLE, WHITE CORD, CANOPY & LOOP



BLC 8' BLACK CORD AND CANOPY
WHC 8' WHITE CORD AND CANOPY



3CBLC 3 CABLE AND BLACK CORD & CANOPY
3CWHC 3 CABLE AND WHITE CORD & CANOPY



HKBC 3/4" HOOK WITH 8' BLACK CORD
HKWC 3/4" HOOK WITH 8' WHITE CORD

STEM MOUNTS




ST(XX) STEM- 3/4" NPT

XX = LENGTH OF STEM
(EXAMPLE – "ST18" = STEM MOUNT 18" LENGTH)
*CANOPY NOT INCLUDED, ADD IN SECTION D


D - MOUNTING ADD-ONS

INCANDESCENT MOUNTING ADD-ONS

* FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY.



SLC 1/2" SLOPE CEILING CANOPY 1/2"
SLC 3/4" SLOPE CEILING CANOPY 3/4"
*(Slopes To 20 Degrees)



STC 1/2" 1/2" STEM MOUNT CANOPY



HB3 - 3/4" HUB




F – LIGHT SOURCE


| INCANDESCENT (INC) <small>MED E26</small> | | | | | |
|---|---------|----------------|---|-------------|---------|
| INC 150W (MAX) - FA12, FAP12 INC 300W (MAX) - FA16, FA22, FAP16, FAP22 | | | *IMPORTANT – FOR LIGHT EMITTED DIODE (LED) LIGHT SOURCE OPTION FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE LEFT. EXAMPLE: / 300WINC / | | |
| OPTION | WATTAGE | LUMENS | CRI | VOLTAGE | DIMMING |
| 150WINC | 150W | PER BULB SPECS | >90 | 120-277 VAC | N/A |
| 300WINC | 300W | PER BULB SPECS | >90 | 120-277 VAC | N/A |

J – ACCESSORIES

*NOTE: MUST USE TEMPERED GLASS FOR LIGHT FIXTURES USING HIGH INTENSITY DISCHARGE (HID) LIGHT SOURCE OPTION.




CRL12 - 12" CLEAR CURVED LENS
CRL16 - 16" CLEAR CURVED LENS
CRL22 - 22" CLEAR CURVED LENS




FLE12 - 12" FLAT CLEAR LENS WITH CLIPS
FLE16 - 16" FLAT CLEAR LENS WITH CLIPS
FLE22 - 22" FLAT CLEAR LENS WITH CLIPS



BLE12 12" FLAT CLEAR LENS WITH BAND
BLE16 16" FLAT CLEAR LENS WITH BAND
BLE22 22" FLAT CLEAR LENS WITH BAND



LL12 12" CLEAR CONICAL LENS
LL16 16" CLEAR CONICAL LENS
LL22 22" CLEAR CONICAL LENS



LGR12 12" LOUVERED GRILL
LGR16 16" LOUVERED GRILL
LGR22 22" LOUVERED GRILL



FWG16 - 16" FULL WIRE GRILL
FWG22 - 22" FULL WIRE GRILL



DRL16 - 16" PRISMATIC DROP LENS
DRL22 - 22" PRISMATIC DROP LENS



TRS16 - 16" TOP RING ALUMINUM SHIELD
TRS22 - 22" TOP RING ALUMINUM SHIELD



BRS16 - 16" BOTTOM RING ALUMINUM SHIELD
BRS22 - 22" BOTTOM RING ALUMINUM SHIELD