



BASELITE – TR-TR1 – INC – SPECIFICATION SHEET



PROJECT NAME: _____ PROJECT TYPE: _____

MODEL #	/	/	/	/	/	/	/	/	X	/	/
	A	B	C	D	E	F	G	H	I	J	K

EXAMPLE: TR.FR 41 ST24 SLC1/2" 43 45W 3K LDM120 GR13 44

*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES:



TR/FR/61/3CBLC/ARFL/100INC

A - SHADES

TR SERIES

TR.D - 150WINC (MAX)

TR.FC - 150WINC (MAX)

TR.FR - 150WINC (MAX)

TR1 SERIES

TR1 - 150WINC (MAX)

TR2 SERIES

TR2.FC - 150WINC (MAX)

TR2.FR - 150WINC (MAX)

PTR2 - 150WINC (MAX)

TR3 SERIES

TR3 - 300WINC (MAX)

B - FINISH OPTIONS

(SEE WEBSITE FOR SWATCH COLORS)

(*SEE NOTES FOR LIMITATIONS*)

21P, 41, 41.5, 43, 44, 48, 51, 52, 53, 58, 59, 61, 62, 74, 79, 97, 99, 100, MG.

C - MOUNTING OPTIONS

CORD MOUNT

BLC - 8' black cord & canopy

WHC - 8' white cord & canopy

TCB - 8' black cord, loop, cable & canopy

TCW - 8' white cord, loop, cable & canopy

TLB - 8' black telephone cable

TLW - 8' white telephone cable

CBLC - 8' black cord, cable and canopy

CWHC - 8' white cord, cable and canopy

3CBLC - 3 cable and 8' black cord & canopy

3CBLW - 3 cable and 8' white cord & canopy

HKBC - hook and 8' black cord & canopy

HKWC - hook and 8' white cord & canopy

STEM MOUNT

ST18 - 18" stem

ST24 - 24" stem

ST36 - 36" stem

ST48 - 48" stem

STXX - XX = stem length

D - MOUNTING ADD-ONS

INC ADD-ONS

SLC1/2" - slope ceiling canopy 1/2"

SLC3/4" - slope ceiling canopy 3/4"

STC1/2" - stem mount canopy 1/2"

HB3 - 3/4" hub

E - MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

F - LIGHT SOURCE

(SEE PAGE 3 FOR WATTAGE LIMITATIONS)

INCANDESCENT (INC)

150W, 300W

G - LED COLOR TEMP

NOT AVAILABLE

H - ELECTRICAL OPTION

NOT AVAILABLE

I - GLASS OPTIONS

NOT AVAILABLE

J - ACCESSORIES

TR - OPTIONS

ARFL - 12" flat clear diffuser w/ arms

ARFR - 12" flat metal ring w/ arms

TRD - OPTIONS

LGR - 13" louvered grill

ARFL - 14" flat clear diffuser w/ arms

ARFR - 14" flat metal ring w/ arms

FLE - 12" flat clear lens w/ clips

BLE - 12" flat clear lens w/ band

LL - 12" clear conical lens

CRL - 12" clear curved lens

TR1 - OPTIONS

LGR - 13" louvered grill

ARFL - 14" flat clear diffuser w/ arms

ARFR - 14" flat metal ring w/ arms

FLE - 12" flat clear lens w/ clips

BLE - 12" flat clear lens w/ band

LL - 12" clear conical lens

CRL - 12" clear curved lens

TR2 - OPTIONS

ARFL - 14" flat clear diffuser w/ arms

ARFR - 14" flat metal ring w/ arms

TR3 - OPTIONS

LGR - 13" louvered grill

ARFL - 14" flat clear diffuser w/ arms

ARFR - 14" flat metal ring w/ arms

FLE - 12" flat clear lens w/ clips

BLE - 12" flat clear lens w/ band

LL - 12" clear conical lens

CRL - 12" clear curved lens

K - ACCESSORY COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

NOTES

(1). FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY.

(2). FINISH OPTIONS 19, 21, 22, 23, 75, 76, 77, 83, 84, 88, 93 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.

(3). FINISH OPTIONS 19, 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.

(4). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.

*ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE.

(EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.).


*ALL FIXTURES MOUNT TO A 4-O JUNCTION BOX.

*FIXTURE DIMENSIONS MAY VARY \pm 0.25.


TR.D - H-13.75" W-12"



TR.FR - H-15" W-8.5"
TR.FC - H-15" W-8.5"



TR1.PR H-15" W-12.5"



TR3 - H-15.25" W-12"

TR2.FR - H-18" W-12"
TR2.FC - H-18" W-12"






C - MOUNTING OPTIONS

CORD MOUNTS


BASELITE USES A DURABLE SJT CORD FOR ALL CORD MOUNT OPTIONS. ALL CORD MOUNTS COME WITH AN 6" ROUND CANOPY.




CBLC 8' BLACK CORD, CABLE & CANOPY
CWHC 8' WHITE CORD, CABLE & CANOPY




TLB 2.5' BLACK TELEPHONE CABLE
TLW 2.5' WHITE TELEPHONE CABLE



TCB 8' CABLE, BLACK CORD, CANOPY & LOOP
TCW 8' CABLE, WHITE CORD, CANOPY & LOOP



BLC 8' BLACK CORD AND CANOPY
WHC 8' WHITE CORD AND CANOPY



3CBLC 3 CABLE AND BLACK CORD & CANOPY
3CWHC 3 CABLE AND WHITE CORD & CANOPY



HKBC 3/4" HOOK WITH 8' BLACK CORD
HKWC 3/4" HOOK WITH 8' WHITE CORD

STEM MOUNTS




ST(XX) STEM- 3/4" NPT
 XX = LENGTH OF STEM
 (EXAMPLE - "ST18" = STEM MOUNT 18" LENGTH)
 *CANOPY NOT INCLUDED, ADD IN SECTION D


D - MOUNTING ADD-ONS

INCANDESCENT MOUNTING ADD-ONS

* FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY.



SLC 1/2" SLOPE CEILING CANOPY 1/2"
SLC 3/4" SLOPE CEILING CANOPY 3/4"
 *(Slopes To 20 Degrees)

**STC 1/2"** 1/2" STEM MOUNT CANOPY**HB3 -** 3/4" HUB



BASELITE COMMERCIAL LIGHTING

PROJECT NAME: _____
PROJECT TYPE: _____

F – LIGHT SOURCE

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

INCANDESCENT (INC) MED E26

INC 150W (MAX)- TR.D, TR.FR, TR.FC, TR1, TR2.FR, TR2.FC
INC 300W (MAX)- TR3

***IMPORTANT** – FOR LIGHT EMITTED DIODE (LED) LIGHT SOURCE OPTION FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE LEFT. EXAMPLE: / 300WINC /


OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
150WINC	150W	PER BULB SPECS	>90	120-277 VAC	N/A
300WINC	300W	PER BULB SPECS	>90	120-277 VAC	N/A

J – ACCESSORIES


*NOTE: Please see section "J" on the first page for lens sizes and shades requirement options.




CRL - CLEAR CURVED LENS




ARFL - FLAT CLEAR LENS WITH ARMS




ARFR - FLAT METAL RING




FLE - FLAT CLEAR LENS WITH CLIPS



BLE - FLAT CLEAR LENS WITH BAND



LL - CLEAR CONICAL LENS



LGR - LOUVERED GRILL