



BASELITE – TR-TR1 – LED – SPECIFICATION SHEET



PROJECT NAME: _____ PROJECT TYPE: _____

MODEL #	/	/	/	/	/	/	/	/	X	/	/
EXAMPLE:	A	B	C	D	E	F	G	H	I	J	K
	TR.FR	41	ST24	SLC1/2"	43	45W	3K	LDM120		GR13	44

*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES:



TR/FR/61/3CBLC/ARFL/100INC

A - SHADES

TR SERIES

TR.D - 25WLED (MAX)

TR.FC - 25WLED (MAX)

TR.FR - 25WLED (MAX)

TR1 SERIES

TR1 - 25WLED (MAX)

TR2 SERIES

TR2.FR - 25WLED (MAX)

TR2.FC - 25WLED (MAX)

PTR2 - 25WLED (MAX)

TR3 SERIES

TR3 - 25WLED (MAX)

B - FINISH OPTIONS

(SEE WEBSITE FOR SWATCH COLORS)

(*SEE NOTES FOR LIMITATIONS*)

21P, 41, 41.5, 43, 44, 48, 51, 52, 53, 58, 59,

61, 62, 74, 79, 97, 99, 100, MG.

C - MOUNTING OPTIONS

CORD MOUNT

LBLC - 8' black cord & canopy

LWHC - 8' white cord & canopy

LTCB - 8' black cord, loop, cable & canopy

LTCW - 8' white cord, loop, cable & canopy

LTLB - 8' black telephone cable

LTLW - 8' white telephone cable

LCBLC - 8' black cord, cable and canopy

LCWHC - 8' white cord, cable and canopy

3LCBLC - 3 cable and 8' black cord & canopy

3LCBLW - 3 cable and 8' white cord & canopy

HKLBC - hook and 8' black cord & canopy

HKLWC - hook and 8' white cord & canopy

STEM MOUNT

ST18 - 18" stem

ST24 - 24" stem

ST36 - 36" stem

ST48 - 48" stem

STXX - XX = stem length

D - MOUNTING ADD-ONS

LED ADD-ONS

LSLC - LED slope ceiling canopy

LSTC - LED stem mount canopy

HB3 - $\frac{3}{4}$ " hub

E - MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

F - LIGHT SOURCE

(SEE PAGE 3 FOR WATTAGE LIMITATIONS)

LIGHT EMITTED DIODE (LED)

10W, 12W, 25W

*NOTE - MAX WATTAGE IS LISTED NEXT TO THE SHADE MODEL NUMBER IN SECTION "A". ALL WATTAGES BELOW THAT ARE ALSO AVAILABLE FOR THE SAME MODEL NUMBER.

G - LED COLOR TEMP

27K - 2700 KELVIN

3K - 3000 KELVIN

35K - 3500 KELVIN

4K - 4000 KELVIN

5K - 5000 KELVIN

H - ELECTRICAL OPTION

(SEE PAGE 3 FOR DIMMING OPTION SPECIFICATIONS)

LDM120

LDM0-10

I - GLASS OPTIONS

NOT AVAILABLE

J - ACCESSORIES

TR - OPTIONS

ARFL - 12" flat clear diffuser w/ arms

ARFR - 12" flat metal ring w/ arms

TRD - OPTIONS

LGR - 13" louvered grill

ARFL - 14" flat clear diffuser w/ arms

ARFR - 14" flat metal ring w/ arms

FLE - 12" flat clear lens w/ clips

BLE - 12" flat clear lens w/ band

LL - 12" clear conical lens

CRL - 12" clear curved lens

TR1 - OPTIONS

LGR - 13" louvered grill

ARFL - 14" flat clear diffuser w/ arms

ARFR - 14" flat metal ring w/ arms

FLE - 12" flat clear lens w/ clips

BLE - 12" flat clear lens w/ band

LL - 12" clear conical lens

CRL - 12" clear curved lens

TR2 - OPTIONS

ARFL - 14" flat clear diffuser w/ arms

ARFR - 14" flat metal ring w/ arms

FLE - 12" flat clear lens w/ clips

BLE - 12" flat clear lens w/ band

LL - 12" clear conical lens

CRL - 12" clear curved lens

TR3 - OPTIONS

LGR - 13" louvered grill

ARFL - 14" flat clear diffuser w/ arms

ARFR - 14" flat metal ring w/ arms

FLE - 12" flat clear lens w/ clips

BLE - 12" flat clear lens w/ band

LL - 12" clear conical lens

CRL - 12" clear curved lens

K - ACCESSORY COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

NOTES

(1). FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY.

(2). FINISH OPTIONS 19, 21, 22, 23, 75, 76, 77, 83, 84, 88, 93 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.


(3). FINISH OPTIONS 19, 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.

(4). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.


*ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE.
(EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.).

*ALL FIXTURES MOUNT TO A 4-O JUNCTION BOX.

*FIXTURE DIMENSIONS MAY VARY \pm 0.25.



TR.D - H-13.75" W-12"




TR.FR - H-15" W-8.5"

TR.FC - H-15" W-8.5"




TR1.PR H-15" W-12.5"



TR2 - H-18" W-12"

TR2.FR - H-18" W-12"

TR2.FC - H-18" W-12"



PTR2 - H-18" W-16"



BASELITE COMMERCIAL LIGHTING

PROJECT NAME: _____
PROJECT TYPE: _____

C - MOUNTING OPTIONS

LED CORD MOUNTS


*FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY. *CORDS RATED FOR DRY LOCATION *CANOPY DIMENSIONS: 4" (H) 5.5" (W)
*CORD AND CANOPY COME IN THE SAME COLOR.



LCBLC 8' BLACK CORD, CABLE & CANOPY
LCWHC 8' WHITE CORD, CABLE & CANOPY



LTCB 8' CABLE, BLACK CORD, LOOP & CANOPY
LTCW 8' CABLE, WHITE CORD, LOOP & CANOPY



3LCBLC 3 CABLE, BLACK CORD & CANOPY
3LCWHC 3 CABLE, WHITE CORD & CANOPY



LTLB 2.5' BLACK TELEPHONE CABLE & CANOPY
LTLW 2.5' WHITE TELEPHONE CABLE & CANOPY



LBLC 8' BLACK CORD AND CANOPY
LWHC 8' WHITE CORD AND CANOPY



HKLBC 3/4" HOOK WITH 8' BLACK CORD & CANOPY
HKLWC 3/4" HOOK WITH 8' WHITE CORD & CANOPY

STEM MOUNTS

*STEMS ARE RATED FOR DAMP LOCATION




STEM- 1/2" NPT
ST(XX) STEM- 3/4" NPT
XX = LENGTH OF STEM
(EXAMPLE - "ST18" = STEM MOUNT 18" LENGTH)
*CANOPY NOT INCLUDED, ADD IN SECTION D


D - MOUNTING ADD-ONS

LED MOUNTING ADD-ONS

* FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY.



LSLC - LED SLOPE CEILING CANOPY 1/2"
*(Slopes To 20 Degrees)



LSTC - LED STEM MOUNT CANOPY



HB3 - 3/4" HUB



BASELITE COMMERCIAL LIGHTING

PROJECT NAME: _____
PROJECT TYPE: _____

F – LIGHT SOURCE

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

LIGHT EMITTING DIODE (LED)

LED 25W (MAX) - TR.D, TR.FR, TR.FC, TR1, TR2.FR, TR2.FC, PTR2, TR3

***IMPORTANT** – FOR LIGHT EMITTED DIODE (LED) LIGHT SOURCE OPTION, FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE MAX WATTAGE AVAILABILITY. **EXAMPLE: / LED25W /**

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
LED10W	10W	1570	>90	120-277 VAC	TRI-ELV *120V ONLY
LED12W	12W	1596	>90	120-277 VAC	See section "H"
LED25W	25W	3125	>90	120-277 VAC	See section "H"

@3500K

H – ELECTRICAL OPTION

LED DIMMING OPTIONS

(LED10WF – ONLY AVAILABLE WITH **LDM120** - TRI-ELV DIMMING OPTION) ALL OTHER WATTAGES CAN CHOOSE FROM THE OPTIONS BELOW. CONTACT DRIVER MANUFACTURER FOR FURTHER SPECIFICATIONS.

LDM120 - TRIAC / ELV – INPUT 120 / 277V - DIMMING AT 120 VOLT ONLY


LDM0-10V – 0 – 10V – DIMMING AT 120 / 277 VOLTS

J – ACCESSORIES


*NOTE: Please see section "J" on the first page for lens sizes and shades requirement options.




CRL - CLEAR CURVED LENS




ARFL - FLAT CLEAR LENS WITH CLIPS




ARFR - FLAT METAL RING




FLE - FLAT CLEAR LENS WITH CLIPS



BLE12 - 12" FLAT CLEAR LENS WITH BAND



LL12 - 12" CLEAR CONICAL LENS



LGR12 - 12" LOUVERED GRILL