



BASELITE – RP-RD – INC – SPECIFICATION SHEET



PROJECT NAME: _____ PROJECT TYPE: _____

MODEL #	/	/	/	/	/	/	/	/	/	X	/	/
	A	B	C	D	E	F	G	H	I	J	K	
EXAMPLE:	RD22	41	ST24	SLC1/2"	41	150W	-	-	-	GR13	44	

*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES:



RP16/61/CBLC/150INC

A - SHADES

RD SERIES

RD12 - 150W INC (MAX)

RD16 - 300W INC (MAX)

RD22 - 300W INC (MAX)

RP SERIES

RP12 - 150W INC (MAX)

RP16 - 300W INC (MAX)

RP22 - 300W INC (MAX)

B - FINISH OPTIONS

(SEE WEBSITE FOR SWATCH COLORS)

(*SEE NOTES FOR LIMITATIONS*)

21P, 41, 41.5, 43, 44, 48, 51, 52, 53, 58, 59, 61, 62, 74, 79, 97, 99, 100, MG.

C - MOUNTING OPTIONS

CORD MOUNT

BLC - 8' BLACK CORD & CANOPY

WHC - 8' WHITE CORD & CANOPY

TCB - 8' BLACK CORD, LOOP, CABLE & CANOPY

TCW - 8' WHITE CORD, LOOP, CABLE & CANOPY

TLB - 8' BLACK TELEPHONE CABLE

TLW - 8' WHITE TELEPHONE CABLE

CBLC - 8' BLACK CORD, CABLE & CANOPY

CWHC - 8' WHITE CORD, CABLE & CANOPY

3CBLC - 3 CABLE & 8' BLACK CORD & CANOPY

3CBLW - 3 CABLE & 8' WHITE CORD & CANOPY

HKBC - HOOK & 8' BLACK CORD & CANOPY

HKWC - HOOK & 8' WHITE CORD & CANOPY

STEM MOUNT

ST18 - 18" STEM

ST24 - 24" STEM

ST36 - 36" STEM

ST48 - 48" STEM

STXX - XX = STEM LENGTH

D - MOUNTING ADD-ONS

INC ADD-ONS

SLC1/2" - SLOPE CEILING CANOPY 1/2"

SLC3/4" - SLOPE CEILING CANOPY 3/4"

STC1/2" - STEM MOUNT CANOPY 1/2"

HB3 - 3/4" HUB

E - MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

F - LIGHT SOURCE

(SEE PAGE 3 FOR WATTAGE LIMITATIONS)

INCANDESCENT (INC)

150W, 300W

G - LED COLOR TEMP

NOT AVAILABLE

H - ELECTRICAL OPTION

NOT AVAILABLE

I - GLASS OPTIONS

NOT AVAILABLE

J - ACCESSORIES

LEN16 - 16" FLAT CLEAR LENS

LEN22 - 22" FLAT CLEAR LENS

LL16 - 16" CLEAR CONICAL LENS

LL22 - 22" CLEAR CONICAL LENS

DRL16 - 16" CLEAR PRISMATIC DROP LENS

DRL22 - 22" CLEAR PRISMATIC DROP LENS

BRS16 - 16" ALUMINUM BOTTOM RING

BRS22 - 22" ALUMINUM BOTTOM RING

TRS16 - 16" ALUMINUM TOP RING

TRS22 - 22" ALUMINUM TOP RING

K - ACCESSORY COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

NOTES

(1). FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY.

(2). FINISH OPTIONS 19, 21, 22, 23, 75, 76, 77, 83, 84, 88, 93 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.


(3). FINISH OPTIONS 19, 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.

(4). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.


*ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.).

*ALL FIXTURES MOUNT TO A 4-0 JUNCTION BOX.

*FIXTURE DIMENSIONS MAY VARY ± 0.25.



	HEIGHT	WIDTH
RD12	12"	14.5"
RD16	18"	18"
RD22	25"	23.5"




	HEIGHT	WIDTH
RP12	12"	14.5"
RP16	18"	18"
RP22	25"	23.5"



C – MOUNTING OPTIONS

INCANDESCENT CORD MOUNTS


BASELITE USES A DURABLE SJT CORD FOR ALL CORD MOUNT OPTIONS. ALL CORD MOUNTS COME WITH AN 6" ROUND CANOPY.




CBLC 8' BLACK CORD, CABLE & CANOPY
CWHC 8' WHITE CORD, CABLE & CANOPY




TLB 2.5' BLACK TELEPHONE CABLE
TLW 2.5' WHITE TELEPHONE CABLE



TCB 8' CABLE, BLACK CORD, CANOPY & LOOP
TCW 8' CABLE, WHITE CORD, CANOPY & LOOP



BLC 8' BLACK CORD AND CANOPY
WHC 8' WHITE CORD AND CANOPY



3CBLC 3 CABLE AND BLACK CORD & CANOPY
3CWHC 3 CABLE AND WHITE CORD & CANOPY



HKBC 3/4" HOOK WITH 8' BLACK CORD
HKWC 3/4" HOOK WITH 8' WHITE CORD

STEM MOUNTS




ST(XX) STEM- 3/4" NPT

XX = LENGTH OF STEM
(EXAMPLE – "ST18" = STEM MOUNT 18" LENGTH)
*CANOPY NOT INCLUDED, ADD IN SECTION D

D - MOUNTING ADD-ONS

INCANDESCENT MOUNTING ADD-ONS

* FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY.



SLC 1/2" SLOPE CEILING CANOPY 1/2"
SLC 3/4" SLOPE CEILING CANOPY 3/4"
*(Slopes To 20 Degrees)



STC 1/2" 1/2" STEM MOUNT CANOPY



HB3 - 3/8" HUB



F – LIGHT SOURCE

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT. PLEASE CONTACT THE FACTORY.


INCANDESCENT (INC) MED E26

INC 150W (MAX)- RD12, RP12
300W (MAX)- RD16, RP16, RD22, RP22

***IMPORTANT** – FOR LIGHT EMITTED DIODE (LED) LIGHT SOURCE OPTION FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE LEFT. EXAMPLE: / 300WINC /


OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
150WINC	150W	PER BULB SPECS	>90	120-277 VAC	N/A
300WINC	300W	PER BULB SPECS	>90	120-277 VAC	N/A

J – ACCESSORIES



LEN16 - 16" CLEAR FLAT LENS


LEN22 - 22" CLEAR FLAT LENS



LL12 12" CLEAR CONICAL LENS

LL16 16" CLEAR CONICAL LENS

LL22 22" CLEAR CONICAL LENS



DRL16 - 16" PRISMATIC DROP LENS

DRL22 - 22" PRISMATIC DROP LENS



TRS16 - 16" TOP RING ALUMINUM SHIELD

TRS22 - 22" TOP RING ALUMINUM SHIELD



BRS16 - 16" BOTTOM RING ALUMINUM SHIELD

BRS22 - 22" BOTTOM RING ALUMINUM SHIELD