





## C - MOUNTING OPTIONS

## LED CORD MOUNTS

\*FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY. \*CORDS RATED FOR DRY LOCATION \*CANOPY DIMENSIONS: 4" (H) 5.5" (W)  
\*CORD AND CANOPY COME IN THE SAME COLOR.



**LCBLC** 8' BLACK CORD, CABLE & CANOPY  
**LCWHC** 8' WHITE CORD, CABLE & CANOPY



**LTCB** 8' CABLE, BLACK CORD, LOOP & CANOPY  
**LTCW** 8' CABLE, WHITE CORD, LOOP & CANOPY



**3LCBLC** 3 CABLE, BLACK CORD & CANOPY  
**3LCWHC** 3 CABLE, WHITE CORD & CANOPY



**LTLB** 2.5' BLACK TELEPHONE CABLE & CANOPY  
**LTLW** 2.5' WHITE TELEPHONE CABLE & CANOPY



**LBLC** 8' BLACK CORD AND CANOPY  
**LWHC** 8' WHITE CORD AND CANOPY



**HKLBC** 3/4" HOOK WITH 8' BLACK CORD & CANOPY  
**HKLWC** 3/4" HOOK WITH 8' WHITE CORD & CANOPY

## STEM MOUNTS

\*STEMS ARE RATED FOR DAMP LOCATION




STEM- 1/2" NPT  
**ST(XX)** STEM- 3/4" NPT  
XX = LENGTH OF STEM  
(EXAMPLE - "ST18" = STEM MOUNT 18" LENGTH)  
\*CANOPY NOT INCLUDED, ADD IN SECTION D


## D - MOUNTING ADD-ONS

## LED MOUNTING ADD-ONS

\* FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY.



**LSLC** - LED SLOPE CEILING CANOPY  
\*(Slopes To 20 Degrees)



**LSTC** - STEM MOUNT CANOPY



**HB3** - 3/4" HUB



## BASELITE COMMERCIAL LIGHTING

PROJECT NAME: \_\_\_\_\_  
PROJECT TYPE: \_\_\_\_\_

### F – LIGHT SOURCE

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

#### LIGHT EMITTING DIODE (LED)

**LED 25W (MAX)**- RP12, RD12  
**LED 50W (MAX)**- RP16, RD16  
**LED 100W (MAX)**- RP22, RD22

**\*IMPORTANT** – FOR LIGHT EMITTED DIODE (LED) LIGHT SOURCE OPTION, FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE MAX WATTAGE AVAILABILITY. **EXAMPLE: / LED80W /**

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
LED10W	10W	1570	>90	120-277 VAC	TRI-ELV *120V ONLY
LED12W	12W	1596	>90	120-277 VAC	See section "H"
LED25W	25W	3125	>90	120-277 VAC	See section "H"
LED35W	35W	4200	>90	120-277 VAC	See section "H"
LED50W	50W	5750	>90	120-277 VAC	See section "H"
LED80W	80W	8800	>90	120-277 VAC	See section "H"
LED100W	100W	10500	>90	120-277 VAC	See section "H"
@3500K					

### H – ELECTRICAL OPTION


#### LED DIMMING OPTIONS

(LED10WF – ONLY AVAILABLE WITH **LDM120** - TRI-ELV DIMMING OPTON) ALL OTHER WATTAGES CAN CHOOSE FROM THE OPTIONS BELOW. CONTACT DRIVER MANUFACTURER FOR FURTHER SPECIFICATIONS.

**LDM120** - TRIAC / ELV – INPUT 120 / 277V - DIMMING AT 120 VOLT ONLY  
**LDM0-10V** - 0 – 10V – DIMMING AT 120 / 277 VOLTS

### J – ACCESSORIES


\*NOTE: MUST USE TEMPERED GLASS FOR LIGHT FIXTURES USING HIGH INTENSITY DISCHARGE (HID) LIGHT SOURCE OPTION.



**LEN16** - 16" CLEAR FLAT LENS  
**LEN22** - 22" CLEAR FLAT LENS



**DRL16** - 16" CLEAR PRISMATIC DROP LENS  
**DRL22** - 22" CLEAR PRISMATIC DROP LENS



**LL16** - 16" CLEAR CONICAL LENS  
**LL22** - 22" CLEAR CONICAL LENS



**TRS16** - 16" TOP RING ALUMINUM SHIELD  
**TRS22** - 22" TOP RING ALUMINUM SHIELD



**BRS16** - 16" BOTTOM RING ALUMINUM SHIELD  
**BRS22** - 22" BOTTOM RING ALUMINUM SHIELD