



BASELITE – STAGECOACH – INC– SPECIFICATION SHEET



PROJECT NAME: _____ PROJECT TYPE: _____

MODEL #	/	/	/	/	/	/	/	/	/	/	/	/
	A	B	C	D	E	F	G	H	I	J	K	
EXAMPLE:	SG16	41	E16	SQ ½"	43	45W	3K	LDM120	PR3	GR16	44	

*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES:



SG12/85/B101/85/GR12/100INC

A - SHADES

STAGECOACH

- SG11** - 100WINC (MAX)
- SGF11** - 100WINC (MAX)
- SG12** - 100WINC (MAX)
- SG16** - 200WINC (MAX)
- SG38** - 3-60WINC (MAX)
- SG58** - 5-60WINC (MAX)

B - FINISH OPTIONS

(SEE WEBSITE FOR SWATCH COLORS)
(*SEE NOTES FOR LIMITATIONS*)

- 14, 15, 16, 17, 18, 19, 19P, 20, 20P, 20PB, 20SB, 21, 21P, 22, 22P, 23, 23P, 38, 39, 40, 41, 41.5, 42, 43, 44, 45, 46, 48, 49, 50, 51, 52, 53, 54, 55, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, MG.

C - MOUNTING OPTIONS

½" ARM EXTENSIONS

- E1, E2, E3, E4, B1, E16, E17, E27

¾" ARM EXTENSIONS

- E3A, E4A, E5, E6, E7, E8, E9, E10, E11, E12, E13, B15, B15S, E19, E20, E21, E25

E14 - CREATE YOUR OWN

(BASELITE WILL TAKE YOUR SKETCH AND FABRICATE A CUSTOM ARM EXTENSION TO MEET YOUR NEEDS).

¾" WALL MOUNT

- B13, WM13R, WM13X, B10, B11, B101

¾" WALL MOUNT

- B9, B9C, B12, WM10, WM11, WM14X, WM15, WM35X, WM55X, WM60X, WM61X WM70X, WM71X

CORD MOUNT

- BLC, WHC, TCB, TCW, TCHB, TCHW, TLB, TLW, TLB, TLW, RCB, RCW, RCHB, RCHW, FHB, FHW, CBLC, CWHC

STEM MOUNT

- ST6, ST12, ST18, ST24, ST36, ST48, STXX

D - MOUNTING ADD-ONS

INC ADD-ONS

- CB1/2", CB3/4", CBC1/2", CBC3/4", SLC1/2", SLC3/4", STC1/2"

UNIVERSAL ADD-ONS

- SQ ½", SQ ¾", FH ½", FH ¾", TRB ½", TRB ¾", SWL, LGSWL, CNK, INB, RINB

E - MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

F - LIGHT SOURCE

(SEE PAGE 4 FOR WATTAGE LIMITATIONS)

INCANDESCENT (INC)

- 100W, 150W, 200W

G - LED COLOR TEMP

NOT AVAILABLE

H - ELECTRICAL OPTION

NOT AVAILABLE

I - GLASS OPTIONS

- CL3, CL4, CLT3, CLT4, BL3, BL4, RE3, RE4, GR3, GR4, AH3, AH4, FR3, FR4, FRT3, FRT4, PR3, PR4, BA, BAX, BAF, PR8, PR8F, FN, OC

J - ACCESSORIES

- GR11, GR12, GR16, REF, UGR, LGR11, LGR12, LGR16, CRL11, CRL12, CRL16, FLE11, FLE12, FLE16, FGR11, FGR12, FGR16, GU-1, GU-2, WG-1, WG-2

NOTE: GR11 & GR12 NOT AVAILABLE WHEN GLASS OPTION IS CHOSEN.

K - ACCESSORY COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

NOTES

(1). FINISH OPTIONS 75, 76, 77, 83, 84, 88, 93 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.

(2). FINISH OPTIONS 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.

(3). FINISH OPTIONS FOR SHADES ≤ 10" IN DIAMETER ARE THE SAME INSIDE AND OUT OF FIXTURE. SHADES > 10" IN DIAMETER ARE WHITE ON THE INSIDE.

(4). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.

(5). COLOR CORDS ARE NOT APPLICABLE FOR LED OPTIONS.

*ALL ARMS COME WITH A CAST BACKPLATE (CB1/2", CB3/4", LWTM, CFWTM, ECT.).

*ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.).


*ALL FIXTURES MOUNT TO A 4-O JUNCTION BOX.

*FIXTURE DIMENSIONS MAY VARY ± 0.25.


*CORD AND CANOPY COME IN THE SAME COLOR.




SGF11 H-7" W-11"




SG11 H-9" W-11"



SG12 H-7" W-12"




SG16 H-14" W-16"



SG38 H-11" W-23.5"

FIXTURE COMES AS IS, NO OTHER MOUNTING APPLIES.



SG58 H-11" W-26"

FIXTURE COMES AS IS, NO OTHER MOUNTING APPLIES.



C - MOUNTING OPTIONS

1/2" ARM EXTENSIONS

*ARMS RATED FOR WET LOCATION * MAXIMUM SECTIONS OF ARMS ARE DIMENSIONED *E27 CUSTOM BACK PLATE - 8" (H) .5" (W)




E1 8.5"(H) 18"(W)



E2 13.5"(H) 35"(W)



E3 16"(H) 24.75"(W)



E4 14.5"(H) 22.25"(W)



B1 6.75"(H) 12"(W)



E16 4.75"(H) 8.5"(W)




E17 4.75"(H) 9.5"(W)



E27 10.25"(H) 10.5"(W)

3/4" ARM EXTENSIONS


*ARMS RATED FOR WET LOCATION * MAXIMUM SECTIONS OF ARMS ARE DIMENSIONED




E20 85"(H) 27.25"(W)




E3A 16"(H) 24.75"(W)




E4A 14.5"(H) 22.25"(W)



E5 15"(H) 37"(W)




E6 9"(H) 22.25"(W)




E9 40.25"(H) 27.5"(W)




E12 4.75(H) 37.5"(W)




E7 9"(H) 48.25"(W)




E8 12"(H) 29.75"(W)




E13 30"(H) 25.25"(W)




E14 TBD"(H) TBD"(W)



B15 9.5"(H) 23"(W)



E11 19"(H) 35"(W)



E25 32"(H) 27"(W)



B15S 9.5"(H) 18"(W)



E21 12"(H) 27"(W)



E19 10"(H) 10"(W)

1/2" WALL MOUNTS

*MOUNTS RATED FOR WET LOCATION * MAXIMUM SECTIONS OF MOUNTS ARE DIMENSIONED



B10 4.75"(H) 11"(W)




B101 4.75"(H) 12"(W)




B11 4.75"(H) 13"(W)




B13 4.75"(H) 15"(W)



WM13 12"(H) 9.5"(W)



WM13R 12"(H) 9.5"(W)



WM13X 12"(H) 10.5"(W)

3/4" WALL MOUNTS


*MOUNTS RATED FOR WET LOCATION * MAXIMUM SECTIONS OF MOUNTS ARE DIMENSIONED



B12 4.75"(H) 14"(W)




B9 5"(H) 18"(W)




B9C 5"(H) 18"(W)


*CHAIN HEIGHT TBD BY CUSTOMER



WM14 18"(H) 12"(W)



WM14X 18"(H) 14"(W)










WM15 23"(H) 19.5"(W)



C - MOUNTING OPTIONS (CONTINUED)


3/4" WALL MOUNTS

*MOUNTS RATED FOR WET LOCATION * MAXIMUM SECTIONS OF MOUNTS ARE DIMENSIONED

**WM18** 30"(H) 20"(W)**WM35** 26"(H) 18.25"(W)**WM35X** 26"(H) 22"(W)**WM55** 19"(H) 25.5"(W)**WM55X** 19"(H) 27"(W)**WM60** 18"(H) 20"(W)**WM60X** 18"(H) 22"(W)**WM61** 18"(H) 20"(W)**WM61X** 18"(H) 22"(W)**WM70** 18"(H) 20"(W)**WM70X** 18"(H) 22"(W)**WM71** 18"(H) 20"(W)**WM71X** 18"(H) 22"(W)

STEM MOUNTS


*STEMS RATED FOR DAMP LOCATION

**DP24** DOUBLE PENDANT 20"(H) 24"(W)*DP24 COMES STANDARD WITH STC
AND ST18**ST(XX)** STEM- 1/2" NPTXX = LENGTH OF STEM
(EXAMPLE - "ST18" = STEM MOUNT 18" LENGTH)
*CANOPY NOT INCLUDED, ADD IN SECTION D
* 1/4" NPT AND 3/4" NPT AVAILABLE UPON REQUEST**SC24** SCROLL STEM 33"(H) 24"(W)

*SC24 COMES STANDARD WITH STC

INCANDESCENT CORD MOUNTS

*INCANDESCENT MAX WATTAGE 150 WATT. CALL FACTORY FOR HIGHER WATTAGES. LOOPS, CABLES, AND CHAINS AVAILABLE ONLY FOR INCANDESCENT. *CORDS RATED FOR DRY LOCATION *CANOPY DIMENSIONS: .625" (H) 5.25" (W) *CORD AND CANOPY COME IN THE SAME COLOR.

**BLC** 8' BLACK CORD
WHC 8' WHITE CORD**TCB** 8' BLACK CORD, CABLE, and LOOP
TCW 8' WHITE CORD, CABLE, and LOOP**TCHB** 8' BLACK CORD, 3' CHAIN, and LOOP
TCHW 8' WHITE CORD, 3' CHAIN, and LOOP**TLB** 8' BLACK TELEPHONE CORD AND CABLE
TLW 8' WHITE TELEPHONE CORD AND CABLE
* Not available H.I.D.**RCB** 8' BLACK CORD, CABLE, and LOOP
RCW 8' WHITE CORD, CABLE, and LOOP**RCHB** 8' BLACK CORD, 3' CHAIN, and LOOP
RCHW 8' WHITE CORD, 3' CHAIN, and LOOP**FHB** 8' BLACK CORD WITH FLAT HUB
FWH 8' WHITE CORD WITH FLAT HUB**CBLC** 8' BLACK CORD and CABLE
CWLC 8' WHITE CORD and CABLE**CHB** 8' BLACK CORD, 3' CHAIN, and LOOP
CHW 8' WHITE CORD, 3' CHAIN, and LOOP
* Loop may vary due to shade style



I – GLASS OPTIONS

*NOTE: MUST USE TEMPERED GLASS FOR LIGHT FIXTURES USING HIGH INTENSITY DISCHARGE (HID) LIGHT SOURCE OPTION.



CL3 3" CLEAR GLASS



PR3 3" PRISMATIC GLASS



RE3 3" RED GLASS



BL3 3" BLUE GLASS

CL4 4" CLEAR GLASS

PR4 4" PRISMATIC GLASS

RE4 4" RED GLASS

BL4 4" BLUE GLASS

CLT3 3" CLEAR TEMPERED

CLT4 4" CLEAR TEMPERED



FR3 3" FROSTED GLASS

FR4 4" FROSTED GLASS

FRT3 3" FROSTED TEMPERED

FRT4 4" FROSTED TEMPERED




AH3 3" AMBER HYDE GLASS

AH4 4" AMBER HYDE GLASS



GR3 3" GREEN GLASS

GR4 4" GREEN GLASS



GLASS – DIMENSIONS	
3" GLASS	
Diameter	3.34"
Height	6.93"
Fitter	3.29"
4" GLASS	
Diameter	4.34"
Height	8.37"
Fitter	4.29"

GLASS – MAX WATTAGE	
3" GLASS – 100W INC / LED12W	
4" GLASS – 200W INC / LED25W	



BA 6" OPAL BALL
(100W INC MAX/LED12W)



BAX 9" CLEAR GLOBE
BAF 9" FROSTED GLOBE
(200W INC MAX/LED25W)



FN 8" CLEAR TEXTURED GLOBE
(150W INC MAX/LED25W)



BA7 7" CLEAR GLOBE

BA7F 7" FROSTED GLOBE
(100W INC MAX/LED25W)




PR8 8" PRISMATIC

PR8F 8" PRISMATIC FROSTED
(200W INC MAX/LED45W)



OC 8" OPAL TAPERED GLOBE
(60W INC MAX/LED25W)


J – ACCESSORIES



GR11 11" WIRE GRILL

GR12 12" WIRE GRILL


GR16 16" WIRE GRILL
(GR11 & GR12 not available
when glass option is
chosen.)



LGR11 11" LOUVERED GRILL

LGR12 12" LOUVERED GRILL

LGR16 16" LOUVERED GRILL



FGR11 11" FLAT GRILL

FGR12 12" FLAT GRILL


FGR16 16" FLAT GRILL



CRL11 11" CURVED POLYCARB LENSE

CRL12 12" CURVED POLYCARB LENSE


CRL16 16" CURVED POLYCARB LENSE



FLE11 11" FLAT CLEAR LENSE

FLE12 12" FLAT CLEAR LENSE


FLE16 16" FLAT CLEAR LENSE




REF 9.5" DIAMETER REFRACTOR




UGR U- WIRE GUARD




WG-1 WIRE GUARD



WG-2 WIRE GUARD
Available for shades
12" or higher



GU-1 CAST ALUMINUM GUARD



GU-2 CAST ALUMINUM GUARD
Available for shades
12" or higher