

BASELITE - PW- INC - SPECIFICATION SHEET





PROJECT NAME: PROJECT TYPE: . MODEL# Χ В С D Ε F Н J G Κ 1 EXAMPLE: PW1 BWCC 3-25WLED LDM120 WG1

A - SHADES

PW SERIES

PW1 - 100WINC (MAX), (3" GLASS), (3" GUARD) PW2 - 200WINC (MAX), (4" GLASS), (4" GUARD)

B-FINISH OPTIONS

(*SEE NOTES FOR LIMITATIONS*) (SEE WEBSITE FOR SWATCH COLORS) 20, 21, 22, 23, 40, 41, 41.5, 42, 43, 44, 45, 46, 48, 49, 50, 51, 52, 53, 54, 55, 59, 60, 61, 62, 63, 70, 71, 72, 73

C – MOUNTING OPTIONS

CORD MOUNT

BLC, WHC, TCB, TCW, TCHB, TCHW, TLB, TLW, TLB, TLW, RCB, RCW, RCHB, RCHW, FHB, FHW, HBLC, HWHC, CBLC, CWHC **STEM MOUNT**

ST6, ST12, ST18, ST24, ST36, ST48, STXX

D - MOUNTING ADD-ONS

CNK - 13" ROUND CANOPY

E - MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

F – LIGHT SOURCE

(SEE PAGE 2 FOR WATTAGE LIMITATIONS) INCANDESCENT (INC) 100W, 150W, 200W

G – LED COLOR TEMP

NOT AVAILABLE

H – ELECTRICAL OPTION

NOT AVAILABLE

I - GLASS OPTIONS

CL3, CLT3, BL3, RE3, GR3, AH3, FR3, FRT3, PR3

4" GLASS

CL4, CLT4, BL4, RE4, GR4, AH4, FR4, FRT4, PR4

J - ACCESSORIES

3" GUARDS

WG1

4" GUARDS

WG2

K – ACCESSORY COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

NOTES

(1). FINISH OPTIONS 40, 49, 54, 61, 62, 63, 70, 71, 72, 73 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE, OTHER FINISHES ARE WHITE INSIDE.

(2). FINISH OPTIONS FOR SHADES ≤ 10" IN DIAMETER ARE THE SAME INSIDE AND OUT OF FIXTURE SHADES > 10" IN DIAMETER ARE WHITE ON THE INSIDE.

(3). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.

*ALL ARMS COME WITH A CAST BACKPLATE (CB1/2", CB3/4", LWTM, CFWTM, ECT.).


*ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.).

*ALL FIXTURES MOUNT TO A 4-O JUNCTION BOX.


*FIXTURE DIMENSIONS MAY VARY ± 0.25 .

*CORD AND CANOPY COME IN THE SAME COLOR.

*RATED FOR WET LOCATION.



PW1 H - 11.5" W - 4.5"



PW2 H - 12.75" W - 5.5"

BASELITE VAPOR JAR CATALOG

PROJECT NAME: ______PROJECT TYPE: _____

C-MOUNTING OPTIONS

STEM MOUNTS

*STEMS RATED FOR DAMP LOCATION



ST(XX)

STEM- 1/2" NPT

XX = LENGTH OF STEM (EXAMPLE – "ST18" = STEM MOUNT 18" LENGTH) *CANOPY NOT INCLUDED, ADD IN SECTION D

* 1/4" NPT AND 3/4" NPT AVAILABLE UPON REQUEST

INCANDESCENT CORD MOUNTS

*INCANDESCENT MAX WATTAGE 150 WATT. CALL FACTORY FOR HIGHER WATTAGES. LOOPS, CABLES, AND CHAINS AVAILABLE ONLY FOR INCANDESCENT *CORDS RATED FOR DRY LOCATION *CANOPY DIMENSIONS: .625" (H) 5.25" (W) *CORD AND CANOPY COME IN THE SAME COLOR.





TCB 8' BLACK CORD, CABLE, and LOOP
TCW 8' WHITE CORD, CABLE, and LOOP



TCHB 8' BLACK CORD, 3' CHAIN, and LOOP
TCHW 8' WHITE CORD, 3' CHAIN, and LOOP



TLW 8' BLACK TELEPHONE CORD AND CABLE

**TLW 8' WHITE TELEPHONE CORD AND CABLE



RCB 8' BLACK CORD, CABLE, and LOOP
RCW 8' WHITE CORD, CABLE, and LOOP



RCHB 8' BLACK CORD, 3' CHAIN, and LOOP

RCHW 8' WHITE CORD, 3' CHAIN, and LOOP



FHW 8' BLACK CORD WITH FLAT HUB
8' WHITE CORD WITH FLAT HUB



CBLC 8' BLACK CORD and CABLE
CWLC 8' WHITE CORD and CABLE



CHB 8' BLACK CORD, 3' CHAIN, and LOOP

CHW 8' WHITE CORD, 3' CHAIN, and LOOP * Loop may vary due to shade style

F – LIGHT SOURCE

INCANDESCENT (INC) MED E26

INC 100W- PW1 INC 200W- PW2

*IMPORTANT – FOR INCANDESCENT (INC) LIGHT SOURCE OPTION, FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE LEFT.

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
100WINC	100W	PER BULB SPECS	>90	120-277 VAC	N/A
150WINC	150W	PER BULB SPECS	>90	120-277 VAC	N/A
200WINC	200W	PER BULB SPECS	>90	120-277 VAC	N/A

^{*}FIXTURE WATTAGE CAN BE DE-RATED TO MEET CODE COMPLIANCE "XXMED" – XX = DESIRED WATTAGE RATING BELOW MAX.

BASELITE VAPOR JAR CATALOG

PROJECT NAME: _____PROJECT TYPE: _____

I – GLASS OPTIONS

NOTE : GLASS IS HEAT REISISTANCE BOROSILICATE. *TEMPERD GLASS AVAILABLE UPON REQUEST. CONTANCT YOUR LOCAL SALES REPRESENTATIVE FOR INFORMATION OR CALL FACTORY FOR QUESTIONS.



J – ACCESSORIES

