



# BASELITE - PIER MOUNTS - INC - SPECIFICATION SHEET



PROJECT NAME: \_\_\_\_\_ PROJECT TYPE: \_\_\_\_\_

MODEL #	/	/	X	/	X	/	/	/	/	/	X	/
EXAMPLE:	PR15	41	-	-	41	12WLED	3K	LDM120	FR	-	41	

\*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES:



## A - SHADES

- PR**  
**PR1** - 100WINC (MAX)  
**PR2** - 100WINC (MAX)  
**PR3** - 100WINC (MAX)  
**PR4** - 100WINC (MAX)  
**PR5** - 100WINC (MAX)  
**PR11** - 200WINC (MAX)  
**PR12** - 200WINC (MAX)  
**PR13** - 200WINC (MAX)  
**PR14** - 200WINC (MAX)  
**PR15** - 200WINC (MAX)  
**PRH/PRD**  
**PRH1** - 100WINC (MAX)  
**PRD1** - 100WINC (MAX)

## B - FINISH OPTIONS

(\*SEE NOTES FOR LIMITATIONS\*)  
 (SEE WEBSITE FOR SWATCH COLORS)  
 20, 21, 22, 23, 40, 41, 41.5, 42, 43, 44, 45,  
 46, 48, 49, 50, 51, 52, 53, 54, 55, 59, 60,  
 61, 62, 63, 70, 71, 72, 73

## C - MOUNTING OPTIONS

NOT AVAILABLE

## D - MOUNTING ADD-ONS

NOT AVAILABLE

## E - MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

## F - LIGHT SOURCE

(SEE PAGE 2 FOR WATTAGE LIMITATIONS)  
**INCANDESCENT (INC)**  
 100W, 200W

## G - LED COLOR TEMP

NOT AVAILABLE

## H - ELECTRICAL OPTION

NOT AVAILABLE

## I - GLASS OPTIONS

**GLASS**  
 CL, FR

## J - ACCESSORIES

NOT AVAILABLE

## K - ACCESSORY COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

## NOTES

- (1). FINISH OPTIONS 40, 49, 54, 61, 62, 63, 70, 71, 72, 73 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.
- (2). FINISH OPTIONS FOR SHADES ≤ 10" IN DIAMETER ARE THE SAME INSIDE AND OUT OF FIXTURE. SHADES > 10" IN DIAMETER ARE WHITE ON THE INSIDE.
- (3). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.  
 \*ALL ARMS COME WITH A CAST BACKPLATE (CB1/2", CB3/4", LWTM, CFWTM, ECT.).  
 \*ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.).  
 \*ALL FIXTURES MOUNT TO A 4-O JUNCTION BOX.  
 \*FIXTURE DIMENSIONS MAY VARY ± 0.25.  
 \*CORD AND CANOPY COME IN THE SAME COLOR.  
 \*RATED FOR WET LOCATION.



**PR1** H - 10.25" W - 6.25"  
**PR11** H - 11.75" W - 6.25"




**PR2** H - 10.25" W - 6.25"  
**PR12** H - 11.75" W - 6.25"




**PR3** H - 10.25" W - 6.25"  
**PR13** H - 11.75" W - 6.25"




**PR4** H - 10.25" W - 6.25"  
**PR14** H - 11.75" W - 6.25"




**PR5** H - 10.25" W - 6.25"  
**PR15** H - 11.75" W - 6.25"



**PRH1** H - 12" W - 8"



**PRD1** H - 12" W - 12"



**PMAS116** H - 14.75" W - 16



**F – LIGHT SOURCE**

**INCANDESCENT (INC) MEDIUM BASE E26**

**INC 100W(MAX)** - PR1, PR2, PR3, PR4, PR5, PRH1, PRD1  
**INC 200W (MAX)** - PR11, PR12, PR13, PR14, PR15

*\*IMPORTANT – FOR COMPACT FLUORESCENT (CF) LIGHT SOURCE, FIXTURES ARE LIMITED DUE TO THE SIZE OF THE SHADE. PLEASE SEE THE CHART TO THE LEFT TO SEE WHAT WATTAGE IS COMPARABLE FOR EACH FIXTURE WHEN ORDERING. EXAMPLE: /INC100W/*

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
INC100W	100W	PER BULB SPECS	>90	120-277 VAC	N/A
INC200W	200W	PER BULB SPECS	>90	120-277 VAC	N/A

**I – GLASS OPTIONS**

\* NOTE: MUST USE TEMPERED GLASS FOR LIGHT FIXTURES USING HIGH INTENSITY DISCHARGE (HID) LIGHT SOURCE OPTION. \* GLASS SIZE COMES STANDARD WITH CHOSEN SHADE. ONLY GLASS TRANSPARENCY CAN BE CHOSEN.  
\* SMALL GLASS ONLY AVAILABLE FOR BSM1 – 6 \* LARGE GLASS ONLY AVAILABLE FOR BSM11 - 16



**CL** CLEAR SMALL GLASS




**FR** FROSTED SMALL GLASS



**CL** CLEAR LARGE GLASS



**FR** FROSTED LARGE GLASS



GLASS – DIMENSIONS	
<b>SMALL GLASS</b>	
Diameter	4.25"
Height	6.25"
Fitter	5.25"
<b>LARGE GLASS</b>	
Diameter	4.25"
Height	8.5"
Fitter	5.25"