



BASELITE - BISTRO – MED – SPECIFICATION SHEET



PROJECT NAME: _____ PROJECT TYPE: _____

NOTES: **BABA COMPLIANT**

*FOR A COMPLETE MODEL NUMBER, MAKE A SELECTION FROM THE DROP DOWNS BELOW. SKIP SECTIONS THAT DO NOT APPLY.

MODEL

EXAMPLE: S2H1 41 BLC SLC1/2" 41 60MED

A - SHADES

BISTRO COLLECTION

- S2H1 - (100W MAX)
- S2H2 - (100W MAX)
- S2H3 - (100W MAX)
- S2H4 - (100W MAX)
- S2H5 - (100W MAX)
- S2H6 - (100W MAX)
- S2H7 - (100W MAX)
- S2H8 - (100W MAX)
- S2H9 - (100W MAX)
- S2H10 - (100W MAX)
- CA57 - (100W MAX)
- GBL6 - (100W MAX)
- WMCS5 - (100W MAX)
- S2KT6 - (100W MAX)
- FMS14 - (100W MAX)
- H2FH - (100W MAX)

B - FINISH OPTIONS

(SEE WEBSITE FOR SWATCH COLORS)
 (*SEE NOTES FOR LIMITATIONS*)
 14, 15, 16, 17, 18, 19, 19P, 20, 20P, 20PB, 20SB, 21, 21P, 22, 22P, 23, 23P, 38, 39, 40, 41, 41.5, 42, 43, 44, 45, 46, 48, 49, 50, 51, 52, 53, 54, 55, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, MG.

C - MOUNTING OPTIONS

1/2" WALL MOUNT

WM20, WM21, WM23, WM24, WM25, WM26, WM29, WM29V

CORD MOUNT

BLC, WHC

STEM MOUNT

ST6, ST12, ST18, ST24, ST36, ST48, STXX

D - MOUNTING ADD-ONS

INC ADD-ONS

STC1/2"
SLC1/2"

E - MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

F - LIGHT SOURCE

(SEE PAGE 3 FOR WATTAGE LIMITATIONS)

MEDIUM BASE E26 (MED)

60W, 100W (MAX)

G - LED COLOR TEMP

NOT AVAILABLE

H - ELECTRICAL OPTION

NOT AVAILABLE

I - GLASS OPTIONS

NOT AVAILABLE

J - ACCESSORIES

NOT AVAILABLE


K - ACCESSORY COLOR

SEE SECTION "B" FOR COLOR OPTIONS.


NOTES

- (1). FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY.
 - (2). FINISH OPTIONS 19A, 21A, 22A, 23A, 75, 76, 77, 83, 84, 88, 93 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.
 - (3). FINISH OPTIONS 19, 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.
 - (4). FINISH OPTIONS FOR SHADES ≤ 10" IN DIAMETER ARE THE SAME INSIDE AND OUT OF FIXTURE. SHADES > 10" IN DIAMETER ARE WHITE ON THE INSIDE.
 - (5). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.
 - (6). COLOR CORDS ARE NOT APPLICABLE FOR LED OPTIONS.
- *ALL ARMS COME WITH A CAST BACKPLATE (CB1/2", CB3/4", LWTM, CFWTM, ECT.).
 *ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER).
 *ALL FIXTURES MOUNT TO A 4-O JUNCTION BOX.
 *FIXTURE DIMENSIONS MAY VARY ± 0.25.
 *CORD AND CANOPY COME IN THE SAME COLOR.


SHADE DIMENSIONS




FMS14 H- 4" W- 14"




S2H1 H- 4.5" W- 8.5"




S2H3 H- 5" W- 9"




S2H5 H- 6" W- 10"




S2H7 H- 4.5" W- 10"




S2H9 H- 5" W- 9"




CA57 H- 7.625" W- 5.25"




WMC5 H- 6.5" W- 5"




S2H2 H- 4.5" W- 12"



S2H4 H- 3.5" W- 10"




S2H6 H- 7" W- 12"




S2H8 H- 3.125" W- 9"




S2H10 H- 4.5" W- 7.5"



S2KT6 H- 8" W- 6"



H2FH H- 2.5" W- 12"




GBL6 H- 5" W- 6"

GLASS PANEL MIRRORS INSIDE REFLECTOR
NO MIRRORS AVAILABLE, SPECIFY ON ORDER



C - MOUNTING OPTIONS


1/4" WALL MOUNTS



WM20 6"(H) 8.25"(W)




WM21 4.75"(H) 8"(W)




WM23 12.5"(H) 8"(W)



WM24 11"(H) 6.375"(W)




WM26 12"(H) 9"(W)



WM25 9"(H) 5.5"(W)



WM29 9.5"(H) 14"(W)



WM29V 21.75"(H) 15.25"(W)

CORD MOUNT

*CORDS RATED FOR DRY LOCATION *CANOPY DIMENSIONS: .625" (H) 5.25" (W) *CORD AND CANOPY COME IN THE SAME COLOR.



BLC 8' BLACK CORD (INCLUDES CANOPY)
WHC 8' WHITE CORD (INCLUDES CANOPY)

STEM MOUNTS

NOTE: CANOPY NOT INCLUDED, ADD IN SECTION "D"



ST(XX) STEM- 1/4" NPT
XX = LENGTH OF STEM
(EXAMPLE - "ST18" = STEM MOUNT 18" LENGTH)

*STEM OPTION FOR ALL BISTRO EXCLUDING: FMS14 & H2FH




ST(XX) STEM- 1/2" NPT
XX = LENGTH OF STEM
(EXAMPLE - "ST18" = STEM MOUNT 18" LENGTH)




D - MOUNTING ADD-ONS

ARM ADD-ONS



STC 1/2" 1/2" STEM MOUNT CANOPY



SLC 1/2" SLOPE CEILING CANOPY 1/2"
*(Slopes To 20 Degrees)

F- LIGHT SOURCE

MEDIUM BASE (MED) MED E26

MED 100W (MAX) - S2H1, S2H2, S2H3, S2H4, S2H5, S2H6, S2H7, S2H8, S2H9, S2H10, S2KT6, CA57, FMS14, GBL6, GRS810, H2, WMC5

***IMPORTANT** – FOR MEDIUM BASE (MED) LIGHT SOURCE OPTION FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE LEFT.

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
MED60W	60W	PER BULB SPEC	PER BULB SPEC	120-277 VAC	PER BULB SPEC
MED100W	100W	PER BULB SPEC	PER BULB SPEC	120-277 VAC	PER BULB SPEC

*FIXTURE WATTAGE CAN BE DE-RATED TO MEET CODE COMPLIANCE "XXMED" – XX = DESIRED WATTAGE RATING BELOW MAX.