



BASELITE – A - AH – LED – SPECIFICATION SHEET



PROJECT NAME: _____ PROJECT TYPE: _____

MODEL #	/	/	X	/	X	/	X	/	/	/	/	/	/
EXAMPLE:	A	B	C	D	E	F	G	H	I	J	K		

AH1 41 - - 100WINC 3K LDM120 FR3 CG1 41

*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES: BABA COMPLIANT

A - SHADES

A-AH SERIES

- A1** - 12WLED (MAX), (3" GLASS), (3" GUARD)
- A2** - 25WLED (MAX), (4" GLASS), (4" GUARD)
- AH1** - 12WLED (MAX), (3" GLASS), (3" GUARD)
- AH2** - 25WLED (MAX), (4" GLASS), (4" GUARD)

B - FINISH OPTIONS

(SEE NOTES FOR LIMITATIONS)
(SEE WEBSITE FOR SWATCH COLORS)

20, 21, 22, 23, 40, 41, 41.5, 42, 43, 44, 45, 46, 48, 49, 50, 51, 52, 53, 54, 55, 59, 60, 61, 62, 63, 70, 71, 72, 73

C - MOUNTING OPTIONS

NOT AVAILABLE

D - MOUNTING ADD-ONS

NOT AVAILABLE

E - MOUNTING COLOR

NOT AVAILABLE

F - LIGHT SOURCE

(SEE PAGE 2 FOR WATTAGE LIMITATIONS)

LIGHT EMITTED DIODE (LED)

10W, 12W, 25W

*NOTE – MAX WATTAGE IS LISTED NEXT TO THE SHADE MODEL NUMBER IN SECTION "A". ALL WATTAGES BELOW THAT ARE ALSO AVAILABLE FOR THE SAME MODEL NUMBER.

G - LED COLOR TEMP

- 27K** – 2700 KELVIN
- 3K** – 3000 KELVIN
- 35K** – 3500 KELVIN
- 4K** – 4000 KELVIN
- 5K** – 5000 KELVIN

H - ELECTRICAL OPTION

(SEE PAGE 2 FOR DIMMING OPTION SPECIFICATIONS)

LDM120

LDM0-10

I - GLASS OPTIONS

- 3" GLASS** (AVAILABLE FOR A1 & AH1)
CL3, CLT3, BL3, RE3, GR3, AH3, FR3, FRT3, PR3
- 4" GLASS** (AVAILABLE FOR A2 & AH2)
CL4, CLT4, BL4, RE4, GR4, AH4, FR4, FRT4, PR4

J - ACCESSORIES

- 3" GUARDS** (AVAILABLE FOR A1 & AH1)
CG1, WG1
- 4" GUARDS** (AVAILABLE FOR A2 & AH2)
CG2, WG2

K - ACCESSORY COLOR


SEE SECTION "B" FOR COLOR OPTIONS.

NOTES

- (1). FINISH OPTIONS 40, 49, 54, 61, 62, 63, 70, 71, 72, 73 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.
- (2). FINISH OPTIONS FOR SHADES \leq 10" IN DIAMETER ARE THE SAME INSIDE AND OUT OF FIXTURE. SHADES $>$ 10" IN DIAMETER ARE WHITE ON THE INSIDE.
- (3). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.

*ALL ARMS COME WITH A CAST BACKPLATE (CB1/2", CB3/4", LWTM, CFWTM, ECT.).
*ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.).
*ALL FIXTURES MOUNT TO A RECESSED 4-O JUNCTION BOX.
*FIXTURE DIMENSIONS MAY VARY \pm 0.25.
*RATED FOR WET LOCATION.

SHADE DIMENSIONS




A1 H-13" W-4" PROJ. -725"

A2 H-15.5" W-5.5" PROJ. -8.125"

3" GLASS & 3" GUARD AVAILABLE FOR A1

4" GLASS & 4" GUARD AVAILABLE FOR A2



AH1 H-13" W-6.5" PROJ. -9"

AH2 H-16" W-8.25" PROJ. -10.5"

3" GLASS & 3" GUARD AVAILABLE FOR AH1

4" GLASS & 4" GUARD AVAILABLE FOR AH2



AH1/77/100WINC/FR3/CG1/77

**F – LIGHT SOURCE**

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS.

LIGHT EMITTING DIODE (LED)**LED 12W (MAX) - A1, AH1****LED 25W (MAX) - A2, AH2**

*IMPORTANT – FOR LIGHT EMITTED DIODE (LED) LIGHT SOURCE OPTION, FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE MAX WATTAGE AVAILABILITY.

EXAMPLE: / LED25W /

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
LED10WF	10W	1280	>90	120-277 VAC	TRI-ELV *120V ONLY
LED12W	12W	1481	>90	120-277 VAC	See section "H"
LED25W	25W	2812	>90	120-277 VAC	See section "H"

@3500K

H – ELECTRICAL OPTION

BASELITE'S ELECTRICAL OPTIONS ARE ONLY COMPATIBLE FOR CERTAIN FIXTURES, SO RESTRICTIONS APPLY DUE TO THE SIZE OF THE DRIVER AND FIXTURE. PLEASE SEE INFORMATION BELOW AND FOR FURTHER DETAILS CONTACT THE FACTORY.

LED DIMMING OPTIONS

(LED10WF – ONLY AVAILABLE WITH **LDM120** – TRI-ELV DIMMING OPTON) ALL OTHER WATTAGES CAN CHOOSE FROM THE OPTIONS BELOW. CONTACT DRIVER MANUFACTURER FOR FURTHER SPECIFICATIONS.

LDM120 - TRIAC / ELV – INPUT 120 / 277V - DIMMING AT 120 VOLT ONLY**LDM0-10V** - 0 – 10V – DIMMING AT 120 / 277 VOLTS**I – GLASS OPTIONS**

* NOTE : GLASS IS HEAT RESISTANCE BOROSILICATE. *TEMPERED GLASS AVAILABLE UPON REQUEST. CONTACT YOUR LOCAL SALES REPRESENTATIVE FOR INFORMATION OR CALL FACTORY FOR QUESTIONS.

* 3" GUARDS AVAILABLE FOR 4PE1, 4HPE1, 4DPE1

**CL3** 3" CLEAR GLASS
CL4 4" CLEAR GLASS**PR3** 3" PRISMATIC GLASS
PR4 4" PRISMATIC GLASS**RE3** 3" RED GLASS
RE4 4" RED GLASS**BL3** 3" BLUE GLASS
BL4 4" BLUE GLASS**FR3** 3" FROSTED GLASS
FR4 4" FROSTED GLASS**AH3** 3" AMBER HYDE GLASS
AH4 4" AMBER HYDE GLASS**GR3** 3" GREEN GLASS
GR4 4" GREEN GLASS

GLASS – DIMENSIONS

3" GLASS
Diameter 3.34"
Height 6.93"
Fitter 3.29"4" GLASS
Diameter 4.34"
Height 8.37"
Fitter 4.29"

GLASS – MAX WATTAGE





3" GLASS – 100W INC / LED12W

4" GLASS – 200W INC / LED25W

J – ACCESSORIES

* 3" GUARDS AVAILABLE FOR A1 & AH1

* 4" GUARDS AVAILABLE FOR A2 & AH2

**WG1** 3" WIRE GUARD**WG2** 4" WIRE GUARD**CG1** 3" CAST GUARD**CG2** 4" CAST GUARD