



BASELITE – SCHOOLHOUSE – INC – SPEC SHEET



PROJECT NAME: _____ PROJECT TYPE: _____

MODEL #	/	/	/	/	/	/	/	/	
EXAMPLE:	A SCP	B PSTL	C 41.5	D ST18	E STC	F 41.5	G 12LED	H 3K	I LDM120

NOTES: BABA COMPLIANT

A - SHADES

SCHOOL HOUSE

SKT -100W (MAX) 8" GLASS
S2R8 -100W (MAX) 8" GLASS
SCF -100W (MAX) 12" GLASS 150W (MAX) 14" & 16" GLASS 200W (MAX) 18" GLASS
SCFS -100W(MAX) 12" GLASS 150W (MAX) 14" & 16" GLASS 200W (MAX) 18" GLASS
FNF -100W (MAX) 12" GLASS 150W (MAX) 14" & 16" GLASS
FNP -100W (MAX) 12" GLASS 150W (MAX) 14" & 16" GLASS
SCP -200W (MAX) 18" GLASS
SCPC -200W (MAX) 18" GLASS
SCPL -200W (MAX) 18" GLASS
DLP -100W (MAX) 12" GLASS 150W (MAX) 14" & 16" GLASS 200W (MAX)18" GLASS

B - GLASS OPTIONS

6" FITTER

SCH14, SCO12, SHO14, SHO16, SHO18, SQO12, SOB12, SOB14, SOB16, SOB18, PSGN, PSRD, PSTL, PSGY

4" FITTER

PSBL, SQO8, AC, SHC10

4" THREADED FITTER

BAF.PSGN, BAF.PSRD, BAF.PSTL, BAF.PSBL

C - FINISH OPTIONS

(SEE WEBSITE FOR SWATCH COLORS)

(*SEE NOTES FOR LIMITATIONS*)

14, 15, 16, 17, 18, 19, 19P, 20, 20P, 20PB, 20SB, 21A, 21, 22A, 22, 23A, 23, 38, 39, 40, 41, 41.5, 43, 44, 48, 49, 50, 51, 52, 53, 55, 57, 58, 59, 61, 62, 63, 78, 80, 81, 82, 85, 86, 87, 89, 91, 92, 94, 95, 97, 98, 99, 100

D - MOUNTING OPTIONS

BLC - 8' BLACK CORD

WHC - 8' WHITE CORD

TCHB - 8' CORD, 3' CHAIN, & LOOP

TCHW - 8' CORD, 3' CHAIN, & LOOP

CBLC - 8' CORD & CABLE

CWLC - 8' CORD & CABLE

STXX - STEM (XX=STEM LENGTH)

E - MOUNTING ADD-ONS

SLC $\frac{1}{2}$ " - SLOPE CEILING CANOPY $\frac{1}{2}$ "

STC $\frac{1}{2}$ " - STEM CANOPY $\frac{1}{2}$ "

F - MOUNTING COLOR

*SEE SECTION "C" FOR MOUNTING COLOR OPTIONS.

G - LIGHT SOURCE

(SEE SECTION "G" FOR LIGHT SOURCE AND WATTAGE OPTIONS)

INCANDESCENT (INC)

100W, 150W, 200W

H - LED COLOR

(ONLY APPLICABLE FOR LED LIGHT SOURCE. SKIP THIS SECTION IF OPTION DOES NOT APPLY.)

27K - 2700 KELVIN

3K - 3000 KELVIN

35K - 3500 KELVIN

4K - 4000 KELVIN

5K - 5000 KELVIN

I - ELECTRICAL OPTIONS

(ONLY APPLICABLE FOR LED LIGHT SOURCE. SKIP THIS SECTION IF OPTION DOES NOT APPLY.)

LED DIMMING OPTIONS

LDM120

LDM277

LDM0-10

NOTES

*ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.)


*FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY

*FINISH OPTIONS 19, 21, 22, 23 ARE AN ACID FINISH AND IS APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.

*FINISH OPTIONS 61 & 62 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS. *FIXTURE DIMENSIONS MAY VARY \pm 0.25"



SCFS/PSTL/41.5/12LED/3K/LDM120



SKT H-3" W-4"



DLP H-10" W-6"




SCF H-8.75" W-6"

*FLUSH MOUNT, MOUNTING OPTIONS DO NOT APPLY



FNF H-7" W-6"

*FLUSH MOUNT, MOUNTING OPTIONS DO NOT APPLY




SCFS H-5.75" W-6.25"

*FLUSH MOUNT, MOUNTING OPTIONS DO NOT APPLY



SCPL H-29.25" W-20.5"

FNP H-10.5" W-6"



S2R8 H-2.5" W-4.5"



SCPC H-3" W-6"



BASELITE – SCHOOLHOUSE - SPECIFICATION SHEET

PROJECT NAME: _____
PROJECT TYPE: _____

B – GLASS OPTIONS

*NOTE – THE LIST OF “SHADES” ARE ALL APPLICABLE WITH THE GLASS OPTIONS SHOWN IN THIS SECTION.

6" FITTER SHADES

SCF
SCFS
SCP
SCPC
SCPL
DLP



SHC14 – 14" CLEAR GLASS



SHO12 – 12" OPAL GLASS
SHO14 – 14" OPAL GLASS
SHO16 – 16" OPAL GLASS
SHO18 – 18" OPAL GLASS



SQO12 – 12" SQUARE OPAL GLASS



SOB12 – 12" SLANT OPAL GLASS
SOB14 – 14" SLANT OPAL GLASS
SOB16 – 16" SLANT OPAL GLASS
SOB18 – 18" SLANT OPAL GLASS



PSGN
12" OPAL GLASS
WITH LIME GREEN AND BLACK
PINSTRIPE HAND-PAINTED LINES



PSRD
12" OPAL GLASS
WITH RED-ORANGE AND BLACK
PINSTRIPE HAND-PAINTED LINES



PSTL
12" OPAL GLASS
WITH TEAL AND BLACK
PINSTRIPE HAND-PAINTED LINES



PSGY
12" OPAL GLASS
WITH GREY PINSTRIPE
HAND-PAINTED LINES

*NOTE – THE LIST OF “SHADES” ARE ALL APPLICABLE WITH THE GLASS OPTIONS SHOWN IN THIS SECTION. FOR LED OPTION 12W MAX.

4" FITTER SHADES

FNF
FNP
S2R8



PSBL
8" OPAL GLASS
WITH NAVY BLUE AND BLACK
PINSTRIPE HAND-PAINTED LINES



SQO8
8" SQUARE
OPAL GLASS



AC
7" CLEAR TEXTURED
ACORN GLASS



SHC10 – 10" CLEAR GLASS

*NOTE – THE LIST OF “SHADES” ARE ALL APPLICABLE WITH THE GLASS OPTIONS SHOWN IN THIS SECTION. FOR LED OPTION 12W MAX.

4" THREADED FITTER SHADES

SKT



BAF.PSGN
8" OPAL GLASS
WITH LIME GREEN PINSTRIPE
HAND-PAINTED LINES



BAF.PSRD
8" OPAL GLASS
WITH RED-ORANGE PINSTRIPE
HAND-PAINTED LINES



BAF.PSTL
8" OPAL GLASS
WITH TEAL PINSTRIPE
HAND-PAINTED LINES



BAF.PSBL
8" OPAL GLASS
WITH NAVY BLUE PINSTRIPE
HAND-PAINTED LINES



BASELITE – SCHOOLHOUSE - SPECIFICATION SHEET

PROJECT NAME: _____
PROJECT TYPE: _____

D - MOUNTING OPTIONS

STEM MOUNTS

*STEMS RATED FOR DAMP LOCATION

*CANOPY NOT INCLUDED, ADD IN SECTION D

*AVAILABLE MODELS FOR THE $\frac{1}{4}$ " STEM OPTION

SKT
S2R8



ST(XX) STEM MOUNT- $\frac{1}{4}$ " NPT

XX = LENGTH OF STEM
(EXAMPLE – "ST18" = STEM MOUNT 18" LENGTH)
*CANOPY NOT INCLUDED, ADD IN SECTION E

*AVAILABLE MODELS FOR THE $\frac{1}{2}$ " STEM OPTION

SCP
DLP
FNP



ST(XX) STEM MOUNT- $\frac{1}{2}$ " NPT

XX = LENGTH OF STEM
(EXAMPLE – "ST18" = STEM MOUNT 18" LENGTH)
*CANOPY NOT INCLUDED, ADD IN SECTION E

CORD MOUNTS

*CORDS RATED FOR DRY LOCATION

*CANOPY DIMENSIONS: .625" (H) 5.25" (W)

*AVAILABLE MODELS FOR INC CORD OPTION

SCP
SKT
S2R8



BLC 8' BLACK CORD (INCLUDES INC CANOPY)

WHC 8' WHITE CORD (INCLUDES INC CANOPY)



TCHB 8' BLACK CORD, 3' CHAIN, and LOOP

TCHW 8' WHITE CORD, 3' CHAIN, and LOOP

*MUST USE FOR 18" GLASS OPTION




CBLC 8' BLACK CORD and CABLE

CWLC 8' WHITE CORD and CABLE

*MUST USE FOR 18" GLASS OPTION


E - MOUNTING ADD-ONS

$\frac{1}{2}$ " STEM ADD-ONS



SLC $\frac{1}{2}$ " - SLOPE CEILING CANOPY $\frac{1}{2}$ "

(*Slopes To 20 Degrees)



STC $\frac{1}{2}$ " - STEM MOUNT CANOPY $\frac{1}{2}$ "

G - LIGHT SOURCE

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS.

INCANDESCENT (INC) MED E26

INC 100W(MAX) - SKT, S2R8 (WITH 8" GLASS OPTION)
SCF, SCFS, FNF, DLP, S2R8 (WITH 12" GLASS OPTION)
INC 150W(MAX) - SKT, SCF, SCFS, FNF, DLP, S2R8
(WITH 14" & 16" GLASS OPTION)
INC 200W(MAX) - SCF, SCFS, DLP, SCPL, SCP, SCP
(WITH 18" GLASS OPTION)

*IMPORTANT – FOR INCANDESCENT (INC) LIGHT SOURCE OPTION, FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE RIGHT. EXAMPLE: / INC100W /

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
100WINC	100W	PER BULB SPECS	>90	120-277 VAC	PER BULB SPECS
150WINC	150W	PER BULB SPECS	>90	120-277 VAC	PER BULB SPECS
200WINC	200W	PER BULB SPECS	>90	120-277 VAC	PER BULB SPECS