



BASELITE - DE-DP-DHE-DHP-DPV - CF - SPEC SHEET



PROJECT NAME: _____ PROJECT TYPE: _____

MODEL #	/	/	/	X	/	/	/	/	/	/	/
EXAMPLE:	A	B	C	D	E	F	G	H	I	J	K
	DHE1	41	E18	-	41	12WINC	3K	LDM120	FR3	CG1	41

*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES: **BABA COMPLIANT**



DHE1/52/E18/52/100WINC/FR3/CG1/52

A - SHADES

DE-DHE SERIES

- DE1 - 32WCF (MAX), (3" GLASS), (3" GUARD)
- DE2 - 42WCF (MAX), (4" GLASS), (4" GUARD)
- DHE1 - 32WCF (MAX), (3" GLASS), (3" GUARD)
- DHE2 - 42WCF (MAX), (4" GLASS), (4" GUARD)

DP-DHP SERIES

- DP1 - 32WCF (MAX), (3" GLASS), (3" GUARD)
- DP2 - 42WCF (MAX), (4" GLASS), (4" GUARD)
- DHP1 - 32WCF (MAX), (3" GLASS), (3" GUARD)
- DHP2 - 42WCF (MAX), (4" GLASS), (4" GUARD)

DPV SERIES

- DPV1 - 32WCF (MAX), (3" GLASS), (3" GUARD)
- DPV2 - 42WCF (MAX), (4" GLASS), (4" GUARD)

B - FINISH OPTIONS

(SEE NOTES FOR LIMITATIONS)
 (SEE WEBSITE FOR SWATCH COLORS)
 20, 21, 22, 23, 40, 41, 41.5, 42, 43, 44, 45,
 46, 48, 49, 50, 51, 52, 53, 54, 55, 59, 60,
 61, 62, 63, 70, 71, 72, 73

C - MOUNTING OPTIONS

* ALL FIXTURES COMES AS IS. NO OTHER MOUNTING APPLIES
E18 - COMES STANDARD WITH DE & DHE
STEM MOUNT
 ST6, ST12, ST18, ST24, ST36, ST48, STXX

D - MOUNTING ADD-ONS

CF ADD-ONS
 CFWTM, CFSLC, CFSTC
UNIVERSAL ADD-ONS
 LGSWL

E - MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

F - LIGHT SOURCE

(SEE PAGE 2 FOR WATTAGE LIMITATIONS)
COMPACT FLUORESCENT (CF)
 26W, 32W, 42W

G - LED COLOR TEMP

NOT AVAILABLE

H - ELECTRICAL OPTION

(SEE PAGE 2 FOR DIMMING OPTION SPECIFICATIONS)
CDM120
CDM277
CDM120/277

I - GLASS OPTIONS

3" GLASS
 (AVAILABLE FOR DE1, DHE1, DP1, DHP1, DPV1)
 CL3, CLT3, BL3, RE3, GR3,
 AH3, FR3, FRT3, PR3
4" GLASS
 (AVAILABLE FOR DE2, DHE2, DP2, DHP2, DPV2)
 CL4, CLT4, BL4, RE4, GR4,
 AH4, FR4, FRT4, PR4

J - ACCESSORIES


3" GUARDS
 (AVAILABLE FOR DE1, DHE1, DP1, DHP1, DPV1)
 CG1, WG1
4" GUARDS
 (AVAILABLE FOR DE2, DHE2, DP2, DHP2, DPV2)
 CG2, WG2

K - ACCESSORY COLOR

SEE SECTION "B" FOR COLOR OPTIONS.


NOTES

- (1). FINISH OPTIONS 40, 49, 54, 61, 62, 63, 70, 71, 72, 73 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.
- (2). FINISH OPTIONS FOR SHADES ≤ 10" IN DIAMETER ARE THE SAME INSIDE AND OUT OF FIXTURE. SHADES > 10" IN DIAMETER ARE WHITE ON THE INSIDE.
- (3). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS. *ALL ARMS COME WITH A CAST BACKPLATE (CB1/2", CB3/4", LWTM, CFWTM, ECT.). *ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.) *ALL FIXTURES MOUNT TO A RECESSED 4-0 JUNCTION BOX. *FIXTURE DIMENSIONS MAY VARY ± 0.25. *RATED FOR WET LOCATION.




DE1 H - 11.375" W - 15"

DE2 H - 13.75" W - 16.25"
 3" GLASS & 3" GUARD AVAILABLE FOR DE1
 4" GLASS & 4" GUARD AVAILABLE FOR DE2




DP1 H - 11.375" W - 15"

DP2 H - 13.75" W - 16.25"
 3" GLASS & 3" GUARD AVAILABLE FOR DP1
 4" GLASS & 4" GUARD AVAILABLE FOR DP2




DHE1 H - 11.375" W - 19"

DHE2 H - 13.75" W - 21"
 3" GLASS & 3" GUARD AVAILABLE FOR DHE1
 4" GLASS & 4" GUARD AVAILABLE FOR DHE2



DHP1 H - 11.375" W - 19"

DHP2 H - 13.75" W - 21"
 3" GLASS & 3" GUARD AVAILABLE FOR DHP1
 4" GLASS & 4" GUARD AVAILABLE FOR DHP2



DPV1 H - 4" W - 21.5"

DPV2 H - 55" W - 26.25"
 3" GLASS & 3" GUARD AVAILABLE FOR DPV1
 4" GLASS & 4" GUARD AVAILABLE FOR DPV2



C - MOUNTING OPTIONS

STEM MOUNTS

*STEMS RATED FOR DAMP LOCATION




ST(XX) STEM- 1/2" NPT

XX = LENGTH OF STEM
(EXAMPLE – "ST18" = STEM MOUNT 18" LENGTH)
*CANOPY NOT INCLUDED, ADD IN SECTION D
* 1/4" NPT AND 3/4" NPT AVAILABLE UPON REQUEST


D - MOUNTING ADD-ONS

COMPACT FLUORESCENT STEM AND ARM ADD-ONS

* FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY.



CFWTM WEATHERTIGHT CF WALL MOUNT



CFSLC CF SLOPE CEILING CANOPY




CFSTC CF STEM MOUNT CANOPY

UNIVERSAL STEM AND ARM ADD-ONS

* EXAMPLE FOR MULTIPLE MOUNTING ADD-ONS:

MODEL #: -/-/LWTM, TRB 1/2", LGSWL/-/-/-/-/-/-/-/-
A B C D E F G H I J K



LGSWL 1/2" NPT SWIVEL
For all shades greater than 7" wide in diameter

F – LIGHT SOURCE

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS.

COMPACT FLUORESCENT (CF)

CF 26W, 32W(MAX) - DE1, DHE1, DP1, DHP1, DPV1
CF 26W, 32W, OR 42(MAX) - DE2, DHE2, DP2, DHP2, DPV2

*IMPORTANT – FOR COMPACT FLUORESCENT (CF) LIGHT SOURCE, FIXTURES ARE LIMITED DUE TO THE SIZE OF THE SHADE. PLEASE SEE THE CHART TO THE LEFT TO SEE WHAT WATTAGE IS COMPARABLE FOR EACH FIXTURE WHEN ORDERING.
EXAMPLE: / CF42W /

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
CF26W	26W	PER BULB SPECS	>90	120-277 VAC	See section "H"
CF32W	32W	PER BULB SPECS	>90	120-277 VAC	See section "H"
CF42W	42W	PER BULB SPECS	>90	120-277 VAC	See section "H"



H – ELECTRICAL OPTION

MOST BASELITE'S ELECTRICAL OPTIONS ARE ONLY COMPATIBLE FOR CERTAIN FIXTURES. PLEASE SEE NOTES BELOW AND FOR FURTHER DETAILS CONTACT THE FACTORY. FOR DIMMING BALLAST OPTION, PLEASE CHOOSE MARK X OR MARK VII, SO RESTRICTIONS APPLY DUE TO THE SIZE OF THE BALLAST AND FIXTURE.

COMPACT FLUORESCENT DIMMING OPTIONS

PROVIDED WITH ADVANCE TRANSFORMER, PLEASE CHOOSE MARK 10 OR MARK 7 WITH SPECIFIED VOLTAGE FROM THE LIST BELOW. CONTACT BALLAST MANUFACTURER FOR SPECIFICATIONS.

- CDM7-120/277** - ADVANCE MARK 7 0-10v ELECTRICAL BALLST – 120/277 VOLT
- CDM10-120** - ADVANCE MARK 10 ELECTRICAL BALLST – 120 VOLT
- CDM10-277** - ADVANCE MARK 10 ELECTRICAL BALLST – 277 VOLT

I – GLASS OPTIONS

* 3" GUARDS AVAILIABLE FOR DE1, DHE1, DP1, DHP1, DPV1 *4" GUARDS AVAILIABLE FOR DE2, DHE2, DP2, DHP2, DPV2

*NOTE : GLASS IS HEAT RESISTANCE BOROSILICATE. *TEMPERD GLASS AVAILABLE UPON REQUEST. CONTANCT YOUR LOCAL SALES REPRESENTATIVE FOR INFORMATION OR CALL FACTORY FOR QUESTIONS.



CL3 3" CLEAR GLASS
CL4 4" CLEAR GLASS



PR3 3" PRISMATIC GLASS
PR4 4" PRISMATIC GLASS



RE3 3" RED GLASS
RE4 4" RED GLASS



BL3 3" BLUE GLASS
BL4 4" BLUE GLASS



FR3 3" FROSTED GLASS
FR4 4" FROSTED GLASS




AH3 3" AMBER HYDE GLASS
AH4 4" AMBER HYDE GLASS



GR3 3" GREEN GLASS
GR4 4" GREEN GLASS


GLASS – DIMENSIONS	
3" GLASS	
Diameter	3.34"
Height	6.93"
Fitter	3.29"
4" GLASS	
Diameter	4.34"
Height	8.37"
Fitter	4.29"




GLASS – MAX WATTAGE	
3" GLASS	100W INC / LED12W
4" GLASS	200W INC / LED25W

J – ACCESSORIES


* 3" GUARDS AVAILIABLE FOR DE1, DHE1, DP1, DHP1, DPV1 *4" GUARDS AVAILIABLE FOR DE2, DHE2, DP2, DHP2, DPV2




WG1 3" WIRE GUARD



WG2 4" WIRE GUARD



CG1 3" CAST GUARD



CG2 4" CAST GUARD