



BASELITE - WALL MOUNTS - CF - SPECIFICATION SHEET



PROJECT NAME: _____ PROJECT TYPE: _____

MODEL #	/	/	X	/	X	/	/	/	/	/	X	/
EXAMPLE:	A	B	C	D	E	F	G	H	I	J	K	
	BSM1	41	-	-	41	12WLED	3K	LDM120	FR	-	41	

*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES: **BABA COMPLIANT**



BSM5/48/100WINC/CL

A - SHADES

BSM

- BSM1 - 32WCF (MAX)
- BSM2 - 32WCF (MAX)
- BSM3 - 32WCF (MAX)
- BSM4 - 32WCF (MAX)
- BSM5 - 32WCF (MAX)
- BSM6 - 32WCF (MAX)
- BSM11 - 42WCF (MAX)
- BSM12 - 42WCF (MAX)
- BSM13 - 42WCF (MAX)
- BSM14 - 42WCF (MAX)
- BSM15 - 42WCF (MAX)
- BSM16 - 42WCF (MAX)

B - FINISH OPTIONS

(SEE NOTES FOR LIMITATIONS)
(SEE WEBSITE FOR SWATCH COLORS)
20, 21, 22, 23, 40, 41, 41.5, 42, 43, 44, 45,
46, 48, 49, 50, 51, 52, 53, 54, 55, 59, 60,
61, 62, 63, 70, 71, 72, 73

C - MOUNTING OPTIONS

NOT AVAILABLE

D - MOUNTING ADD-ONS

NOT AVAILABLE

E - MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

F - LIGHT SOURCE

(SEE PAGE 2 FOR WATTAGE LIMITATIONS)
COMPACT FLUORESCENT (CF)
26W, 32W, 42W

G - LED COLOR TEMP

NOT AVAILABLE

H - ELECTRICAL OPTION

(SEE PAGE 2 FOR DIMMING OPTION SPECIFICATIONS)

- CDM120
- CDM277
- CDM120/277

I - GLASS OPTIONS

GLASS
CL, FR

J - ACCESSORIES


NOT AVAILABLE

K - ACCESSORY COLOR

SEE SECTION "B" FOR COLOR OPTIONS.


NOTES

- (1). FINISH OPTIONS 40, 49, 54, 61, 62, 63, 70, 71, 72, 73 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.
- (2). FINISH OPTIONS FOR SHADES $\leq 10"$ IN DIAMETER ARE THE SAME INSIDE AND OUT OF FIXTURE. SHADES $> 10"$ IN DIAMETER ARE WHITE ON THE INSIDE.
- (3). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.
*ALL ARMS COME WITH A CAST BACKPLATE (CB1/2", CB3/4", LWTM, CFWTM, ECT.).
*ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER).
*ALL FIXTURES MOUNT TO A RECESSED 4-O JUNCTION BOX.
*FIXTURE DIMENSIONS MAY VARY ± 0.25 .
*CORD AND CANOPY COME IN THE SAME COLOR.
*RATED FOR WET LOCATION.




BSM1 H - 6.25" W - 10.75"

BSM11 H - 6.25" W - 12.75"




BSM2 H - 6.25" W - 10.75"

BSM12 H - 6.25" W - 12.75"




BSM3 H - 6.25" W - 10.75"

BSM13 H - 6.25" W - 12.75"




BSM4 H - 6.25" W - 10.75"

BSM14 H - 6.25" W - 12.75"



BSM5 H - 6.25" W - 10.75"

BSM15 H - 6.25" W - 12.75"



BSM6 H - 6.25" W - 10.75"

BSM16 H - 6.25" W - 12.75"



F – LIGHT SOURCE

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS.

COMPACT FLUORESCENT (CF)

CF 26W, 32W(MAX) - BSM1, BSM2, BSM3, BSM4, BSM5, BSM6
CF 26W, 32W OR 42W(MAX) - BSM11, BSM12, BSM13, BSM14, BSM15, BSM16

***IMPORTANT** – FOR COMPACT FLUORESCENT (CF) LIGHT SOURCE, FIXTURES ARE LIMITED DUE TO THE SIZE OF THE SHADE. PLEASE SEE THE CHART TO THE LEFT TO SEE WHAT WATTAGE IS COMPARABLE FOR EACH FIXTURE WHEN ORDERING.
EXAMPLE: /CF32W/

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
CF26W	26W	PER BULB SPECS	>90	120-277 VAC	See section "H"
CF32W	32W	PER BULB SPECS	>90	120-277 VAC	See section "H"
CF42W	42W	PER BULB SPECS	>90	120-277 VAC	See section "H"

H – ELECTRICAL OPTION

MOST BASELITE'S ELECTRICAL OPTIONS ARE ONLY COMPATIBLE FOR CERTAIN FIXTURES. PLEASE SEE NOTES BELOW AND FOR FURTHER DETAILS CONTACT THE FACTORY. FOR DIMMING BALLAST OPTION, PLEASE CHOOSE MARK X OR MARK VII, SO RESTRICTIONS APPLY DUE TO THE SIZE OF THE BALLAST AND FIXTURE.

COMPACT FLUORESCENT DIMMING OPTIONS

PROVIDED WITH ADVANCE TRANSFORMER, PLEASE CHOOSE MARK 10 OR MARK 7 WITH SPECIFIED VOLTAGE FROM THE LIST BELOW. CONTACT BALLAST MANUFACTURER FOR SPECIFICATIONS.

- CDM7-120/277** - ADVANCE MARK 7 0-10v ELECTRICAL BALLST – 120/277 VOLT
- CDM10-120** - ADVANCE MARK 10 ELECTRICAL BALLST – 120 VOLT
- CDM10-277** - ADVANCE MARK 10 ELECTRICAL BALLST – 277 VOLT

I – GLASS OPTIONS

* GLASS SIZE COMES STANDARD WITH CHOSEN SHADE. ONLY GLASS TRANSPARENCY CAN BE CHOSEN. * SMALL GLASS ONLY AVAILABLE FOR BSM1 – 6. * LARGE GLASS ONLY AVAILABLE FOR BSM11 - 16



GLASS – DIMENSIONS	
SMALL GLASS	
Diameter	4.25"
Height	6.25"
Fitter	5.25"
LARGE GLASS	
Diameter	4.25"
Height	8.5"
Fitter	5.25"