



BASELITE - WALL MOUNTS - INC - SPECIFICATION SHEET



PROJECT NAME: _____ PROJECT TYPE: _____

MODEL #	/	/	X	/	X	/	/	/	/	/	X	/
EXAMPLE:	A	B	C	D	E	F	G	H	I	J	K	
	BSM1	41	-	-	41	12WLED	3K	LDM120	FR	-	41	

*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES: **BABA COMPLIANT**



BSM5/48/100WINC/CL

A - SHADES

BSM

- BSM1 - 100WINC (MAX)
- BSM2 - 100WINC (MAX)
- BSM3 - 100WINC (MAX)
- BSM4 - 100WINC (MAX)
- BSM5 - 100WINC (MAX)
- BSM6 - 100WINC (MAX)
- BSM11 - 200WINC (MAX)
- BSM12 - 200WINC (MAX)
- BSM13 - 200WINC (MAX)
- BSM14 - 200WINC (MAX)
- BSM15 - 200WINC (MAX)
- BSM16 - 200WINC (MAX)

B - FINISH OPTIONS

(*SEE NOTES FOR LIMITATIONS*)
 (SEE WEBSITE FOR SWATCH COLORS)
 20, 21, 22, 23, 40, 41, 41.5, 42, 43, 44, 45,
 46, 48, 49, 50, 51, 52, 53, 54, 55, 59, 60,
 61, 62, 63, 70, 71, 72, 73

C - MOUNTING OPTIONS

NOT AVAILABLE

D - MOUNTING ADD-ONS

NOT AVAILABLE

E - MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

F - LIGHT SOURCE

(SEE PAGE 2 FOR WATTAGE LIMITATIONS)
INCANDESCENT (INC)
 100W, 200W

G - LED COLOR TEMP

NOT AVAILABLE

H - ELECTRICAL OPTION

NOT AVAILABLE

I - GLASS OPTIONS

GLASS
 CL, FR

J - ACCESSORIES


NOT AVAILABLE

K - ACCESSORY COLOR


SEE SECTION "B" FOR COLOR OPTIONS.

NOTES


- (1). FINISH OPTIONS 40, 49, 54, 61, 62, 63, 70, 71, 72, 73 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.
 - (2). FINISH OPTIONS FOR SHADES ≤ 10" IN DIAMETER ARE THE SAME INSIDE AND OUT OF FIXTURE. SHADES > 10" IN DIAMETER ARE WHITE ON THE INSIDE.
 - (3). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.
- *ALL ARMS COME WITH A CAST BACKPLATE (CB1/2", CB3/4", LWTM, CFWTM, ECT.).
 - *ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.).
 - *ALL FIXTURES MOUNT TO A RECESSED 4-O JUNCTION BOX.
 - *FIXTURE DIMENSIONS MAY VARY ± 0.25.
 - *CORD AND CANOPY COME IN THE SAME COLOR.
 - *RATED FOR WET LOCATION.




BSM1 H - 6.25" W - 9.25"
BSM11 H - 6.25" W - 11.25"




BSM2 H - 6.25" W - 9.25"
BSM12 H - 6.25" W - 11.25"




BSM3 H - 6.25" W - 9.25"
BSM13 H - 6.25" W - 11.25"



BSM4 H - 6.25" W - 9.25"
BSM14 H - 6.25" W - 11.25"



BSM5 H - 6.25" W - 9.25"
BSM15 H - 6.25" W - 11.25"



BSM6 H - 6.25" W - 9.25"
BSM16 H - 6.25" W - 11.25"



F – LIGHT SOURCE

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

COMPACT FLUORESCENT (CF)

INC 100W(MAX) - BSM1, BSM2, BSM3, BSM4, BSM5, BSM6
INC 200W (MAX) - BSM11, BSM12, BSM13, BSM14, BSM15, BSM16

***IMPORTANT** – FOR COMPACT FLUORESCENT (CF) LIGHT SOURCE, FIXTURES ARE LIMITED DUE TO THE SIZE OF THE SHADE. PLEASE SEE THE CHART TO THE LEFT TO SEE WHAT WATTAGE IS COMPARABLE FOR EACH FIXTURE WHEN ORDERING. **EXAMPLE:** / INC100W /

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
INC100W	100W	PER BULB SPECS	>90	120-277 VAC	N/A
INC200W	200W	PER BULB SPECS	>90	120-277 VAC	N/A

***FIXTURE WATTAGE CAN BE DE-RATED TO MEET CODE COMPLIANCE "CFXXW" – XX = DESIRED WATTAGE RATING BELOW MAX.**

I – GLASS OPTIONS

* GLASS SIZE COMES STANDARD WITH CHOSEN SHADE. ONLY GLASS TRANSPARENCY CAN BE CHOSEN. * SMALL GLASS ONLY AVAILABLE FOR BSM1 – 6. * LARGE GLASS ONLY AVAILABLE FOR BSM11 - 16



CL CLEAR SMALL GLASS



FR FROSTED SMALL GLASS



CL CLEAR LARGE GLASS



FR FROSTED LARGE GLASS

