



BASELITE – WIRE PENDANTS – MED – SPEC SHEET



PROJECT NAME: _____ PROJECT TYPE: _____

| MODEL # | / | / | / | / | / | / | X | X | X | X | X |
|----------|-----|----------|-----|-----|----|--------|---|---|---|---|---|
| | A | B | C | D | E | F | G | H | I | J | K |
| EXAMPLE: | 3TD | 80-59-81 | BLC | CNK | 41 | 150INC | | | | | |

*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES: **BABA COMPLIANT**



A - SHADES

WIRE PENDANTS

- GHM8** - 150W (MAX)
- PEHD615** - 150W (MAX)
- WRO** - 150W (MAX)
- WRO1** - 150W (MAX)
- WRO2** - 150W (MAX)
- WDM14** - 100W (MAX)
- ON16** - 100W (MAX)
- WDMD12** - 150W (MAX)

B - FINISH OPTIONS

(SEE WEBSITE FOR SWATCH COLORS)
 (*SEE NOTES FOR LIMITATIONS*)
 14, 15, 16, 17, 18, 19, 19P, 20, 20P,
 20PB, 20SB, 21, 21P, 22, 22P, 23, 23P,
 38, 39, 40, 41, 41.5, 42, 43, 44, 45, 46,
 48, 49, 50, 51, 52, 53, 54, 55, 57, 58, 59,
 60, 61, 62, 63, 64, 65, 66, 70, 71, 72, 73,
 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84,
 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95,
 96, 97, 98, 99, 100, MG.

C – MOUNTING OPTIONS

CORD MOUNT

MBC, MWC, MTCB, MTCW, MTCHB, MTCHW,
 MTLB, MTLW, MRCB, MRCW, MRCHB,
 MRCHW, MFHW, MFHW, MCBLC, MCWLC,
 MCHB, MCHW

STEM MOUNT

ST6, ST12, ST18, ST24, ST36, ST48, STXX

D – MOUNTING ADD-ONS

ADD-ONS

CNK – MULTIPLE FIXTURE CANOPY
 STC – STEM MOUNT CANOPY
 SLC1/2" – SLOPE CEILING CANOPY ½"

E – MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

F – LIGHT SOURCE

(SEE PAGE 3 FOR WATTAGE LIMITATIONS)

MEDIUM BASE (MED) E26

100w, 150W, 200W

G – LED COLOR TEMP

NOT AVAILABLE

H – ELECTRICAL OPTION

NOT AVAILABLE

I – GLASS OPTIONS

CALL FACTORY FOR REQUEST.

J – ACCESSORIES


CALL FACTORY FOR REQUEST.

K – ACCESSORY COLOR


SEE SECTION "B" FOR COLOR OPTIONS.

NOTES


- (1). FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY.
 - (2). FINISH OPTIONS 19, 21, 22, 23, 75, 76, 77, 83, 84, 88, 93 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.
 - (3). FINISH OPTIONS FOR SHADES ≤ 10" IN DIAMETER ARE THE SAME INSIDE AND OUT OF FIXTURE. SHADES > 10" IN DIAMETER ARE WHITE ON THE INSIDE.
 - (4). FINISH OPTIONS 19, 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.
 - (5). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.
 - (5). COLOR CORDS ARE NOT APPLICABLE FOR LED OPTIONS.
- *ALL FIXTURES MOUNT TO A 4-O JUNCTION BOX.
 *FIXTURE DIMENSIONS MAY VARY ±0.25.




GHM8 H-10.5" W-8"




WDM14 H-8.75" W-14"




PEHD615 H-19" W-15"



ON16 H-11.75" W-16"




WRO H-13" W-22"



WDMD12 H-12.75" W-11.75"



WRO1 H-21.25" W-10.75"



WRO2 H-15" W-35"



BASELITE – WIRE PENDANTS – MED – SPEC SHEET

PROJECT NAME: _____ PROJECT TYPE: _____

C - MOUNTING OPTIONS

D - MOUNTING ADD-ONS

STEM MOUNT

*STEMS RATED FOR DAMP LOCATION * 1/4" NPT AND 3/4" NPT AVAILABLE UPON REQUEST




ST(XX) STEM MOUNT - 1/2" NPT
 XX = LENGTH OF STEM
 (EXAMPLE – "ST18" = STEM MOUNT 18" LENGTH)
 *CANOPY NOT INCLUDED, ADD IN SECTION D


MOUNTING ADD-ON



CNK CANOPY For MULTIPLE FIXTURES
 *CNK dimensions vary on number of fixtures applied



SLC 1/2" SLOPE CEILING CANOPY 1/2"
 *(Slopes To 20 Degrees)



STC 1/2" 1/2" STEM MOUNT CANOPY

CORD MOUNTS

MAX WATTAGE 150 WATT. CALL FACTORY FOR HIGHER WATTAGES. *CORDS RATED FOR DRY LOCATION *CANOPY DIMENSIONS: 2.5" (H) 5.875" (W)



MBC 8' BLACK CORD
MWC 8' WHITE CORD




MTCB 8' BLACK CORD, CABLE, and LOOP
MTCW 8' WHITE CORD, CABLE, and LOOP



MTCHB 8' BLACK CORD, 3' CHAIN, and LOOP
MTCHW 8' WHITE CORD, 3' CHAIN, and LOOP



MTLB 8' BLACK TELEPHONE CORD AND CABLE
MTLW 8' WHITE TELEPHONE CORD AND CABLE



MRCB 8' BLACK CORD, CABLE, and LOOP
MRCW 8' WHITE CORD, CABLE, and LOOP



MRCHB 8' BLACK CORD, 3' CHAIN, and LOOP
MRCHW 8' WHITE CORD, 3' CHAIN, and LOOP



MFHB 8' BLACK CORD WITH FLAT HUB
MFHW 8' WHITE CORD WITH FLAT HUB



MCBLC 8' BLACK CORD and CABLE
MCWLC 8' WHITE CORD and CABLE



MCHB 8' BLACK CORD, 3' CHAIN, and LOOP
MCHW 8' WHITE CORD, 3' CHAIN, and LOOP
 * Loop may vary due to shade style

F – LIGHT SOURCE

MEDIUM BASE (MED) E26

100W (MAX) – ON16, WDM14
150W (MAX) – GHM8, PEHD615, WRO, WRO1, WRO2, WDMD12

*IMPORTANT – FOR LIGHT EMITTED DIODE (LED) LIGHT SOURCE OPTION, FIXTURES ARE LIMITED DUE TO SIZE OF THE SIZE OF THE DRIVER. E FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE LEFT. **EXAMPLE: / MED150W /**

| OPTION | WATTAGE | LUMENS | CRI | VOLTAGE | DIMMING |
|---------|---------|----------------|-----|-------------|---------|
| MED100W | 100W | PER BULB SPECS | >90 | 120-277 VAC | N/A |
| MED150W | 150W | PER BULB SPECS | >90 | 120-277 VAC | N/A |