



BASELITE – OPAL BALL – MED – SPECIFICATION



PROJECT NAME: _____ PROJECT TYPE: _____

MODEL #	/	/	/	/	/	/	X	X	X	X	X
	A	B	C	D	E	F	G	H	I	J	K
EXAMPLE:	W513	41	E16	SQ 1/2"	43	100W					

*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES: **BABA COMPLIANT**



A - SHADES

- OPAL BALL (ACRYLIC)**
2OB8 - 60W (MAX)
5OB8RB - 60W (MAX)
HDOB12 - 100W (MAX)
OB8 - 60W (MAX)
OBW8 - 60W (MAX)
OB10 - 100W (MAX)
OBR10 - 100W (MAX)
OB12 - 100W (MAX)
OB14 - 150W (MAX)
OB16 - 150W (MAX)
OB18 - 150W (MAX)
OB20 - 200W (MAX)
OB22 - 200W (MAX)
OB24 - 200W (MAX)
OBF10 - 60W (MAX)
SGOB6 - 60W (MAX)

B - FINISH OPTIONS

- (SEE WEBSITE FOR SWATCH COLORS)
 (*SEE NOTES FOR LIMITATIONS*)
 14, 15, 16, 17, 18, 19, 19P, 20, 20P, 20PB, 20SB, 21, 21P, 22, 22P, 23, 23P, 38, 39, 40, 41, 41.5, 42, 43, 44, 45, 46, 48, 49, 50, 51, 52, 53, 54, 55, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, MG.

C - MOUNTING OPTIONS

- STEM MOUNT**
 DP24, DWM, ST6, ST12, ST18, ST24, ST36, ST48, STXX
CORD MOUNT
 MCB, MCW, MTCB, MTCW, MTCHB, MTCHW, MRCB, MRCW, MRCHB, MRCHW, MCHB, MCHW
WALL MOUNT
 WM17, WM21

D - MOUNTING ADD-ONS

- INC ADD-ONS**
 SLC1/2", SLC3/4", STC1/2"
UNIVERSAL ADD-ONS
 CNK

E - MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

F - LIGHT SOURCE

(SEE PAGE 4 FOR WATTAGE LIMITATIONS)
MEDIUM BASE (MED) E26
 60W, 100W, 150W, 200W

G - LED COLOR TEMP

NOT AVAILABLE

H - ELECTRICAL OPTION

NOT AVAILABLE

I - GLASS OPTIONS

NOT AVAILABLE

J - ACCESSORIES

NOT AVAILABLE


K - ACCESSORY COLOR

NOT AVAILABLE

NOTES


- (1). FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY.
- (2). FINISH OPTIONS 19, 21, 22, 23, 75, 76, 77, 83, 84, 88, 93 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.
- (3). FINISH OPTIONS 19, 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.
- (4). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.
- (5). COLOR CORDS ARE NOT APPLICABLE FOR LED OPTIONS.
 *ALL FIXTURES MOUNT TO A RECESSED 4-O JUNCTION BOX.
 *FIXTURE DIMENSIONS MAY VARY ± 0.25.
- (6). MATERIAL – ACRYLIC OPAL BALL
 *LARGER OPLA BALL SIZES AVAILABLE UPON REQUEST. UP TO 36". THESE SIZES ARE CUSTOM MADE. CALL FACTORY FOR DETAILS.

SHADE DIMENSIONS



2OB8	16"	16" TO 27.75"
-------------	-----	---------------

*FIXTURE COMES AS SHOWN
 *OTHER MOUNTING OPTIONS DO NOT APPLY. MAX OPAL BALL 16".




SGOB6	12"	10"
--------------	-----	-----

*FIXTURE COMES AS SHOWN
 *OTHER MOUNTING OPTIONS DO NOT APPLY.




OBR10	22"	10"
--------------	-----	-----

*FIXTURE COMES AS SHOWN
 *OTHER MOUNTING OPTIONS DO NOT APPLY.




OBW8	12"	10"
-------------	-----	-----

*FIXTURE COMES AS SHOWN
 *OTHER MOUNTING OPTIONS DO NOT APPLY.




	HEIGHT	WIDTH
OB8	8"	8"
OB10	10"	10"
OB12	12"	12"
OB14	14"	14"
OB16	16"	16"
OB18	18"	18"
OB20	20"	20"
OB22	22"	22"
OB24	24"	24"



	HEIGHT	WIDTH
OBF10	11"	9.5"

*FIXTURE COMES AS SHOWN
 *OTHER MOUNTING OPTIONS DO NOT APPLY.



	HEIGHT	WIDTH
HDOB12	12"	12"




C - MOUNTING OPTIONS

STEM MOUNTS


*STEMS RATED FOR DAMP LOCATION

*DP24 COMES STANDARD WITH STC AND ST18

*1/4" NPT AND 3/4" NPT AVAILABLE UPON REQUEST



DP24 DOUBLE PENDANT



DWM DOUBLE WALL MOUNT
*MAX OPAL BALL 16"



ST(XX) - STEM- 1/2" NPT

CORD MOUNTS


*MAX WATTAGE 150 WATT.

*CORDS RATED FOR DRY LOCATION

*CANOPY DIMENSIONS: .625" (H) 5.25"(W)



MCB 8' BLACK CORD
MCW 8' WHITE CORD



TCB 8' BLACK CORD, CABLE, and LOOP
TCW 8' WHITE CORD, CABLE, and LOOP



TCHB 8' BLACK CORD, 3' CHAIN, and LOOP
TCHW 8' WHITE CORD, 3' CHAIN, and LOOP



RCB 8' BLACK CORD, CABLE, and LOOP
RCW 8' WHITE CORD, CABLE, and LOOP




RCHB 8' BLACK CORD, 3' CHAIN, and LOOP
RCHW 8' WHITE CORD, 3' CHAIN, and LOOP




CHB 8' BLACK CORD, 3' CHAIN, and LOOP
CHW 8' WHITE CORD, 3' CHAIN, and LOOP
* Loop may vary due to shade style

WALL MOUNT




WM17 HEIGHT 11" WIDTH 10.5"



WM21 HEIGHT 4.75" WIDTH 8.5"

D - MOUNTING ADD-ONS

STEM ADD-ONS



SLC 1/2" SLOPE CEILING CANOPY 1/2"
SLC 3/4" SLOPE CEILING CANOPY 3/4"
*(Slopes to 20)



STC 1/2" 1/2" STEM MOUNT CANOPY



D - MOUNTING ADD-ONS (CONTINUED)

UNIVERSAL STEM AND ARM ADD-ONS



CNK CANOPY For MULTIPLE FIXTURES

*CNK dimensions vary on number of fixtures applied

F – LIGHT SOURCE

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

MEDIUM BASE (MED) E26

60W (MAX)- 5OB8RB, 2OB8, OB8, OBW8, OBF8, SGOB6
100W (MAX)- HD0B12, OB10, OBR10, OB12
150W (MAX)- OB14, OB16, OB18
200W (MAX)- OB20, OB22, OB24

***IMPORTANT** – FOR LIGHT EMITTED DIODE (LED) LIGHT SOURCE OPTION FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE AVAILABILITY CHART TO THE LEFT. EXAMPLE: / MED150W /

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
MED60W	60W	PER BULB SPECS	>90	120-277 VAC	N/A
MED100W	100W	PER BULB SPECS	>90	120-277 VAC	N/A
MED150W	150W	PER BULB SPECS	>90	120-277 VAC	N/A
MED200W	200W	PER BULB SPECS	>90	120-277 VAC	N/A