




BASELITE – BULKHEADS – CF – SPECIFICATION SHEET



PROJECT NAME: _____ PROJECT TYPE: _____

MODEL # / / x / x / x / / / x / / x / x / x

EXAMPLE: BLH1 41 - - - 25W 3K - FR9 - -

*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES: **BABA COMPLIANT**



BLH3/CL9/44/100INC

A – SHADES

BLH SERIES

BLH1 - 42WCF (MAX)
BLH2 - 42WCF (MAX)
BLH3 - 42WCF (MAX)
BLH4 - 42WCF (MAX)
BLHB1 - 42WCF (MAX)
BLHB2 - 42WCF (MAX)
BLHB3 - 42WCF (MAX)
BLHB4 - 42WCF (MAX)

B – FINISH OPTIONS

(SEE WEBSITE FOR SWATCH COLORS)
 (*SEE NOTES FOR LIMITATIONS*)
 14, 15, 16, 17, 18, 19, 19P, 20, 20P, 20PB,
 20SB, 21, 21P, 22, 22P, 23, 23P, 38, 39, 40,
 41, 41.5, 42, 43, 44, 45, 46, 48, 49, 50, 51,
 52, 53, 54, 55, 57, 58, 59, 60, 61, 62, 63, 64,
 65, 66, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79,
 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91,
 92, 93, 94, 95, 96, 97, 98, 99, 100, MG.

C – MOUNTING OPTIONS

NOT AVAILABLE

D – MOUNTING ADD-ONS

NOT AVAILABLE

E – MOUNTING COLOR

NOT AVAILABLE

F – LIGHT SOURCE

(SEE PAGE 2 FOR WATTAGE LIMITATIONS)
COMPACT FLUORESCENT (CF)
 26W, 32W, 42W

G – LED COLOR TEMP

NOT AVAILABLE

H – ELECTRICAL OPTION

NOT AVAILABLE

I – ACRYLIC OPTIONS

CL – CLEAR PRISMATIC LENSE
FR – FROSTED PRISMATIC LENSE
OPAL – OPAL LENSE

J – ACCESSORIES

NOT AVAILABLE


K – ACCESSORY COLOR

NOT AVAILABLE


NOTES

- (1). FINISH OPTIONS 75, 76, 77, 83, 84, 88, 93 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.
- (2). FINISH OPTIONS 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.
- (3). FINISH OPTIONS FOR SHADES $\leq 10"$ IN DIAMETER ARE THE SAME INSIDE AND OUT OF FIXTURE. SHADES $> 10"$ IN DIAMETER ARE WHITE ON THE INSIDE.
- (4). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.
- (5). COLOR CORDS ARE NOT APPLICABLE FOR LED OPTIONS.
 *ALL ARMS COME WITH A CAST BACKPLATE (CB1/2", CB3/4", LWTM, CFWTM, ECT.).
 *ACCORDING TO THE LIGHT SOURCE THE BACKPLATE MAY VARY IN SIZE. (EXAMPLE: LED LIGHT SOURCE WILL HAVE A DEEPER BACKPLATE TO HOUSE THE DRIVER.).
 *ALL FIXTURES MOUNT TO A 4-O JUNCTION BOX.
 *FIXTURE DIMENSIONS MAY VARY ± 0.25 .
 *RATED FOR WET LOCATION.


*D = DIAMETER PROJ = PROJECTION




BLH1 D-15" PROJ.-5.75"




BLH2 D - 15" PROJ. - 6"




BLH3 D - 15" PROJ. - 6.5"




BLH4 D - 15" PROJ. - 7"




BLHB1 D - 10" PROJ. - 4"



BLHB2 D - 10" PROJ. - 4"



BLHB3 D - 10" PROJ. - 4"



BLHB4 D - 10" PROJ. - 4"



F – LIGHT SOURCE

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

COMPACT FLUORESCENT (CF)

CF 26W, 32W, OR 42(MAX) - BLH1, BLH2, BLH3, BLH4, BLHB1, BLHB2, BLHB3, BLHB4

***IMPORTANT** – FOR COMPACT FLUORESCENT (CF) LIGHT SOURCE, FIXTURES ARE LIMITED DUE TO THE SIZE OF THE SHADE. PLEASE SEE THE CHART TO THE LEFT TO SEE WHAT WATTAGE IS COMPARABLE FOR EACH FIXTURE WHEN ORDERING.

EXAMPLE: / CF42W /

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
CF26W	26W	PER BULB SPECS	>90	120-277 VAC	N/A
CF32W	32W	PER BULB SPECS	>90	120-277 VAC	N/A
CF42W	42W	PER BULB SPECS	>90	120-277 VAC	N/A

I – ACRYLIC OPTIONS



EX: BLH3.**CL9**.44.100INC

CL9 9" CLEAR PRISMATIC LENSE



EX: BLH1.**FR9**.41.100INC

FR9 9" FROSTED LENSE



EX: BLH4.**OPAL**.53.100INC

OPAL OPAL LENSE

MODEL	CLEAR	FROSTED	OPAL
BLH1	YES	YES	YES
BLH2	YES	YES	YES
BLH3	YES	YES	YES
BLH4	NO	NO	YES
BLHB1	YES	YES	YES
BLHB2	YES	YES	YES
BLHB3	YES	YES	YES
BLHB4	YES	YES	YES