



BASELITE – OPAL BALL – LED – SPECIFICATION SHEET



PROJECT NAME: _____ PROJECT TYPE: _____

MODEL #	/	/	/	/	/	/	/	/	/	X	/	X	/	X
	A	B	C	D	E	F	G	H	I	J	K			
EXAMPLE:	W513	41	E16	SQ 1/2"	43	100W	3K	LDM120	-	-	-			

*SKIP SECTION IF OPTION DOES NOT APPLY

NOTES: **BABA COMPLIANT**



2OB8/2OP/DWM/2OP/2-60INC

A - SHADES

OPAL BALL (ACRYLIC)

OB8 - 10WLED (MAX)
OBW8 - 10WLED (MAX)
OB10 - 10WLED (MAX)
OB10 - 10WLED (MAX)
OB12 - 25WLED (MAX)
OB14 - 25WLED (MAX)
OB16 - 25WLED (MAX)
OB18 - 25WLED (MAX)
OB20 - 25WLED (MAX)
OB22 - 25WLED (MAX)
OB24 - 25WLED (MAX)
2OB8 - 10WLED (MAX)
OBF10 - 10WLED (MAX)

B - FINISH OPTIONS

(SEE WEBSITE FOR SWATCH COLORS)
 (*SEE NOTES FOR LIMITATIONS*)
 14, 15, 16, 17, 18, 19, 19P, 20, 20P, 20PB, 20SB, 21, 21P, 22, 22P, 23, 23P, 38, 39, 40, 41, 41.5, 42, 43, 44, 45, 46, 48, 49, 50, 51, 52, 53, 54, 55, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, MG.

C - MOUNTING OPTIONS

LED CORD MOUNT

LBLC, LWHC, LTCB, LTCW, LTCHB, LTCHW, LTLB, LTLW, LTLB, LTLW, LRCB, LRCW, LRCHB, LRCHW, LFHB, LFHW, LHBLC, LHWHC, LCBL, LCWHC, LCHB, LCHW

STEM MOUNT

DP24, DWM, ST6, ST12, ST18, ST24, ST36, ST48, STXX

WALL MOUNT

WM17X, WM21X

D - MOUNTING ADD-ONS

INC ADD-ONS

LSLC1/2", LSLC3/4", LSTC1/2"

UNIVERSAL ADD-ONS

LCNK

E - MOUNTING COLOR

SEE SECTION "B" FOR COLOR OPTIONS.

F - LIGHT SOURCE

(SEE PAGE 3 FOR WATTAGE LIMITATIONS)

LIGHT EMITTED DIODE (LED)

10W, 12W, 25W

*NOTE - MAX WATTAGE IS LISTED NEXT TO THE SHADE MODEL NUMBER IN SECTION "A". ALL WATTAGES BELOW THAT ARE ALSO AVAILABLE FOR THE SAME MODEL NUMBER.

G - LED COLOR TEMP

27K - 2700 KELVIN
3K - 3000 KELVIN
35K - 3500 KELVIN
4K - 4000 KELVIN
5K - 5000 KELVIN

H - ELECTRICAL OPTION

(SEE PAGE 3 FOR DIMMING OPTION SPECIFICATIONS)

LDM120

LDM0-10W

I - GLASS OPTIONS

NOT AVAILABLE

J - ACCESSORIES

NOT AVAILABLE

K - ACCESSORY COLOR

NOT AVAILABLE

NOTES

(1). FINISH OPTIONS 20, 21, 22, 23 ARE FOR SOLID BRASS FIXTURES ONLY.

(2). FINISH OPTIONS 19, 21, 22, 23, 75, 76, 77, 83, 84, 88, 93 AND 98 ARE APPLIED BY HAND. THESE FINISHES WILL VARY IN CONSISTENCY.

(3). FINISH OPTIONS 19, 38, 39, 40, 49, 54, 57, 58, 61, 62, 63, 70, 71, 72, 73, 78, 83, 84, 88, 92, 93, 98 ONLY AVAILABLE INSIDE AND OUT OF FIXTURE. OTHER FINISHES ARE WHITE INSIDE.

(4). FINISH OPTIONS 61, 62, 70, 71, 72, 73 ARE FINISHED WITH A SUPERCHROME ON THE INSIDE FOR ALL LED LIGHT SOURCE OPTIONS.


(5). COLOR CORDS ARE NOT APPLICABLE FOR LED OPTIONS.

*ALL FIXTURES MOUNT TO A 4-0 JUNCTION BOX.


*FIXTURE DIMENSIONS MAY VARY ± 0.25.

(6). MATERIAL - ACRYLIC OPAL BALL

*LARGER SIZES AVAILABLE UPON REQUEST. UP TO 36". THESE SIZES ARE CUSTOM MADE. CALL FACTORY FOR DETAILS.




	HEIGHT	WIDTH
OB8	8"	8"
OB10	10"	10"
OB12	12"	12"
OB14	14"	14"
OB16	16"	16"
OB18	18"	18"
OB20	20"	20"
OB22	22"	22"
OB24	24"	24"




	HEIGHT	WIDTH
2OB8	16"	16" TO 27.75"

*FIXTURE COMES AS SHOWN


*OTHER MOUNTING OPTIONS DO NOT APPLY




	HEIGHT	WIDTH
SCPGOB12	16"	13.5"



	HEIGHT	WIDTH
OBF10	11"	9.5"



	HEIGHT	WIDTH
OBR10	22"	10"




	HEIGHT	WIDTH
OBW8	12"	8"




C - MOUNTING OPTIONS

STEM MOUNTS


*STEMS RATED FOR DAMP LOCATION *DP24 COMES STANDARD WITH STC AND ST18 *3/4" NPT AVAILABLE UPON REQUEST



DP24 - DOUBLE PENDANT



DWM - DOUBLE WALL MOUNT



STQ(XX) - STEM- 1/4" NPT

ST(XX) - STEM- 1/2" NPT

XX = LENGTH OF STEM

(EXAMPLE - "ST18" = STEM MOUNT 18" LENGTH)

*CANOPY NOT INCLUDED, ADD IN SECTION D

L.E.D. CORD MOUNTS


*FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY. *CORDS RATED FOR DRY LOCATION

*CANOPY DIMENSIONS: 4" (H) 5.5" (W) *CORD AND CANOPY COME IN THE SAME COLOR.



LBLC 8' BLACK CORD

LWHC 8' WHITE CORD



LTCB 8' BLACK CORD, CABLE, and LOOP

LTCW 8' WHITE CORD, CABLE, and LOOP




LTCHB 8' BLACK CORD, 3' CHAIN, and LOOP

LTCHW 8' WHITE CORD, 3' CHAIN, and LOOP



LTLB 8' BLACK TELEPHONE CORD AND CABLE

LTLW 8' WHITE TELEPHONE CORD AND CABLE



LRCB 8' BLACK CORD, CABLE, and LOOP

LRCW 8' WHITE CORD, CABLE, and LOOP



LRCHB 8' BLACK CORD, 3' CHAIN, and LOOP

LRCHW 8' WHITE CORD, 3' CHAIN, and LOOP



LFHB 8' BLACK CORD WITH FLAT HUB

LFHW 8' WHITE CORD WITH FLAT HUB



LCBLC 8' BLACK CORD and CABLE

LCWHC 8' WHITE CORD and CABLE




LCHB 8' BLACK CORD, 3' CHAIN, and LOOP


LCHW 8' WHITE CORD, 3' CHAIN, and LOOP

* Loop may vary due to shade style

L.E.D. WALL MOUNT



WM17X HEIGHT 11" WIDTH 12.25"




WM21X HEIGHT 4.75" WIDTH 9.5"

D - MOUNTING ADD-ONS

L.E.D. STEM ADD-ONS

* FOR LED & COMPACT FLUORESCENT OPTIONS, CANOPIES WILL VARY IN SIZE DUE TO SIZE OF THE DRIVER/BALLAST THAT WILL BE LOCATED INSIDE OF THE CANOPY.



LSLC 1/2" SLOPE CEILING CANOPY 1/2"

LSLC 3/4" SLOPE CEILING CANOPY 3/4"
(Slopes to 20 Degrees)



LSTC 1/2" 1/2" STEM MOUNT CANOPY



D - MOUNTING ADD-ONS (CONTINUED)

UNIVERSAL STEM AND ARM ADD-ONS



LCNK CANOPY For MULTIPLE FIXTURES

*CNK dimensions vary on number of fixtures applied

F – LIGHT SOURCE

BASELITE'S PUBLISHED LUMINAIRE PHOTOMETRIC TESTING WAS PERFORMED IN A 3-METER INTEGRATING SPHERE USING THE 4TT GEOMETRY METHOD. DATA IS CONSIDERED TO BE REPRESENTATIVE OF THE CONFIGURATIONS SHOWN, WITHIN THE TOLERANCES ALLOWED BY LIGHTING FACTS. TO OBTAIN AN IES FILE SPECIFIC TO YOUR PROJECT, PLEASE CONTACT THE FACTORY.

LIGHT EMITTING DIODE (LED)

LED 10W (MAX)- OB8, OBW8, 2OB8, OB10, OBF10, OBR10
LED 25W (MAX)- OB12, OB14, OB16, OB18, OB20, OB22, OB24

***IMPORTANT** – FOR LIGHT EMITTED DIODE (LED) LIGHT SOURCE OPTION, FIXTURES ARE LIMITED DUE TO SIZE OF THE FIXTURE AND THE CORD WATTAGE RESTRICTIONS. PLEASE SEE MAX WATTAGE AVAILABILITY. **EXAMPLE: / LED25W /**

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
LED10WF	10W	1280	>90	120-277 VAC	TRI-ELV *120V ONLY
LED12W	12W	1481	>90	120-277 VAC	See section "H"
LED25W	25W	2812	>90	120-277 VAC	See section "H"

@3500K

H – ELECTRICAL OPTION

MOST BASELITE'S ELECTRICAL OPTIONS ARE ONLY COMPATIBLE FOR CERTAIN FIXTURES. PLEASE SEE NOTES BELOW AND FOR FURTHER DETAILS CONTACT THE FACTORY.

LED DIMMING OPTIONS

(LED10WF – ONLY AVAILABLE WITH **LDM120** - TRI-ELV DIMMING OPITON) ALL OTHER WATTAGES CAN CHOOSE FROM THE OPTIONS BELOW. CONTACT DRIVER MANUFACTURER FOR FURTHER SPECIFICATIONS.

LDM120 - TRIAC / ELV – INPUT 120 / 277V - DIMMING AT 120 VOLT ONLY

LDM0-10V – 0 – 10V – DIMMING AT 120 / 277 VOLTS